
CGPath Reference

[Graphics & Imaging](#) > Quartz



2006-12-22



Apple Inc.
© 2003, 2006 Apple Computer, Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Mac, Mac OS, and Quartz are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

CGPath Reference 5

Overview	5
Functions by Task	5
Creating and Managing Paths	5
Modifying Quartz Paths	6
Getting Information about Quartz Paths	6
Functions	7
CGPathAddArc	7
CGPathAddArcToPoint	8
CGPathAddCurveToPoint	9
CGPathAddEllipseInRect	10
CGPathAddLines	11
CGPathAddLineToPoint	11
CGPathAddPath	12
CGPathAddQuadCurveToPoint	12
CGPathAddRect	13
CGPathAddRects	14
CGPathApply	15
CGPathCloseSubpath	15
CGPathContainsPoint	16
CGPathCreateCopy	16
CGPathCreateMutable	17
CGPathCreateMutableCopy	17
CGPathEqualToPath	18
CGPathGetBoundingBox	18
CGPathGetCurrentPoint	18
CGPathGetTypeID	19
CGPathsIsEmpty	19
CGPathsIsRect	20
CGPathMoveToPoint	20
CGPathRelease	21
CGPathRetain	21
Callbacks	22
CGPathApplierFunction	22
Data Types	22
CGPathRef	22
CGMutablePathRef	23
CGPathElement	23
Constants	23
Path Drawing Modes	23
Path Element Types	24

Document Revision History 27

Index 29

CGPath Reference

Derived From:	CType
Framework:	ApplicationServices/ApplicationServices.h
Companion guide	Quartz 2D Programming Guide
Declared in	CGContext.h CGPath.h

Overview

A **graphics path** is a description of a 2D geometric scene using sequences of lines and Bézier curves. `CGPathRef` defines an opaque type that represents an immutable graphics path. `CGMutablePathRef` defines an opaque type that represents a mutable graphics path. To draw using a Quartz path, you need to add the path to a graphics context—see `CGContextAddPath`.

Each figure in a scene may be described by a **subpath**. A subpath has an ordered set of **path elements**, that represent single steps in the construction of a subpath. (For example, `MoveToPoint` (bottom left) and `AddLineToPoint` (bottom right) are path elements.) A subpath also maintains state information, including a **starting point** and a **current point**. When drawing a path, Quartz traverses each subpath using its path elements and its state.

The lines and curves in a subpath are always connected, but they do not necessarily form a closed figure. Furthermore, subpaths do not need to be connected to each other. For example, you could use a graphics path to draw the outlines of a sequence of text characters.

Functions by Task

Creating and Managing Paths

- [CGPathCreateMutable](#) (page 17)
Creates a mutable graphics path.
- [CGPathCreateMutableCopy](#) (page 17)
Creates a mutable copy of an existing graphics path.
- [CGPathCreateCopy](#) (page 16)
Creates an immutable copy of a graphics path.
- [CGPathRelease](#) (page 21)
Decrements the retain count of a graphics path.

[CGPathRetain](#) (page 21)

Increments the retain count of a graphics path.

Modifying Quartz Paths

[CGPathAddArc](#) (page 7)

Appends an arc to a mutable graphics path, possibly preceded by a straight line segment.

[CGPathAddArcToPoint](#) (page 8)

Appends an arc to a mutable graphics path, possibly preceded by a straight line segment.

[CGPathAddCurveToPoint](#) (page 9)

Appends a Bézier curve to a mutable graphics path.

[CGPathAddLines](#) (page 11)

Appends an array of new line segments to a mutable graphics path.

[CGPathAddLineToPoint](#) (page 11)

Appends a line segment to a mutable graphics path.

[CGPathAddPath](#) (page 12)

Appends a path to a mutable graphics path.

[CGPathAddQuadCurveToPoint](#) (page 12)

Appends a quadratic curve to a mutable graphics path.

[CGPathAddRect](#) (page 13)

Appends a rectangle to a mutable graphics path.

[CGPathAddRects](#) (page 14)

Appends an array of rectangles to a mutable graphics path.

[CGPathApply](#) (page 15)

For each element in a graphics path, calls a custom applier function.

[CGPathMoveToPoint](#) (page 20)

Starts a new subpath at a specified location in a mutable graphics path.

[CGPathCloseSubpath](#) (page 15)

Closes and completes a subpath in a mutable graphics path.

[CGPathAddEllipseInRect](#) (page 10)

Adds to a path an ellipse that fits inside a rectangle.

Getting Information about Quartz Paths

[CGPathEqualToPath](#) (page 18)

Indicates whether two graphics paths are equivalent.

[CGPathGetBoundingBox](#) (page 18)

Returns the bounding box of a graphics path.

[CGPathGetCurrentPoint](#) (page 18)

Returns the current point in a graphics path.

[CGPathGetTypeID](#) (page 19)

Returns the Core Foundation type identifier for Quartz graphics paths.

[CGPathIsEmpty](#) (page 19)

Indicates whether or not a graphics path is empty.

[CGPathIsRect](#) (page 20)

Indicates whether or not a graphics path represents a rectangle.

[CGPathContainsPoint](#) (page 16)

Checks whether a point is contained in a graphics path.

Functions

CGPathAddArc

Appends an arc to a mutable graphics path, possibly preceded by a straight line segment.

```
void CGPathAddArc (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat x,
    CGFloat y,
    CGFloat radius,
    CGFloat startAngle,
    CGFloat endAngle,
    bool clockwise
);
```

Parameters

path

The mutable graphics path to change.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the arc before it is added to the path.

x

The x-coordinate of the center point of the arc.

y

The y-coordinate of the center point of the arc.

r

The radius of the arc.

startAngle

The angle (in radians) from horizontal that determines the starting point of the arc.

endAngle

The angle (in radians) from horizontal that determines the ending point of the arc.

clockwise

A Boolean value that specifies whether or not to draw the arc in the clockwise direction; `true` specifies clockwise.

Discussion

An arc is a segment of a circle with radius r centered at a point (x, y) . When you call this function, you provide the center point, radius, and two angles in radians. Quartz uses this information to determine the end points of the arc, and then approximates the new arc using a sequence of cubic Bézier curves. The `clockwise` parameter determines the direction in which the arc is drawn.

A transformation may be applied to the Bézier curves before they are added to the path. If no transform is needed, the second argument should be `NULL`.

If the specified path already contains a subpath, Quartz implicitly adds a line connecting the current point to the beginning of the arc. If the path is empty, Quartz creates a new subpath for the arc and does not add the initial straight line segment.

The ending point of the arc becomes the new current point of the path.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

`CGPath.h`

CGPathAddArcToPoint

Appends an arc to a mutable graphics path, possibly preceded by a straight line segment.

```
void CGPathAddArcToPoint (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat x1,
    CGFloat y1,
    CGFloat x2,
    CGFloat y2,
    CGFloat radius
);
```

Parameters

path

The mutable path to change. The path must not be empty.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the arc before it is added to the path.

x1

The x-coordinate of the user space for the end point of the first tangent line. The first tangent line is drawn from the current point to $(x1, y1)$.

y1

The y-coordinate of the user space for the end point of the first tangent line. The first tangent line is drawn from the current point to $(x1, y1)$.

x2

The x-coordinate of the user space for the end point of the second tangent line. The second tangent line is drawn from $(x1, y1)$ to $(x2, y2)$.

y2

The y-coordinate of the user space for the end point of the second tangent line. The second tangent line is drawn from $(x1, y1)$ to $(x2, y2)$.

radius

The radius of the arc, in user space coordinates.

Discussion

This function uses a sequence of cubic Bézier curves to draw an arc that is tangent to the line from the current point to $(x1, y1)$ and to the line from $(x1, y1)$ to $(x2, y2)$. The start and end points of the arc are located on the first and second tangent lines, respectively. The start and end points of the arc are also the “tangent points” of the lines.

If the current point and the first tangent point of the arc (the starting point) are not equal, Quartz appends a straight line segment from the current point to the first tangent point. After adding the arc, the current point is reset to the end point of the arc (the second tangent point).

For another way to draw an arc in a path, see [CGPathAddArc](#) (page 7).

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddCurveToPoint

Appends a Bézier curve to a mutable graphics path.

```
void CGPathAddCurveToPoint (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat cp1x,
    CGFloat cp1y,
    CGFloat cp2x,
    CGFloat cp2y,
    CGFloat x,
    CGFloat y
);
```

Parameters*path*

The mutable path to change. The path must not be empty.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the curve before it is added to the path.

cx1

The x-coordinate of the first control point.

cy1

The y-coordinate of the first control point.

cx2

The x-coordinate of the second control point.

cy2

The y-coordinate of the second control point.

x

The x-coordinate of the end point of the curve.

y

The y-coordinate of the end point of the curve.

Discussion

Appends a cubic Bézier curve from the current point in a path to the specified location using two control points, after an optional transformation. Before returning, this function updates the current point to the specified location (*x*, *y*).

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddEllipseInRect

Adds to a path an ellipse that fits inside a rectangle.

```
void CGPathAddEllipseInRect (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGRect rect
);
```

Parameters*path*

The path to modify.

m

An affine transform to apply to the ellipse, or NULL if you don't want to transform the ellipse.

rect

A rectangle to enclose the ellipse.

Discussion

The ellipse is approximated by a sequence of Bézier curves. Its center is the midpoint of the rectangle defined by the *rect* parameter. If the rectangle is square, then the ellipse is circular with a radius equal to one-half the width (or height) of the rectangle. If the *rect* parameter specifies a rectangular shape, then the major and minor axes of the ellipse are defined by the width and height of the rectangle.

The ellipse forms a complete subpath of the path—that is, the ellipse drawing starts with a move-to operation and ends with a close-subpath operation, with all moves oriented in the clockwise direction. If you supply an affine transform, then the constructed Bézier curves that define the ellipse are transformed before they are added to the path.

Availability

Available in Mac OS X v10.4 and later.

Declared In

CGPath.h

CGPathAddLines

Appends an array of new line segments to a mutable graphics path.

```
void CGPathAddLines (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    const CGPoint points[],
    size_t count
);
```

Parameters

path

The mutable path to change.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the lines before adding them to the path.

points

An array of points that specifies the line segments to add.

count

The number of elements in the array.

Discussion

This is a convenience function that adds a sequence of connected line segments to a path, using the following operation:

```
CGPathMoveToPoint (path, m, points[0].x, points[0].y);
for (k = 1; k < count; k++) {
    CGPathAddLineToPoint (path, m, points[k].x, points[k].y);
}
```

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddLineToPoint

Appends a line segment to a mutable graphics path.

```
void CGPathAddLineToPoint (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat x,
    CGFloat y
);
```

Parameters

path

The mutable path to change. The path must not be empty.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the line before it is added to the path.

x

The x-coordinate of the end point of the line.

y

The y-coordinate of the end point of the line.

DiscussionBefore returning, this function updates the current point to the specified location (*x*, *y*).**Availability**

Available in Mac OS X version 10.2 and later.

Related Sample Code

CALayerEssentials

Declared In

CGPath.h

CGPathAddPath

Appends a path to a mutable graphics path.

```
void CGPathAddPath (
    CGMutablePathRef path1,
    const CGAffineTransform *m,
    CGPathRef path2
);
```

Parameters*path1*

The mutable path to change.

*m*A pointer to an affine transformation matrix, or NULL if no transformation is needed. If specified, Quartz applies the transformation to *path2* before it is added to *path1*.*path2*

The path to add.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddQuadCurveToPoint

Appends a quadratic curve to a mutable graphics path.

```
void CGContextAddQuadCurveToPoint (
    CGContextMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat cpx,
    CGFloat cpy,
    CGFloat x,
    CGFloat y
);
```

Parameters*path*

The mutable path to change. The path must not be empty.

m

A pointer to an affine transformation matrix, or NULL if no transformation is needed. If specified, Quartz applies the transformation to the curve before adding it to the path.

cpx

The x-coordinate of the control point.

cpy

The y-coordinate of the control point.

x

The x-coordinate of the end point of the curve.

y

The y-coordinate of the end point of the curve.

Discussion

Before returning, this function updates the current point to the specified location (x, y).

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddRect

Appends a rectangle to a mutable graphics path.

```
void CGContextAddRect (
    CGContextMutablePathRef path,
    const CGAffineTransform *m,
    CGRect rect
);
```

Parameters*path*

The mutable path to change.

m

A pointer to an affine transformation matrix, or NULL if no transformation is needed. If specified, Quartz applies the transformation to the rectangle before adding it to the path.

rect

The rectangle to add.

Discussion

This is a convenience function that adds a rectangle to a path, using the following sequence of operations:

```
// start at origin
CGPathMoveToPoint (path, m, CGRectGetMinX(rect), CGRectGetMinY(rect));

// add bottom edge
CGPathAddLineToPoint (path, m, CGRectGetMaxX(rect), CGRectGetMinY(rect));

// add right edge
CGPathAddLineToPoint (path, m, CGRectGetMaxX(rect), CGRectGetMaxY(rect));

// add top edge
CGPathAddLineToPoint (path, m, CGRectGetMinX(rect), CGRectGetMaxY(rect));

// add left edge and close
CGPathCloseSubpath (path);
```

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathAddRects

Appends an array of rectangles to a mutable graphics path.

```
void CGPathAddRects (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    const CGRect rects[],
    size_t count
);
```

Parameters

path

The mutable path to change.

m

An affine transformation matrix, or NULL if no transformation is needed. If specified, Quartz applies the transformation to the rectangles before adding them to the path.

rects

The array of new rectangles to add.

count

The number of elements in the array.

Discussion

This is a convenience function that adds an array of rectangles to a path, using the following operation:

```
for (k = 0; k < count; k++) {
    CGPathAddRect (path, m, rects[k]);
}
```

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathApply

For each element in a graphics path, calls a custom applier function.

```
void CGPathApply (
    CGPathRef path,
    void *info,
    CGPathApplierFunction function
);
```

Parameters*path*

The path to which the function will be applied.

info

A pointer to the user data that Quartz will pass to the function being applied, or NULL.

function

A pointer to the function to apply. See [CGPathApplierFunction](#) (page 22) for more information.

Discussion

For each element in the specified path, Quartz calls the applier function, which can examine (but not modify) the element.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathCloseSubpath

Closes and completes a subpath in a mutable graphics path.

```
void CGPathCloseSubpath (
    CGMutablePathRef path
);
```

Parameters*path*

The path to change.

Discussion

Appends a line from the current point in a path to the starting point of the current subpath and ends the subpath. On return, the current point is now the previous starting point.

Availability

Available in Mac OS X version 10.2 and later.

Related Sample Code

CALayerEssentials

Declared In

CGPath.h

CGPathContainsPoint

Checks whether a point is contained in a graphics path.

```
bool CGPathContainsPoint (
    CGPathRef path,
    const CGAffineTransform *m,
    CGPoint point,
    bool eoFill
);
```

Parameters*path*

The path to evaluate the point against.

m

An affine transform. If *m* is not NULL then the point is transformed by this affine transform prior to determining whether the path contains the point.

point

The point to check.

eoFill

A Boolean value that, if *true*, specifies to use the even-odd fill rule to evaluate the painted region of the path. If *false*, the winding fill rule is used.

Return Value

Returns *true* if the point is contained in the path; *false* otherwise.

Discussion

A point is contained in a path if it is inside the painted region when the path is filled and the path is a closed path. You can call the function `CGPathCloseSubpath` to ensure that a path is closed.

Availability

Available in Mac OS X v10.4 and later.

Declared In

CGPath.h

CGPathCreateCopy

Creates an immutable copy of a graphics path.

```
CGPathRef CGPathCreateCopy (
    CGPathRef path
);
```

Parameters*path*

The path to copy.

Return Value

A new, immutable copy of the specified path. You are responsible for releasing this object.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathCreateMutable

Creates a mutable graphics path.

```
CGMutablePathRef CGPathCreateMutable (  
    void  
);
```

Return Value

A new mutable path. You are responsible for releasing this object.

Availability

Available in Mac OS X version 10.2 and later.

Related Sample Code

CALayerEssentials

Declared In

CGPath.h

CGPathCreateMutableCopy

Creates a mutable copy of an existing graphics path.

```
CGMutablePathRef CGPathCreateMutableCopy (  
    CGPathRef path  
);
```

Parameters

path

The path to copy.

Return Value

A new, mutable, copy of the specified path. You are responsible for releasing this object.

Discussion

You can modify a mutable graphics path by calling the various CGPath geometry functions, such as [CGPathAddArc](#) (page 7), [CGPathAddLineToPoint](#) (page 11), and [CGPathMoveToPoint](#) (page 20).

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathEqualToPath

Indicates whether two graphics paths are equivalent.

```

bool CGPathEqualToPath (
    CGPathRef path1,
    CGPathRef path2
);

```

Parameters

path1

The first path being compared.

path2

The second path being compared.

Return Value

A Boolean value that indicates whether or not the two specified paths contain the same sequence of path elements. If the paths are not the same, returns `false`.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathGetBoundingBox

Returns the bounding box of a graphics path.

```

CGRect CGPathGetBoundingBox (
    CGPathRef path
);

```

Parameters

path

The graphics path to evaluate.

Return Value

A rectangle that represents the bounding box of the specified path.

Discussion

The bounding box is the smallest rectangle completely enclosing all points in the path, including control points for Bézier and quadratic curves.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathGetCurrentPoint

Returns the current point in a graphics path.

```
CGPoint CGPointGetCurrentPoint (
    CGPathRef path
);
```

Parameters*path*

The path to evaluate.

Return Value

The current point in the specified path.

DiscussionIf the path is empty—that is, if it has no elements—this function returns `CGPointZero` (see `CGGeometry`).To determine whether a path is empty, use `CGPathIsEmpty` (page 19).**Availability**

Available in Mac OS X version 10.2 and later.

Declared In`CGPath.h`**CGPathGetTypeID**

Returns the Core Foundation type identifier for Quartz graphics paths.

```
CTypeID CGPointGetTypeID (
    void
);
```

Return ValueThe Core Foundation identifier for the opaque type `CGPathRef` (page 22).**Availability**

Available in Mac OS X version 10.2 and later.

Declared In`CGPath.h`**CGPathIsEmpty**

Indicates whether or not a graphics path is empty.

```
bool CGPointIsEmpty (
    CGPathRef path
);
```

Parameters*path*

The path to evaluate.

Return Value

A Boolean value that indicates whether the specified path is empty.

Discussion

An empty path contains no elements.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathIsRect

Indicates whether or not a graphics path represents a rectangle.

```
bool CGPathIsRect (
    CGPathRef path,
    CGRect *rect
);
```

Parameters

path

The path to evaluate.

rect

On input, a pointer to an uninitialized rectangle. If the specified path represents a rectangle, on return contains a copy of the rectangle.

Return Value

A Boolean value that indicates whether the specified path represents a rectangle. If the path represents a rectangle, returns `true`.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

CGPathMoveToPoint

Starts a new subpath at a specified location in a mutable graphics path.

```
void CGPathMoveToPoint (
    CGMutablePathRef path,
    const CGAffineTransform *m,
    CGFloat x,
    CGFloat y
);
```

Parameters

path

The mutable path to change.

m

A pointer to an affine transformation matrix, or `NULL` if no transformation is needed. If specified, Quartz applies the transformation to the point before changing the path.

x

The x-coordinate of the new location.

y

The y-coordinate of the new location.

Discussion

This function initializes the starting point and the current point to the specified location (x,y) after an optional transformation.

Availability

Available in Mac OS X version 10.2 and later.

Related Sample Code

CALayerEssentials

Declared In

CGPath.h

CGPathRelease

Decrements the retain count of a graphics path.

```
void CGPathRelease (
    CGPathRef path
);
```

Parameters*path*

The graphics path to release.

Discussion

This function is equivalent to `CFRelease`, except that it does not cause an error if the `path` parameter is `NULL`.

Availability

Available in Mac OS X version 10.2 and later.

Related Sample Code

CALayerEssentials

Declared In

CGPath.h

CGPathRetain

Increments the retain count of a graphics path.

```
CGPathRef CGPathRetain (
    CGPathRef path
);
```

Parameters*path*

The graphics path to retain.

Return Value

The same path you passed in as the `path` parameter.

Discussion

This function is equivalent to `CFRetain`, except that it does not cause an error if the `path` parameter is `NULL`.

Availability

Available in Mac OS X version 10.2 and later.

Declared In

CGPath.h

Callbacks

CGPathApplierFunction

Defines a callback function that can view an element in a graphics path.

```
typedef void (*CGPathApplierFunction) (
    void *info,
    const CGPathElement *element
);
```

If you name your function `MyCGPathApplierFunc`, you would declare it like this:

```
void MyCGPathApplierFunc (
    void *info,
    const CGPathElement *element
);
```

Discussion

See also [CGPathApply](#) (page 15).

Availability

Available in Mac OS X v10.2 and later.

Declared In

CGPath.h

Data Types

CGPathRef

An opaque type that represents an immutable graphics path.

```
typedef const struct CGPath *CGPathRef;
```

Availability

Available in Mac OS X v10.2 and later.

Declared In

CGPath.h

CGMutablePathRef

An opaque type that represents a mutable graphics path.

```
typedef struct CGPath *CGMutablePathRef;
```

Availability

Available in Mac OS X v10.2 and later.

Declared In

CGPath.h

CGPathElement

A data structure that provides information about a path element.

```
struct CGPathElement {
    CGPathElementType type;
    CGPoint * points;
};
typedef struct CGPathElement CGPathElement;
```

Fields

type

An element type (or operation).

points

An array of one or more points that serve as arguments.

Availability

Available in Mac OS X v10.2 and later.

Declared In

CGPath.h

Constants

Path Drawing Modes

Options for rendering a path.

```
enum CGPathDrawingMode {
    kCGPathFill,
    kCGPathEOFill,
    kCGPathStroke,
    kCGPathFillStroke,
    kCGPathEOFillStroke
};
typedef enum CGPathDrawingMode CGPathDrawingMode;
```

Constants`kCGPathFill`

Render the area contained within the path using the non-zero winding number rule.

Available in Mac OS X v10.0 and later.

Declared in `CGContext.h`.

`kCGPathEOFill`

Render the area within the path using the even-odd rule.

Available in Mac OS X v10.0 and later.

Declared in `CGContext.h`.

`kCGPathStroke`

Render a line along the path.

Available in Mac OS X v10.0 and later.

Declared in `CGContext.h`.

`kCGPathFillStroke`

First fill and then stroke the path, using the nonzero winding number rule.

Available in Mac OS X v10.0 and later.

Declared in `CGContext.h`.

`kCGPathEOFillStroke`

First fill and then stroke the path, using the even-odd rule.

Available in Mac OS X v10.0 and later.

Declared in `CGContext.h`.

Discussion

You can pass a path drawing mode constant to the function `CGContextDrawPath` to specify how Quartz should paint a graphics context's current path.

Path Element Types

The type of element found in a path.


```
enum CGPathElementType {
    kCGPathElementMoveToPoint,
    kCGPathElementAddLineToPoint,
    kCGPathElementAddQuadCurveToPoint,
    kCGPathElementAddCurveToPoint,
    kCGPathElementCloseSubpath
};
typedef enum CGPathElementType CGPathElementType;
```

Constants

`kCGPathElementMoveToPoint`

The path element that starts a new subpath. See the function [CGPathMoveToPoint](#) (page 20).

Available in Mac OS X v10.2 and later.

Declared in `CGPath.h`.

`kCGPathElementAddLineToPoint`

The path element that adds a line from the current point to the specified point. See the function [CGPathAddLineToPoint](#) (page 11).

Available in Mac OS X v10.2 and later.

Declared in `CGPath.h`.

`kCGPathElementAddQuadCurveToPoint`

The path element that adds a quadratic curve from the current point to the specified point. See the function [CGPathAddQuadCurveToPoint](#) (page 12).

Available in Mac OS X v10.2 and later.

Declared in `CGPath.h`.

`kCGPathElementAddCurveToPoint`

The path element that adds a cubic curve from the current point to the specified point. See the function [CGPathAddCurveToPoint](#) (page 9).

Available in Mac OS X v10.2 and later.

Declared in `CGPath.h`.

`kCGPathElementCloseSubpath`

The path element that closes and completes a subpath. See the function [CGPathCloseSubpath](#) (page 15).

Available in Mac OS X v10.2 and later.

Declared in `CGPath.h`.

Discussion

For more information about paths, see [CGPathRef](#) (page 22).

Document Revision History

This table describes the changes to *CGPath Reference*.

Date	Notes
2006-12-22	Updated for Mac OS X v10.5.
	All instances of the <code>float</code> data type were changed to the <code>CGFloat</code> data type.
2006-01-10	Added clarification on using the function <code>CGPathContainsPoint</code> .
2005-04-29	Updated for Mac OS X v10.4.
	Added the functions <code>CGPathAddEllipseInRect</code> (page 10) and <code>CGPathContainsPoint</code> (page 16).
2004-08-31	Added introductory material.
2004-02-26	First version of this document. An earlier version of this information appeared in <i>Quartz 2D Reference</i> .

REVISION HISTORY

Document Revision History

Index

C

CGMutablePathRef **data type** 23
CGPathAddArc **function** 7
CGPathAddArcToPoint **function** 8
CGPathAddCurveToPoint **function** 9
CGPathAddEllipseInRect **function** 10
CGPathAddLines **function** 11
CGPathAddLineToPoint **function** 11
CGPathAddPath **function** 12
CGPathAddQuadCurveToPoint **function** 12
CGPathAddRect **function** 13
CGPathAddRects **function** 14
CGPathApplierFunction **callback** 22
CGPathApply **function** 15
CGPathCloseSubpath **function** 15
CGPathContainsPoint **function** 16
CGPathCreateCopy **function** 16
CGPathCreateMutable **function** 17
CGPathCreateMutableCopy **function** 17
CGPathElement **structure** 23
CGPathEqualToPath **function** 18
CGPathGetBoundingBox **function** 18
CGPathGetCurrentPoint **function** 18
CGPathGetTypeID **function** 19
CGPathIsEmpty **function** 19
CGPathIsRect **function** 20
CGPathMoveToPoint **function** 20
CGPathRef **data type** 22
CGPathRelease **function** 21
CGPathRetain **function** 21

K

kCGPathElementAddCurveToPoint **constant** 25
kCGPathElementAddLineToPoint **constant** 25
kCGPathElementAddQuadCurveToPoint **constant** 25
kCGPathElementCloseSubpath **constant** 25
kCGPathElementMoveToPoint **constant** 25
kCGPathEOFill **constant** 24

kCGPathEOFillStroke **constant** 24
kCGPathFill **constant** 24
kCGPathFillStroke **constant** 24
kCGPathStroke **constant** 24

P

Path Drawing Modes 23
Path Element Types 24