



EOApplication Java Framework

API Reference



TITLEPAGE

Apple Computer, Inc.

© 1999 Apple Computer, Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Computer, Inc., except to make a backup copy of any documentation provided on CD-ROM.

The Apple logo is a trademark of Apple Computer, Inc.

Use of the “keyboard” Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this book. Apple retains all intellectual property rights associated with the technology described in this book. This book is intended to assist application developers to develop applications only for Apple-labeled or Apple-licensed computers.

Every effort has been made to ensure that the information in this manual is accurate. Apple is not responsible for typographical errors.

Apple Computer, Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Macintosh, and WebObjects are trademarks of Apple Computer, Inc., registered in the United States and other countries. Enterprise Objects is a trademark of Apple Computer, Inc.

NeXT, the NeXT logo, OPENSTEP, Enterprise Objects Framework, Objective-C, and WEBSOCKET are trademarks of NeXT Software, Inc.

Adobe, Acrobat, and PostScript are trademarks of Adobe Systems Incorporated or its subsidiaries and may be registered in certain jurisdictions.

Helvetica and Palatino are registered trademarks of Linotype-Hell AG and/or its subsidiaries.

ITC Zapf Dingbats is a registered trademark of International Typeface Corporation.

ORACLE is a registered trademark of Oracle Corporation, Inc.

SYBASE is a registered trademark of Sybase, Inc.

UNIX is a registered trademark in the United States and other countries, licensed exclusively through X/Open Company Limited.

Windows NT is a trademark of Microsoft Corporation.

All other trademarks mentioned belong to their respective owners.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this manual, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS MANUAL, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS MANUAL IS SOLD “AS IS,” AND YOU, THE PURCHASER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS MANUAL, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

The eoapplication Package

Package: `com.webobjects.eoapplication`

Introduction

Documentation for this package is forthcoming. For information on using this package, see the book *Getting Started with Direct to Java Client*.

The most important classes in this package are:

Class	Description
EOController	A representation of controller objects responsible for managing and sometimes generating the user interface of a Java Client application
EOComponentController	A controller that manages user interface components
EOEntityController	A controller that displays enterprise objects in a user interface
EODocumentController	A controller that displays and edits enterprise objects in a user interface
EOInterfaceController	A controller that represents an Interface Builder nib file
EOApplication	The Java Client application
EOAppletController	A representation of an EOApplet as a controller in the controller hierarchy

Class	Description
EOApplet	The default Applet class used in Java Client applications
EOAction	An abstract representation of operations the user can invoke from the user interface
EOXMLUnarchiver	An object containing the parameters from an XML specification used to create the controllers in the controller hierarchy

Rule System and XML Description

For Direct to Java Client applications, the controller hierarchy for the client side of the application is created from an XML description. The XML description is created by a rule system on the server side of the application. The details of this process are described in the book *Getting Started With Direct to Java Client*.

There are three pieces of information associated with an EOController class that are used to generate a controller hierarchy with the rule system: the controller's `controllerType`, its corresponding XML tag, and its corresponding XML attributes. Each controller class specification identifies this information in a section titled "Rule System and XML Description".

`controllerType`

You use the `controllerType` key to define custom rules that should fire only for certain kinds of controllers. For example, suppose you want to set the minimum width of all an application's windows. To do so, you write a rule whose condition specifies that the `controllerType` is 'windowController'. Then the rule only fires for controllers that control windows. Each controller falls into one of the following controller types:

- n `windowController`
- n `modalDialogController`
- n `entityController`
- n `widgetController`
- n `tableController`
- n `groupingController`
- n `dividingController`

n actionWidgetController

XML Tag and Attributes

As an XML description is parsed, an EOXMLUnarchiver maps XML tags to particular EOController classes. All concrete controller classes—classes whose instances can actually be used in a controller hierarchy—have an XML tag.

XML attributes tell the EOXMLUnarchiver how to configure the controllers. XML attributes are inherited. For example, there are three XML attributes defined for EOController—className, disabledActionNames, and typeName. These attributes can be used by any controller, however, because all controllers are subclasses of EOController.

BeansAppletContext

Inherits from: Object
Implements: java.applet.AppletContext
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

- getApplet
- getApplets
- getAudioClip
- getImage
- showDocument

CLASS BeansAppletContext

showDocument

showStatus

Instance Methods

getApplet

```
public java.applet.Applet getApplet(String aString)
```

getApplets

```
public java.util.Enumeration getApplets()
```

getAudioClip

```
public java.applet.AudioClip getAudioClip(java.net.URL anURL)
```

getImage

```
public synchronized java.awt.Image getImage(java.net.URL anURL)
```

showDocument

```
public void showDocument(  
    java.net.URL anURL,  
    String aString)
```

CLASS BeansAppletContext

showDocument

```
public void showDocument(java.net.URL anURL)
```

showStatus

```
public void showStatus(String aString)
```

CLASS BeansAppletContext

BeansAppletStub

Inherits from: Object
Implements: java.applet.AppletStub
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

- appletResize
- getAppletContext
- getCodeBase
- getDocumentBase
- getParameter

CLASS BeansAppletStub

isActive

Instance Methods

appletResize

```
public void appletResize(  
    int anInt,  
    int anInt)
```

getAppletContext

```
public java.applet.AppletContext getAppletContext()
```

getCodeBase

```
public java.net.URL getCodeBase()
```

getDocumentBase

```
public java.net.URL getDocumentBase()
```

getParameter

```
public String getParameter(String aString)
```

CLASS BeansAppletStub

isActive

```
public boolean isActive()
```

CLASS BeansAppletStub

BeansCallback

Inherits from: Object
Implements: _EOTimer.Callback
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Instance Methods

timerFired

```
public void timerFired(  
    _EOTimer a_EOTimer,  
    java.util.Date aDate,  
    java.util.Date aDate)
```

CLASS BeansCallback

EOAction

Inherits from: javax.swing.AbstractAction
Package: com.webobjects.eoapplication

Class Description

EOAction objects are abstract representations of operations the user can invoke from the user interface. An action does not specify how it appears in the user interface—it can appear as a button, a menu item, or both.

Each action defines a method called the action name, that is invoked when the action triggers. An action also has a description path, which describes the category of the action and its name. For example, a Quit action’s description path might be “Document/Quit”. In addition, the action can have a short description that differs from the last element of the description path, for example, “Quit the Application”.

Actions can have icons for buttons in the application and small icons for minor buttons in the user interface. To allow users to trigger actions with “hot-keys,” each action has a menu accelerator, a javax.swing.KeyStroke the user can type on the keyboard.

Actions often appear in groups in the user interface: buttons in the same group are rendered close together and menu items in the group are rendered in separate menus like the Document, Edit, Tools, or Window menus. To group actions, EOAction defines a category priority. All actions in the same group have the same category priority. An additional parameter, the action priority defines the order in which actions appear within a group (for example, the order menu items appear within a menu).

CLASS EOAction

An action triggers when the user clicks the corresponding user interface widget. In most cases, the action's method is dispatched to the subcontrollers of the controller that displays the action. Methods whose names end with `...ForControllerHierarchy` return such actions. In some cases, the action's method is dispatched to the active widget, like the text field containing the cursor. Methods whose names end with `...ForFocusComponent` return such actions. In other cases, the action's method is dispatched to a particular object, usually the EOApplication at the root of the controller hierarchy.

EOAction defines methods to create actions, access an action's parameters, manage groups of actions, and accessing shared actions used in Direct to Java Client applications.

Constants

Constant	Description
ActivatePreviousWindowActionPriority	Description forthcoming.
AppendActionPriority	Description forthcoming.
CancelActionPriority	Description forthcoming.
ClearActionPriority	Description forthcoming.
CloseWindowActionPriority	Description forthcoming.
DeleteActionPriority	Description forthcoming.
DescriptionPathSeparator	Description forthcoming.
DocumentCategoryPriority	Description forthcoming.
EditCategoryPriority	Description forthcoming.
FindActionPriority	Description forthcoming.
HelpActionPriority	Description forthcoming.
HelpCategoryPriority	Description forthcoming.

CLASS EOAction

Constant	Description
InfoActionPriority	Description forthcoming.
InsertActionPriority	Description forthcoming.
ModalActionsCategoryPriority	Description forthcoming.
NavigationActionPriority	Description forthcoming.
NavigationActionsCategoryPriority	Description forthcoming.
NewMultipleWindowActionPriority	Description forthcoming.
NewSingleWindowActionPriority	Description forthcoming.
ObjectActionPriority	Description forthcoming.
ObjectActionsCategoryPriority	Description forthcoming.
OkayActionPriority	Description forthcoming.
OpenActionPriority	Description forthcoming.
PasteboardCopyActionPriority	Description forthcoming.
PasteboardCutActionPriority	Description forthcoming.
PasteboardDeleteActionPriority	Description forthcoming.
PasteboardPasteActionPriority	Description forthcoming.
PasteboardSelectAllActionPriority	Description forthcoming.
QuitActionPriority	Description forthcoming.
RedoActionPriority	Description forthcoming.
RefreshActionPriority	Description forthcoming.
RevertActionPriority	Description forthcoming.
SaveActionPriority	Description forthcoming.
SaveAllActionPriority	Description forthcoming.
SearchActionPriority	Description forthcoming.

CLASS EOAction

Constant	Description
ToolsCategoryPriority	Description forthcoming.
UndoActionPriority	Description forthcoming.
WindowCategoryPriority	Description forthcoming.

Method Types

Accessing action parameters

actionName
actionPriority
actionTitle
categoryPriority
descriptionPath
descriptionPathComponents
icon
menuAccelerator
setActionName
setActionPriority
setCategoryPriority
setDescriptionPath
setIcon
setMenuAccelerator
setShortDescription
setSmallIcon
shortDescription

CLASS EOAction

smallIcon

Creating actions

EOAction

actionForControllerHierarchy

actionForFocusComponent

actionForObject

standardActionForFocusComponent

standardDocumentActionForControllerHierarchy

standardDocumentActionForApplication

standardDocumentActionForControllerHierarchy

standardEditActionForControllerHierarchy

Creating menu accelerators

keyStrokeWithKeyCode

keyStrokeWithKeyCodeAndModifiers

keyStrokeWithKeyCodeAndShiftModifier

keyStrokeWithString

Accessing specific shared actions

standardActivatePreviousWindowActionForApplication

standardAddActionForControllerHierarchy

standardAppendActionForControllerHierarchy

standardCancelActionForControllerHierarchy

standardClearActionForControllerHierarchy

standardCloseWindowActionForControllerHierarchy

standardDeleteActionForControllerHierarchy

standardDeselectActionForControllerHierarchy

standardEditActionsForFocusComponent

standardFindActionForControllerHierarchy

CLASS EOAction

standardInsertActionForControllerHierarchy
standardInsertWithTaskActionForControllerHierarchy
standardOkActionForControllerHierarchy
standardOkAndSaveActionForControllerHierarchy
standardOpenWithTaskActionForControllerHierarchy
standardQuitActionForApplication
standardRedoActionForControllerHierarchy
standardRefreshActionForApplication
standardRemoveActionForControllerHierarchy
standardRevertActionForControllerHierarchy
standardSaveActionForControllerHierarchy
standardSaveAllActionForApplication
standardSelectActionForControllerHierarchy
standardUndoActionForControllerHierarchy

Managing actions

actionCanBePerformedInContextOfController
actionPerformed
mergedActions
sortedActions

Managing the property change listener

addPropertyChangeListener
firePropertyChange
removePropertyChangeListener

Methods inherited from Object

equals
toString

Constructors

EOAction

```
public EOAction(  
    String actionName,  
    String descriptionPath,  
    String shortDescription,  
    javax.swing.Icon icon,  
    javax.swing.Icon smallIcon,  
    javax.swing.KeyStroke menuAccelerator,  
    int categoryPriority,  
    int actionPriority)
```

Returns a new action (an EOAction object) as specified by the arguments.

See Also: actionName, descriptionPath, shortDescription, icon, smallIcon, menuAccelerator, categoryPriority, and actionPriority.

Static Methods

actionForControllerHierarchy

```
public static EOAction actionForControllerHierarchy(  
    String actionName,  
    String descriptionPath,  
    String shortDescription,  
    javax.swing.Icon icon,  
    javax.swing.Icon smallIcon,  
    javax.swing.KeyStroke menuAccelerator,
```

CLASS EOAction

```
int categoryPriority,  
int actionPriority,  
boolean sendsActionToAllControllers)
```

Returns a new action (an EOAction object) as specified by the arguments. When this action triggers, it is dispatched to the subcontrollers of the controller that displays it. If `sendsActionToAllControllers` is true, the action is dispatched to the subcontrollers of the controller that displays the action. Otherwise, the action is dispatched to the first subcontroller that responds to it.

See Also: EOAction, actionName, descriptionPath, shortDescription, icon, smallIcon, menuAccelerator, categoryPriority, and actionPriority.

actionForFocusComponent

```
public static EOAction actionForFocusComponent(  
    String actionName,  
    String descriptionPath,  
    String shortDescription,  
    javax.swing.Icon icon,  
    javax.swing.Icon smallIcon,  
    javax.swing.KeyStroke menuAccelerator,  
    int categoryPriority,  
    int actionPriority)
```

Returns a new action (an EOAction object) as specified by the arguments. When this action triggers, it is dispatched to the active widget (for example, the text field containing the cursor). The other parameters are identical to the EOAction constructor parameters.

See Also: EOAction, actionName, descriptionPath, shortDescription, icon, smallIcon, menuAccelerator, categoryPriority, and actionPriority.

actionForObject

```
public static EOAction actionForObject(  
    String actionName,  
    String descriptionPath,  
    String shortDescription,  
    javax.swing.Icon icon,  
    javax.swing.Icon smallIcon,  
    javax.swing.KeyStroke menuAccelerator,
```

CLASS EOAction

```
int categoryPriority,  
int actionPriority,  
Object object)
```

Returns a new action (an EOAction object) as specified by the arguments. When this action triggers, it is dispatched directly to `object`. To create an action that gets dispatched to the application, set `object` to the EOApplication at the top of the controller hierarchy. The other parameters are identical to the EOAction constructor parameters.

See Also: EOAction, actionName, descriptionPath, shortDescription, icon, smallIcon, menuAccelerator, categoryPriority, and actionPriority.

keyStrokeWithKeyCode

```
public static javax.swing.KeyStroke keyStrokeWithKeyCode(int keyCode)
```

Returns a KeyStroke given the numerical key code `keyCode` with the appropriate modifier for the client operating system (usually `CTRL_MASK`). See Sun's `javax.swing.KeyStroke` documentation for more information.

keyStrokeWithKeyCodeAndModifiers

```
public static javax.swing.KeyStroke keyStrokeWithKeyCodeAndModifiers(  
    int keyCode,  
    int modifiers)
```

Returns a KeyStroke given the numerical key code `keyCode` and the modifier mask `modifiers`. This method adds the appropriate modifier for the client operating system (usually `CTRL_MASK`). See Sun's `javax.swing.KeyStroke` documentation for more information.

keyStrokeWithKeyCodeAndShiftModifier

```
public static javax.swing.KeyStroke keyStrokeWithKeyCodeAndShiftModifier(int keyCode)
```

Returns a KeyStroke given the numerical key code `keyCode` with the SHIFT modifier. This method also adds the appropriate modifier for the client operating system (usually `CTRL_MASK`). See Sun's `javax.swing.KeyStroke` documentation for more information.

CLASS EOAction

keyStrokeWithString

```
public static javax.swing.KeyStroke keyStrokeWithString(String keyStrokeDescription)
```

Returns a `KeyStroke` for the `String` `keyStrokeDescription`. This method adds the appropriate modifier for the client operating system (usually `CTRL_MASK`). See Sun's `javax.swing.KeyStroke` documentation for more information.

mergedActions

```
public static NSArray mergedActions(  
    NSArray actionArray1,  
    NSArray actionArray2)
```

Returns an `NSArray` containing all of the actions in `actionArray1` and `actionArray2` with duplicate actions removed.

sortedActions

```
public static NSArray sortedActions(NSArray actionArray)
```

Returns a sorted `NSArray` containing the actions in `actionArray`. The actions are sorted first on the category priority, then on the action priority, and finally on the description path.

See Also: `categoryPriority`, `actionPriority`, and `descriptionPath`.

standardActionForFocusComponent

```
public static EOAction standardActionForFocusComponent(  
    String actionName,  
    javax.swing.KeyStroke menuAccelerator,  
    int actionPriority)
```

Returns a shared action as specified by the arguments. When the action triggers, it is dispatched to the focus component (for example, a text field). The action's category priority is the edit action priority so the action is grouped with the other edit actions.

See Also: `actionName`, `menuAccelerator`, and `actionPriority`.

CLASS EOAction

standardActivatePreviousWindowActionForApplication

```
public static EOAction standardActivatePreviousWindowActionForApplication()
```

Returns a shared action (an EOAction object) for the `activatePreviousWindow` method. When this action triggers, it is dispatched to the EOApplication at the top of the controller hierarchy. The action's category priority is the window action priority so the action is grouped with the other window actions. This action appears as the Activate Previous Window item in the Window menu in Direct to Java Client applications.

standardAddActionForControllerHierarchy

```
public static EOAction standardAddActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `add` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardAppendActionForControllerHierarchy

```
public static EOAction standardAppendActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `append` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

standardCancelActionForControllerHierarchy

```
public static EOAction standardCancelActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `cancel` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the modal dialog action priority so the action is grouped with the other modal dialog actions.

CLASS EOAction

standardClearActionForControllerHierarchy

```
public static EOAction standardClearActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `clear` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

standardCloseWindowActionForControllerHierarchy

```
public static EOAction standardCloseWindowActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `close` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the window action priority so the action is grouped with the other window actions.

standardDeleteActionForControllerHierarchy

```
public static EOAction standardDeleteActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `delete` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardDeselectActionForControllerHierarchy

```
public static EOAction standardDeselectActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `deselect` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

CLASS EOAction

standardDocumentActionForApplication

```
public static EOAction standardDocumentActionForApplication(  
    String actionName,  
    javax.swing.KeyStroke menuAccelerator,  
    int actionPriority)
```

Returns a shared action with the method name `actionName`, menu accelerator `menuAccelerator`, and action priority `actionPriority`. When this action triggers, it is dispatched to the EOApplication at the top of the controller hierarchy. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardDocumentActionForControllerHierarchy

```
public static EOAction standardDocumentActionForControllerHierarchy(  
    String actionName,  
    javax.swing.KeyStroke menuAccelerator,  
    int actionPriority)
```

Returns a shared action with the method name `actionName`, menu accelerator `menuAccelerator`, and action priority `actionPriority`. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardDocumentActionForControllerHierarchy

```
public static EOAction standardDocumentActionForControllerHierarchy(  
    String actionName,  
    String baseTitle,  
    javax.swing.KeyStroke menuAccelerator,  
    int actionPriority)
```

Returns a shared action as specified by the arguments. The `baseTitle` parameter is the name of the action as it appears in the user interface and is used for both the short description and the action title. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

See Also: `actionName`, `actionTitle`, `shortDescription`, `menuAccelerator`, and `actionPriority`.

CLASS EOAction

standardEditActionForControllerHierarchy

```
public static EOAction standardEditActionForControllerHierarchy(  
    String actionName,  
    javax.swing.KeyStroke menuAccelerator,  
    int actionPriority)
```

Returns a shared action as specified by the arguments. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

See Also: `actionName`, `menuAccelerator`, and `actionPriority`.

standardEditActionsForFocusComponent

```
public static NSArray standardEditActionsForFocusComponent()
```

Returns an NSArray containing shared actions for the `cut`, `copy`, and `paste` methods. When these actions trigger, they are dispatched to the focus component. Sets the category priorities for the actions to the edit category priority so the actions are grouped with the other edit actions.

standardFindActionForControllerHierarchy

```
public static EOAction standardFindActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `find` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

standardInsertActionForControllerHierarchy

```
public static EOAction standardInsertActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `insertWithTask` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

CLASS EOAction

standardInsertWithTaskActionForControllerHierarchy

```
public static EOAction standardInsertWithTaskActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `insertWithTask` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardOkActionForControllerHierarchy

```
public static EOAction standardOkActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for an OK button in a modal dialog box. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the modal dialog action priority so the action is grouped with the other modal dialog actions.

standardOkAndSaveActionForControllerHierarchy

```
public static EOAction standardOkAndSaveActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for an OK and Save button in a modal dialog box. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the modal dialog action priority so the action is grouped with the other modal dialog actions.

standardOpenWithTaskActionForControllerHierarchy

```
public static EOAction standardOpenWithTaskActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `openWithTask` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

CLASS EOAction

standardQuitActionForApplication

```
public static EOAction standardQuitActionForApplication()
```

Returns a shared action (an EOAction object) for the `quit` method. When this action triggers, it is dispatched to the EOApplication at the top of the controller hierarchy. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardRedoActionForControllerHierarchy

```
public static EOAction standardRedoActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `redo` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

standardRefreshActionForApplication

```
public static EOAction standardRefreshActionForApplication()
```

Returns a shared action (an EOAction object) for the `refresh` method. When this action triggers, it is dispatched to the EOApplication at the top of the controller hierarchy. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardRemoveActionForControllerHierarchy

```
public static EOAction standardRemoveActionForControllerHierarchy()
```

The action's category priority is the document action priority so the action is grouped with the other document actions. Returns a shared action (an EOAction object) for the `remove` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it.

CLASS EOAction

standardRevertActionForControllerHierarchy

```
public static EOAction standardRevertActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `revert` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardSaveActionForControllerHierarchy

```
public static EOAction standardSaveActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `save` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardSaveAllActionForApplication

```
public static EOAction standardSaveAllActionForApplication()
```

Returns a shared action (an EOAction object) for the `saveAll` method. When this action triggers, it is dispatched to the EOApplication at the top of the controller hierarchy. The action's category priority is the document action priority so the action is grouped with the other document actions.

standardSelectActionForControllerHierarchy

```
public static EOAction standardSelectActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `select` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the document action priority so the action is grouped with the other document actions.

CLASS EOAction

standardUndoActionForControllerHierarchy

```
public static EOAction standardUndoActionForControllerHierarchy()
```

Returns a shared action (an EOAction object) for the `undo` method. When the action triggers, it is dispatched to the subcontrollers of the controller that displays it. The action's category priority is the edit action priority so the action is grouped with the other edit actions.

Instance Methods

actionCanBePerformedInContextOfController

```
public boolean actionCanBePerformedInContextOfController(EOController controller)
```

Returns whether or not an action can trigger, which depends on the state of controllers in the controller hierarchy. For example, a Save action for an unedited document can not trigger.

actionName

```
public String actionName()
```

Returns the name of the method that executes when the receiver triggers.

actionPerformed

```
public void actionPerformed(java.awt.event.ActionEvent actionEvent)
```

This method is called when an action is triggered, that is, the user presses the action's button or selects its menu item.

CLASS `EOAction`

`actionPriority`

```
public int actionPriority()
```

Returns the receiver's action priority, which determines the order in which its button or menu item appears within a category.

See Also: `categoryPriority`

`actionTitle`

```
public String actionTitle()
```

Returns the receiver's title, the last component of the receiver's description path.

`addPropertyChangeListener`

```
public void addPropertyChangeListener(java.beans.PropertyChangeListener listener)
```

See the method description for `addPropertyChangeListener` in Sun's documentation for `javax.swing.AbstractAction`.

`categoryPriority`

```
public int categoryPriority()
```

Returns the receiver's category priority, which determines the order in which the group of buttons or menu items that contains the receiver appears.

`descriptionPath`

```
public String descriptionPath()
```

Returns the receiver's menu hierarchy path. For example, the Quit menu item description path is `Document/Quit`.

CLASS EOAction

descriptionPathComponents

```
public NSArray descriptionPathComponents()
```

Returns an NSArray containing the separate components of the receiver's menu hierarchy path.

equals

```
public boolean equals(Object anObject)
```

Indicates whether some object "is equal to" this one.

firePropertyChange

```
protected void firePropertyChange(  
    String propertyName,  
    Object oldValue,  
    Object newValue)
```

See the method description for `firePropertyChange` in Sun's documentation for `javax.swing.AbstractAction`.

icon

```
public javax.swing.Icon icon()
```

Returns the receiver's icon.

menuAccelerator

```
public javax.swing.KeyStroke menuAccelerator()
```

Returns the KeyStroke the user can type to invoke the receiver instead of selecting it from the menu.

CLASS EOAction

removePropertyChangeListener

```
public void removePropertyChangeListener(java.beans.PropertyChangeListener listener)
```

See the method description for `removePropertyChangeListener` in Sun's documentation for `javax.swing.AbstractAction`.

setActionName

```
public void setActionName(String actionName)
```

Sets the name of the method that executes when the receiver triggers.

setActionPriority

```
public void setActionPriority(int actionPriority)
```

Sets the receiver's action priority, which determines the order in which its button or menu item appears within a category.

setCategoryPriority

```
public void setCategoryPriority(int categoryPriority)
```

Returns the receiver's category priority, which determines the order in which the group of buttons or menu items containing the receiver appears.

setDescriptionPath

```
public void setDescriptionPath(String descriptionPath)
```

Sets the receiver's menu hierarchy path to `descriptionPath`.

setIcon

```
public void setIcon(javax.swing.Icon icon)
```

Sets the receiver's icon to `icon`.

CLASS `EOAction`

`setMenuAccelerator`

```
public void setMenuAccelerator(javax.swing.KeyStroke menuAccelerator)
```

Sets the `KeyStroke` the user can type to invoke the receiver instead of selecting it from a menu.

See Also: `keyStrokeWithKeyCode`, `keyStrokeWithKeyCodeAndModifiers`, `keyStrokeWithKeyCodeAndShiftModifier`, and `keyStrokeWithString`.

`setShortDescription`

```
public void setShortDescription(String shortDescription)
```

Sets the action's short description to `shortDescription`. The short description appears in buttons and menu items. If `shortDescription` is `null`, the receiver's title is displayed instead.

See Also: `actionTitle`

`setSmallIcon`

```
public void setSmallIcon(javax.swing.Icon anIcon)
```

Sets the receiver's small icon used for some small buttons in the user interface (the Select button in a Form window's to-one relationship editor is an example).

`shortDescription`

```
public String shortDescription()
```

Returns the receiver's short description, which is displayed in buttons and menu items. If the short description is set to `null` or has not been assigned, `shortDescription` returns the action's title.

See Also: `actionTitle`

CLASS EOAction

smallIcon

```
public javax.swing.Icon smallIcon()
```

Returns the receiver's small icon used for some small buttons in the user interface (the Select button in a Form window's to-one relationship editor is an example). By default, the small icon is not displayed for such buttons; the short description is displayed instead.

See Also: shortDescription

toString

```
public String toString()
```

Returns the receiver as a string that states the receiver's method name, description path, category priority, and action priority.

CLASS EOAction

EOActionButtonsController

Inherits from: EOActionWidgetController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
ACTIONBUTTONSCONTROLLER	actionWidgetController

Method Types

All methods

EOActionButtonsController

actionWidget

CLASS **EOActionButtonsController**

actionWidgetToSubcontrollerAreaDistance
createWidgetForActionsAndPlaceInContainer
disposeActionWidget
setUsesLargeButtonRepresentation
updateActionWidgetEnabling
usesLargeButtonRepresentation

Constructors

EOActionButtonsController

public EOActionButtonsController(EOXMLUnarchiver anEOXMLUnarchiver)

Description forthcoming.

public EOActionButtonsController()

Description forthcoming.

Instance Methods

actionWidget

public javax.swing.JComponent actionWidget()

Description forthcoming.

CLASS EOActionButtonsController

actionWidgetToSubcontrollerAreaDistance

```
protected int actionWidgetToSubcontrollerAreaDistance()
```

Description forthcoming.

createWidgetForActionsAndPlaceInContainer

```
protected void createWidgetForActionsAndPlaceInContainer(  
    NSArray aNSArray,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

disposeActionWidget

```
protected void disposeActionWidget()
```

Description forthcoming.

setUsesLargeButtonRepresentation

```
public void setUsesLargeButtonRepresentation(boolean aBoolean)
```

Description forthcoming.

updateActionWidgetEnabling

```
protected void updateActionWidgetEnabling()
```

Description forthcoming.

usesLargeButtonRepresentation

```
public boolean usesLargeButtonRepresentation()
```

Description forthcoming.

CLASS EOActionButtonsController

EOActionMenuController

Inherits from: EOActionWidgetController :
EOComponentController :
EOController

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
ACTIONMENUCONTROLLER	actionWidgetController

Method Types

All methods

EOActionMenuController

actionWidget

CLASS EOActionMenuController

actionWidgetToSubcontrollerAreaDistance
createWidgetForActionsAndPlaceInContainer
disposeActionWidget
updateActionWidgetEnabling

Constructors

EOActionMenuController

```
public EOActionMenuController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOActionMenuController()
```

Description forthcoming.

Instance Methods

actionWidget

```
public javax.swing.JComponent actionWidget()
```

Description forthcoming.

actionWidgetToSubcontrollerAreaDistance

```
protected int actionWidgetToSubcontrollerAreaDistance()
```

Description forthcoming.

CLASS EOActionMenuController

createWidgetForActionsAndPlaceInContainer

```
protected void createWidgetForActionsAndPlaceInContainer(  
    NSArray aNSArray,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

disposeActionWidget

```
protected void disposeActionWidget()
```

Description forthcoming.

updateActionWidgetEnabling

```
protected void updateActionWidgetEnabling()
```

Description forthcoming.

CLASS EOActionMenuController

EOActionWidgetController

Inherits from: EOComponentController : EOController : Object
Implements: EOActionWidgetController.ActionCollector
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
None (abstract class)	actionWidgetController

Method Types

All methods

EOActionWidgetController
 actionWidget
 actionWidgetContainer

CLASS EOActionWidgetController

actionWidgetPosition
actionWidgetToSubcontrollerAreaDistance
collectedActions
componentDidBecomeVisible
createWidgetForActionsAndPlaceInContainer
dispose
disposeActionWidget
generateComponent
resetActions
setActionWidgetContainer
setActionWidgetPosition
subcontrollerActionsDidChange
subcontrollerConnectionDidChange
updateActionWidgetEnabling

Constructors

EOActionWidgetController

```
public EOActionWidgetController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOActionWidgetController()
```

Description forthcoming.

Instance Methods

actionWidget

public abstract javax.swing.JComponent actionWidget()

Description forthcoming.

actionWidgetContainer

public javax.swing.JComponent actionWidgetContainer()

Description forthcoming.

actionWidgetPosition

public int actionWidgetPosition()

Description forthcoming.

actionWidgetToSubcontrollerAreaDistance

protected abstract int actionWidgetToSubcontrollerAreaDistance()

Description forthcoming.

collectedActions

public NSArray collectedActions()

Description forthcoming.

CLASS EOActionWidgetController

componentDidBecomeVisible

protected void componentDidBecomeVisible()

Description forthcoming.

createWidgetForActionsAndPlaceInContainer

```
protected abstract void createWidgetForActionsAndPlaceInContainer(  
    NSArray anNSArray,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

dispose

public void dispose()

Description forthcoming.

disposeActionWidget

protected abstract void disposeActionWidget()

Description forthcoming.

generateComponent

protected void generateComponent()

Description forthcoming.

resetActions

public void resetActions()

Description forthcoming.

CLASS EOActionWidgetController

setActionWidgetContainer

```
public void setActionWidgetContainer(javax.swing.JComponent aJComponent)
```

Description forthcoming.

setActionWidgetPosition

```
public void setActionWidgetPosition(int anInt)
```

Description forthcoming.

subcontrollerActionsDidChange

```
public void subcontrollerActionsDidChange(EOController anEOController)
```

Description forthcoming.

subcontrollerConnectionDidChange

```
public void subcontrollerConnectionDidChange(EOController anEOController)
```

Description forthcoming.

updateActionWidgetEnabling

```
protected abstract void updateActionWidgetEnabling()
```

Description forthcoming.

CLASS EOActionWidgetController

EOActionWidgets

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

actionMenuWithActions

buttonRowWithActions

disposeActionMenu

disposeButtonRow

disposeMenuBar

menuBarWithActions

CLASS EOActionWidgets

```
updateEnablingOfActionMenu  
updateEnablingOfButtonRow  
updateEnablingOfMenuBar
```

Constructors

EOActionWidgets

```
public EOActionWidgets()
```

Description forthcoming.

Static Methods

actionMenuWithActions

```
public static javax.swing.JComboBox actionMenuWithActions(  
    NSArray anNSArray,  
    EOController anEOController,  
    boolean aBoolean,  
    String aString)
```

Description forthcoming.

buttonRowWithActions

```
public static javax.swing.JComponent buttonRowWithActions(  
    NSArray anNSArray,  
    EOController anEOController,  
    boolean aBoolean,  
    boolean aBoolean,  
    boolean aBoolean)
```

Description forthcoming.

CLASS EOActionWidgets

disposeActionMenu

```
public static void disposeActionMenu(javax.swing.JComboBox aJComboBox)
```

Description forthcoming.

disposeButtonRow

```
public static void disposeButtonRow(javax.swing.JComponent aJComponent)
```

Description forthcoming.

disposeMenuBar

```
public static void disposeMenuBar(javax.swing.JMenuBar aJMenuBar)
```

Description forthcoming.

menuBarWithActions

```
public static javax.swing.JMenuBar menuBarWithActions(  
    NSArray aNSArray,  
    EOController anEOController,  
    boolean aBoolean)
```

Description forthcoming.

updateEnablingOfActionMenu

```
public static void updateEnablingOfActionMenu(javax.swing.JComboBox aJComboBox)
```

Description forthcoming.

updateEnablingOfButtonRow

```
public static void updateEnablingOfButtonRow(javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOActionWidgets

updateEnablingOfMenuBar

```
public static void updateEnablingOfMenuBar(javax.swing.JMenuBar aMenuBar)
```

Description forthcoming.

EOApplet

Inherits from: javax.swing.JApplet
Package: com.webobjects.eoapplication

Class Description

EOApplet is the default Applet class embedded in WebObjects pages containing a WOJavaClientApplet dynamic element. EOApplet's only task is to read all the application's arguments (passed as HTML parameters) and forward them to the initialization code in EOApplication. For maximum flexibility, any application specific code should be implemented in EOApplication's `finishInitialization` method rather than EOApplet's `init` method.

In the controller hierarchy, the applet is represented by an EOAppletController, which becomes a client subcontroller of the EOApplication object.

EOApplet is used in Java Client applications only; there is no equivalent class on the server.

Constructors

EOApplet

```
public EOApplet()
```

Description forthcoming.

Instance Methods

destroy

```
public void destroy()
```

Description forthcoming.

init

```
public void init()
```

Instantiates an EOAppletController for the controller hierarchy and invokes EOApplication's startApplication using parameters retrieved via Applet's getParameter.

EOAppletController

Inherits from: EOComponentController : EOController : Object

Package: com.webobjects.eoapplication

Class Description

This class represents an EOApplet as a controller in the controller hierarchy. When the application is running as an applet, this controller is the direct descendent of the EOApplication in the controller hierarchy. It performs the analogous function as a EOWindowController when the application is running as a Java application.

XML Tag	Default Rule System Controller Type
None (abstract class)	None

Method Types

All methods

EOAppletController

applet

CLASS EOAppletController

```
setApplet  
setVisible  
showInSupercontroller
```

Constructors

EOAppletController

```
public EOAppletController(EOApplet applet)
```

Creates an applet controller for `applet`.

Instance Methods

applet

```
public EOApplet applet()
```

Returns the receiver's applet.

setApplet

```
protected void setApplet(EOApplet applet)
```

Sets the receiver's applet to `applet`.

setVisible

```
public void setVisible(boolean flag)
```

Sets the visibility of the applet according to `flag`. Since applets can not be made invisible, this method does nothing if `visible` is `false`.

CLASS EOAppletController

showInSupercontroller

```
public boolean showInSupercontroller()
```

Properly integrates the content of the applet (usually a component of a EOInterfaceController).

CLASS EOAppletController

EOApplication

Inherits from: EOController : Object

Package: com.webobjects.eoapplication

Class Description

Java Client applications typically execute from the command line (often referred to as a “Java application”) or as an applet running in a browser. EOApplication insulates the developer from this distinction by serving as an execution-mode-independent repository for application-level client-side logic. The provided JApplet subclass EOApplet simply invokes EOApplication with the HTML arguments as parameters.

Each application has a window observer which keeps track of all of the windows in the application, which window is active, and whether all windows have been closed. The window observer has two notifications: `ActiveWindowChangedNotification` and `LastWindowClosedNotification`, which the `finishInitialization` method binds to the `activeWindowDidChange` and `lastWindowDidClose` methods, respectively.

Each application also has a defaults manager, an `EODefaults` object, which maintains two dictionaries for application defaults: a transient dictionary whose values are forgotten when the application exits, and a persistent dictionary whose values are stored on the server. The defaults manager implements `valueForKey` to read the defaults and `setPersistentValueForKey` and `setTransientValueForKey` to store the defaults.

CLASS EOApplication

EOApplication is used in Java Client application only; there is no equivalent class on the server side.

XML Tag	Default Rule System Controller Type
None	None

Constants

Constant	Description
ApplicationDidStart	Description forthcoming.
ApplicationWillQuit	Description forthcoming.

Interfaces Implemented

NSDisposable

dispose

EOKeyValueCodingAdditions (com.webobjects.eocontrol)

EOAction.Enabling

canPerformActionNamed

EOKeyValueCoding (com.webobjects.eocontrol inherited from EOKeyValueCodingAdditions)

NSKeyValueCoding (inherited from EOKeyValueCoding)

Method Types

Accessing the shared instance

sharedApplication

Entering the application

main

startApplication

Initializing and terminating the application

canQuit

finishInitialization

quitsOnLastWindowClose

setCanQuit

setQuitsOnLastWindowClose

CLASS EOApplication

Managing the application

arguments

defaults

languages

Managing documents

documents

documentsForGlobalID

editedDocuments

hasEditedDocuments

Managing the window observer

activeWindowDidChange

lastWindowDidClose

setWindowObserver

windowObserver

Methods inherited from Object

toString

Performing main menu operations

activatePreviousWindow

collectChangesFromServer

defaultActions

saveAll

quit

Constructors

EOApplication

```
public EOApplication()
```

Description forthcoming.

Static Methods

main

```
public static void main(String[] args[])
```

This is the standard entry point for applications started from the command line (not in an applet). The `args` array contains the application's command-line arguments (for example, `-key1 value1 -key2 value2 ...`), which are stored in a parameter dictionary (`NSDictionary`). The user must specify an application URL (using the `-applicationURL <application URL>` argument), the name of a distribution channel class (using the `-channelClassName <channel class name>` argument), or both depending on the specific distribution channel. If the user specifies the application URL, he can optionally specify any initial entry page other than `Main`.

After instantiating an `EODistributionChannel` on the basis of these two parameters, `main` simply invokes `startApplication`.

sharedApplication

```
public static EOApplication sharedApplication()
```

Returns the `EOApplication` instance initialized via the `startApplication` method, throwing an `IllegalStateException` if `startApplication` has not yet been invoked.

CLASS EOApplication

startApplication

```
public static EOApplication startApplication(  
    NSDictionary parameterDictionary,  
    EOComponentController initialTopComponentController,  
    boolean remoteRequestArguments)
```

Creates an EOApplication. An application can execute from the command line or as an applet.

EOApplication's parameters are specified using `parameterDictionary`. If the application is a Java application, the EOApplication's `main` method reads and parses the parameters from the command line. In addition, it sets `remoteRequestArguments` to `true`, which triggers `startApplication` to read additional parameters from the applet at the URL specified on the command line. If the application is started in an applet, all parameters are contained in the HTML.

The `initialTopComponentController` parameter specifies the top-most EOComponentController in the controller hierarchy. For applets, this controller is an EOAppletController. For command line applications, the `main` method sets `initialTopComponentController` to `null`, which causes a new EOFrameController to be instantiated and used as the top-most EOComponentController.

Instance Methods

activatePreviousWindow

```
public void activatePreviousWindow()
```

Activates the previously active window. The user can invoke this method from the Window menu.

activeWindowDidChange

```
public void activeWindowDidChange(NSNotification aNSNotification)
```

This method is invoked when the user changes the active window in the receiver (usually by clicking in an inactive window). It is invoked via a notification from the receiver's window observer.

CLASS EOApplication

arguments

```
public NSDictionary arguments()
```

Returns all of the receiver's arguments in a dictionary. If the application is a Java application (and not an Applet), the arguments can come from both the command line and the applet at the URL specified on the command line.

canPerformActionNamed

```
public boolean canPerformActionNamed(String actionName)
```

Conformance to `EOAction.Enabling`. See the method description of `canPerformActionNamed` in the interface specification for `EOAction.Enabling`. An action may be disallowed if it is disabled or is an `activatePreviousWindow` action and the first window is active.

canQuit

```
public boolean canQuit()
```

Returns whether or not the receiver has a Quit item in the File submenu. Defaults to `true` if the application is run from the command line and `false` if it is started in an applet.

collectChangesFromServer

```
public void collectChangesFromServer()
```

Updates the receiver's Enterprise Objects to reflect the changes sent to the server from other client applications. By default, the application does not automatically update its objects, however, the user can update the objects manually from the Document menu in Direct to Java Client applications.

defaultActions

```
protected NSArray defaultActions()
```

Returns an NSArray containing the actions (EOAction objects) the receiver can perform.

CLASS EOApplication

defaults

```
public EODefaults defaults()
```

Returns the receiver's defaults manager (an EODefaults object). If your application requires the user to log in, you should override this method so it returns `null` until the user logs in.

dispose

```
public void dispose()
```

Prepares the receiver so it is disposed when Java performs garbage collection.

documents

```
public NSArray documents()
```

Returns an NSArray containing the receiver's visible documents (EODocument objects).

documentsForGlobalID

```
public NSArray documentsForGlobalID(  
    com.webobjects.eocontrol.EOGlobalID globalID,  
    String entityName)
```

Returns an NSArray containing the receiver's visible documents (EODocument objects) that edit Enterprise Objects with an entity name matching `entityName` and global ID matching `globalID`.

editedDocuments

```
public NSArray editedDocuments()
```

Returns an NSArray containing the receiver's visible documents (EODocument objects) that have been edited.

CLASS EOApplication

finishInitialization

```
protected void finishInitialization()
```

This method is invoked after the final event thread is guaranteed to be running. If you subclass EOApplication, use this method to initialize anything relating to the user interface or event-handling. Do not perform such initialization using EOApplication's constructor.

hasEditedDocuments

```
public boolean hasEditedDocuments()
```

Returns `true` if any of the receiver's documents has been edited. Otherwise returns `false`.

languages

```
public NSArray languages()
```

Returns an NSArray containing the language names (Strings) for which the application is localized. An example language is `English`.

lastWindowDidClose

```
public void lastWindowDidClose(NSNotification aNSNotification)
```

This method is invoked when the user closes the last window in the receiver. It is invoked as a notification from the receiver's window observer.

See Also: `quitsOnLastWindowClose`

quit

```
public void quit()
```

Causes the receiver to quit (provided `canQuit` is `true`).

See Also: `canQuit`

CLASS EOApplication

quitsOnLastWindowClose

```
public boolean quitsOnLastWindowClose()
```

Returns whether or not the receiver quits when the user closes all of its windows. Defaults to true.

saveAll

```
public boolean saveAll()
```

Attempts to save all of the receiver's edited documents and returns true if it succeeds.

sessionDidTimeOut

```
public void sessionDidTimeOut()
```

Description forthcoming.

setCanQuit

```
public void setCanQuit(boolean flag)
```

Sets whether or not the application has a quit item in the File menu.

setQuitsOnLastWindowClose

```
public void setQuitsOnLastWindowClose(boolean flag)
```

Sets whether or not the receiver quits when the user closes all of its windows.

setWindowObserver

```
public void setWindowObserver(EOWindowObserver anEOWindowObserver)
```

Sets the receiver's window observer to *anEOWindowObserver*. The window observer manages the application's windows: which window is active, how many there are, etc.

CLASS EOApplication

toString

```
public String toString()
```

Returns the receiver as a string that contains the results of the EOController's `toString` method, the languages the receiver supports, and the status of the `canQuit` and `quitsOnLastWindowClose` flags.

windowObserver

```
public EOWindowObserver windowObserver()
```

Returns the receiver's window observer.

CLASS EOApplication

EOArchive

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

EOArchive

loadArchiveNamed

loadArchiveNamed

debug

disposableRegistry

namedObjects

CLASS EOArchive

Constructors

EOArchive

```
public EOArchive(  
    Object anObject,  
    NSDisposableRegistry aNSDisposableRegistry)
```

Static Methods

loadArchiveNamed

```
public static NSDictionary loadArchiveNamed(  
    String aString,  
    Object anObject,  
    String aString,  
    NSDisposableRegistry aNSDisposableRegistry)
```

loadArchiveNamed

```
public static boolean loadArchiveNamed(  
    String aString,  
    Object anObject,  
    String aString)
```


Instance Methods

debug

protected void debug(String aString)

disposableRegistry

public NSDisposableRegistry disposableRegistry()

namedObjects

public NSDictionary namedObjects()

EOBeanSupport

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

beanBases

beanClassLoader

beanClassName

beanCodeBase

beanDocBase

beanReadyToRun

CLASS EBeanSupport

beanReadyToUse

beanSuperClassName

looksInstantiable

looksSerializable

Constructors

EBeanSupport

public EBeanSupport()

Description forthcoming.

Static Methods

beanBases

public static java.net.URL[] beanBases(Object anObject)

Description forthcoming.

beanClassLoader

public static ClassLoader beanClassLoader(Object anObject)

Description forthcoming.

beanClassName

public static String beanClassName(Object anObject)

Description forthcoming.

CLASS EOBeanSupport

beanCodeBase

public static java.net.URL beanCodeBase(Object anObject)

Description forthcoming.

beanDocBase

public static java.net.URL beanDocBase(Object anObject)

Description forthcoming.

beanReadyToRun

public static Object beanReadyToRun(Object anObject)

Description forthcoming.

beanReadyToUse

public static Object beanReadyToUse(Object anObject)

Description forthcoming.

beanSuperclassName

public static String beanSuperclassName(Object anObject)

Description forthcoming.

looksInstantiable

public static boolean looksInstantiable(Object anObject)

Description forthcoming.

CLASS EOBeanSupport

looksSerializable

```
public static boolean looksSerializable(Object anObject)
```

Description forthcoming.

EoBoxController

Inherits from: EOComponentController : EOController : Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
BOXCONTROLLER	groupingController

Constants

Constant	Description
EtchedBorder	Description forthcoming.
LineBorder	Description forthcoming.
LoweredBezelBorder	Description forthcoming.
NoBorder	Description forthcoming.
RaisedBezelBorder	Description forthcoming.

Method Types

All methods

E0BoxController
borderType
generateComponent
highlightsTitle
horizontalBorder
setBorderType
setHighlightsTitle
setHorizontalBorder
setTitleColor
setTitleFont

CLASS EOBoxController

setTitlePosition
setUsesTitledBorder
setVerticalBorder
titleColor
titleFont
titlePosition
usesTitledBorder
verticalBorder

Constructors

EOBoxController

```
public EOBoxController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOBoxController()
```

Description forthcoming.

Instance Methods

borderType

```
public int borderType()
```

Description forthcoming.

CLASS EOBoxController

generateComponent

protected void generateComponent()

Description forthcoming.

highlightsTitle

public boolean highlightsTitle()

Description forthcoming.

horizontalBorder

public int horizontalBorder()

Description forthcoming.

setBorderType

public void setBorderType(int anInt)

Description forthcoming.

setHighlightsTitle

public void setHighlightsTitle(boolean aBoolean)

Description forthcoming.

setHorizontalBorder

public void setHorizontalBorder(int anInt)

Description forthcoming.

CLASS EBoxController

setTitleColor

```
public void setTitleColor(java.awt.Color aColor)
```

Description forthcoming.

setTitleFont

```
public void setTitleFont(java.awt.Font aFont)
```

Description forthcoming.

setTitlePosition

```
public void setTitlePosition(int anInt)
```

Description forthcoming.

setUsesTitledBorder

```
public void setUsesTitledBorder(boolean aBoolean)
```

Description forthcoming.

setVerticalBorder

```
public void setVerticalBorder(int anInt)
```

Description forthcoming.

titleColor

```
public java.awt.Color titleColor()
```

Description forthcoming.

CLASS EOBoxController

titleFont

```
public java.awt.Font titleFont()
```

Description forthcoming.

titlePosition

```
public int titlePosition()
```

Description forthcoming.

usesTitledBorder

```
public boolean usesTitledBorder()
```

Description forthcoming.

verticalBorder

```
public int verticalBorder()
```

Description forthcoming.

EOComponentController

Inherits from:	EOController : Object
Implements:	NSDisposable (Inherited from EOController) com.webobjects.eocontrol.EOKeyValueCodingAdditions (Inherited from EOController) EOAction.Enabling (Inherited from EOController) com.webobjects.eocontrol.EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions) com.webobjects.foundation.NSKeyValueCoding (Inherited from EOKeyValueCoding)
Package:	com.webobjects.eoapplication

Class Description

The EOComponentController class provides behavior for controllers that manage user interface components. A component controller has a **component** , that represents the user interface for the controller itself (not for its subcontrollers), a **subcontroller area** for displaying the user interfaces for its subcontrollers, and an **integration component** —a component that represents the controller when its shown in its supercontrollers user interface.

By default, a controller's integration component is simply the controller's component. In other words, a supercontroller adds its subcontrollers' components to the subcontroller area of its component. However, the integration component can be a completely separate component. For example, the integration component for a window controller is a button that, when pushed, opens the window controller's window.

CLASS `EOComponentController`

Also by default, a controller's subcontroller area is simply the controller's component. In the simplest case, a component controller doesn't have its own user interface, but only serves to display the user interfaces of its subcontrollers. For example, `EOComponentController`'s component is simply an `EOView`. It puts nothing in the view except its subcontrollers' user interfaces. Thus, the subcontroller area is the controller's component—the `EOView`. However, the subcontroller area can be a subcomponent of the controller's component. For example, an `EOBoxController`'s component contains a border (etched or bezel, for example) which is the box controller's user interface. Its subcontroller area is a component located inside the border. This is where the box controller displays its subcontrollers.

Managing the Component

To access a component controller's component, use the method `component`. If the component hasn't yet been created, `component` creates it by invoking `prepareComponent`. And `prepareComponent`, in turn, invokes `generateComponent` to dynamically create the component. Subclasses should override `generateComponent`.

To see if a controller's component has been created, use the method `isComponentPrepared`. Sometimes you need to know if a component has been created, because you can't configure its behavior after its creation. For example, if you want to set a component's alignment behavior, you have to set it with the `EOComponentController` method `setAlignsComponents` before the component controller creates its component.

Visibility

A component controller is visible when its component is visible on screen. When a controller becomes visible, it ensures that it's connected to its supercontroller. However, a controller that's connected to its supercontroller isn't necessarily visible. For example, you might connect an invisible controller when you need to prepare it with data before making it visible.

Similarly, a controller can be "shown" or "hidden" in its supercontroller without changing the controller's visibility. The method `showInSupercontroller` ensures that the receiver's integration component is displayed in its supercontroller's component. This doesn't necessarily change the visibility of the controller. For example, a tab switch controller might switch to another view, but if the switch controller isn't visible when the change occurs, the subcontroller doesn't become visible.

Component Appearance

A component controller's component can have an icon and a label. The component can be represented in the user interface with icon only, label only, or with both icon and label. A component specifies which representation it prefers. A controller can *prefer* to be represented with an icon only, but can't require it. This is because the controller might not have an icon. If the controller prefers icon only and has an icon, then the controller is represented with the icon only. If the controller doesn't prefer icon only and has an icon, then the controller is represented with its icon and label. If the controller doesn't have an icon, the controller is represented with the label only.

A controller always has a label. If the controller's label hasn't been explicitly set, the controller derives one from its subcontrollers.

Layout

Subclasses of `EOComponentController` have complete control over how they lay out their subcontrollers. `EOComponentController`'s implementation can lay out subcontrollers in a row or a column (the default). To change the layout direction, the method `setUsesHorizontalLayout`.

In addition to horizontal/vertical layout behavior, a component can align its components or not. For example, consider a controller that uses vertical layout and contains several `EOTextFieldControllers`. If the controller aligns components, it left aligns the text fields. The default alignment behavior aligns components by making their corresponding labels identically sized. The width of the labels is known as the **alignment width** .

To specify a component's alignment behavior, use the method `setAlignsComponents`. To set the alignment width, use `setAlignmentWidth`.

Resizing

`EOComponentController` implements complex resizing behavior. For example, if a controller's component changes in a way that might affect its minimum size, the controller's supercontroller is notified and the supercontroller ensures that its subcontroller area is at least as big as the minimum size required to show all its subcontrollers.

Using the default behavior, the user interface doesn't automatically shrink. `EOComponentController` only resizes up to meet the minimum requirements. As much as possible it resizes components to fill the available space. A component controller can specify both horizontal and vertical resizing behavior for its component to accommodate this scheme.

Rule System and XML Description

The following tables identify the `controllerType`, XML tag, and XML attributes used by the rule system and EOXMLUnarchiver to generate a controller hierarchy. For more information, see the section [“Rule System and XML Description”](#) (page 8) in the package introduction.

Default Rule System Controller Type

groupingController

XML Tag

COMPONENTCONTROLLER

XML Attribute	Value	Description
<code>alignmentWidth</code>	integer	See “Layout” (page 97).
<code>alignsComponents</code>	“true” or “false”	See “Layout” (page 97).
<code>horizontallyResizable</code>	“true” or “false”	See “Resizing” (page 97).
<code>iconName</code>	string	The filename of the component’s icon. Uses standard resource location behavior to find the icon by name. See “Component Appearance” (page 97) for more information.
<code>iconURL</code>	string	The URL from which the icon is downloaded. See “Component Appearance” (page 97) for more information.
<code>label</code>	string	See “Component Appearance” (page 97).
<code>minimumHeight</code>	integer	The minimum height of the controller’s component, not including its subcontroller area.
<code>minimumWidth</code>	integer	The minimum width of the controller’s component, not including its subcontroller area.
<code>prefersIconOnly</code>	“true” or “false”	See “Component Appearance” (page 97).
<code>usesHorizontalLayout</code>	“true” or “false”	See “Layout” (page 97).
<code>verticallyResizable</code>	“true” or “false”	See “Resizing” (page 97).

Constants

Constant	Description
Bottom	Description forthcoming.
BottomLeft	Description forthcoming.
BottomRight	Description forthcoming.
Center	Description forthcoming.
Left	Description forthcoming.
Right	Description forthcoming.
Top	Description forthcoming.
TopLeft	Description forthcoming.
TopRight	Description forthcoming.

Interfaces Implemented

NSDisposable (Inherited from EOController)

dispose

EOKeyValueCodingAdditions (Inherited from EOController)

EOAction.Enabling (Inherited from EOController)

EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions)

handleQueryWithUnboundKey

handleTakeValueForUnboundKey

unableToSetNullForKey

NSKeyValueCoding (Inherited from EOKeyValueCoding)

Method Types

Constructors

EOComponentController

Managing the component

generateComponent

prepareComponent

setComponent

component

isComponentPrepared

CLASS EOComponentController

Managing the integration component

integration ComponentDidBecomeInvisible
integrationComponentDidBecomeVisible
integrationComponent

Managing the subcontroller area

setSubcontrollerArea
subcontrollerArea
addComponentOfSubcontroller
removeComponentOfSubcontroller

Managing component visibility

showInSupercontroller
makeVisible
componentDidBecomeVisible
showSubcontroller
hideInSupercontroller
makeInvisible
componentDidBecomeInvisible
hideSubcontroller
setVisible
isVisible

Setting component appearance

setPrefersIconOnly
prefersIconOnly
setIcon
icon
setLabel
label

CLASS EOComponentController

Layout behavior

setUsesHorizontalLayout

usesHorizontalLayout

setAlignsComponents

alignsComponents

setAlignmentWidth

alignmentWidth

Resizing behavior

setCanResizeHorizontally

canResizeHorizontally

setCanResizeVertically

canResizeVertically

Configuring user interface sizes

setDefaultComponentSize

defaultComponentSize

ensureMinimumComponentSizeWithoutSubcontrollers

ensureMinimumSubcontrollerAreaSize

subcontrollerMinimumSizeDidChange

minimumComponentSize

minimumComponentSizeWithoutSubcontrollers

minimumIntegrationComponentSize

minimumSubcontrollerAreaSize

Determining the root component controller

isRootComponentController

Methods inherited from EOController

canBeTransient

removeTransientSubcontroller

CLASS EOComponentController

subcontrollerWasAdded

subcontrollerWasRemoved

Methods inherited from Object

toString

Constructors

EOComponentController

```
public EOComponentController(EOXMLUnarchiver unarchiver)
```

Creates a new component controller. For information on how these constructors are used and on what they do, see the method description for the `EOController` constructors in the `EOController` class specification.

```
public EOComponentController()
```

Description forthcoming.

Instance Methods

addComponentOfSubcontroller

```
protected void addComponentOfSubcontroller(EOComponentController controller)
```

Adds the integration component for the receiver's subcontroller, `controller`, to the user interface for the receiver.

CLASS EOComponentController

alignmentWidth

```
public int alignmentWidth()
```

Returns the receiver's alignment width.

See Also: [“Layout”](#) (page 97)

alignsComponents

```
public boolean alignsComponents()
```

Returns `true` if the receiver aligns its components, `false` otherwise.

See Also: [“Layout”](#) (page 97)

canBeTransient

```
public boolean canBeTransient()
```

Returns `true` if the controller can be transient, `false` otherwise. By default, a component controller is transient only if it's an instance of `EOComponentController`, not an instance of a subclass.

See Also: `canBeTransient` (`EOController`)

canResizeHorizontally

```
public boolean canResizeHorizontally()
```

Returns `true` if the receiver can resize its component horizontally, or `false` otherwise.

See Also: [“Resizing”](#) (page 97)

canResizeVertically

```
public boolean canResizeVertically()
```

Returns `true` if the receiver can resize its component vertically, or `false` otherwise.

See Also: [“Resizing”](#) (page 97)

CLASS `EOComponentController`

`component`

```
public javax.swing.JComponent component()
```

Returns the receiver's component, creating and preparing it first if it doesn't already exist.

See Also: [“Managing the Component”](#) (page 96), `prepareComponent`, `generateComponent`

`componentDidBecomeInvisible`

```
protected void componentDidBecomeInvisible()
```

Invoked by the receiver's supercontroller when the receiver's component becomes invisible, giving the receiver a chance to respond. `EOComponentController`'s implementation invokes `breakConnection` to break the receiver's connection to the controller hierarchy.

`componentDidBecomeVisible`

```
protected void componentDidBecomeVisible()
```

Invoked by the receiver's supercontroller when the receiver's component becomes visible, giving the receiver a chance to respond. `EOComponentController`'s implementation invokes `establishConnection` to ensure the receiver is connected to the controller hierarchy.

`defaultComponentSize`

```
public java.awt.Dimension defaultComponentSize()
```

Returns the default size for the receiver's component. This is the size the component is set to when it's created.

See Also: [“Resizing”](#) (page 97)

`dispose`

```
public void dispose()
```

Conformance to `NSDisposable`. See the method description of `dispose` in the interface specification for `NSDisposable`.

CLASS EOComponentController

ensureMinimumComponentSizeWithoutSubcontrollers

```
public void ensureMinimumComponentSizeWithoutSubcontrollers(  
    int width,  
    int height)
```

Ensures that the size of the receiver's component, not including the subcontroller area, is at least as large as the area specified by `width` and `height`. If it isn't, the receiver resizes its component to `width` and `height`. This method is invoked by the receiver itself when its component is changed in a way that might affect the component's minimum size. For example, suppose a label is changed and requires a larger space.

See Also: [“Resizing”](#) (page 97)

ensureMinimumSubcontrollerAreaSize

```
public void ensureMinimumSubcontrollerAreaSize(  
    int width,  
    int height)
```

Ensures that the size of the receiver's subcontroller area is at least as large as the area specified by `width` and `height`. If it isn't, the receiver resizes its subcontroller area to `width` and `height`. This method is invoked when a subcontroller's component changes in a way that might affect its minimum size.

See Also: [“Resizing”](#) (page 97)

generateComponent

```
protected void generateComponent()
```

Creates the receiver's component, including setting up the subcontroller area. Implementations of these methods usually invoke `setComponent` and if necessary `setSubcontrollerArea`. EOComponentController creates an EOView.

See Also: [“Managing the Component”](#) (page 96)

CLASS EOComponentController

handleTakeValueForUnboundKey

```
public void handleTakeValueForUnboundKey(  
    Object value,  
    String key)
```

Conformance to EOKeyValueCoding. See the method description of `handleTakeValueForUnboundKey` in the interface specification for EOKeyValueCoding.

hideInSupercontroller

```
public boolean hideInSupercontroller()
```

Invokes `hideSubcontroller` on the receiver's supercontroller to hide the receiver's component if the component (or integration component) appears in the supercontroller's user interface. Returns `true` on success, `false` otherwise. If the receiver doesn't have a supercontroller, then this method simply makes the receiver invisible. For example, a window controller which is the root component controller simply closes.

This method is invoked automatically (for example, from `makeInvisible`). You should never need to invoke it yourself.

See Also: [“Visibility”](#) (page 96)

hideSubcontroller

```
protected boolean hideSubcontroller(EOComponentController controller)
```

Hides `controller`'s user interface in the interface of the receiver. Returns `true` if the subcontroller was successfully hidden, `false` otherwise. EOComponentController's implementation simply returns `false`. This is because most controllers can't hide their subcontrollers. Examples of controllers that can hide their subcontrollers are tab view controllers, which hide a subcontroller by making another subcontroller visible. Don't invoke this method directly; invoke `hideInSupercontroller` instead.

See Also: [“Visibility”](#) (page 96)

CLASS EOComponentController

icon

```
public javax.swing.Icon icon()
```

Returns the receiver's icon, or `null` if it has none.

See Also: [“Component Appearance”](#) (page 97)

integrationComponent

```
public javax.swing.JComponent integrationComponent()
```

Returns the component used as the integration component in the receiver's supercontroller to represent the receiver. EOComponentController returns its component by default.

See Also: [“Class Description”](#) (page 95)

integrationComponentDidBecomeInvisible

```
protected void integrationComponentDidBecomeInvisible()
```

Invoked by the receiver's supercontroller when the receiver's integration component becomes invisible, giving the receiver a chance to respond. EOComponentController's implementation sets the receiver's visibility to be `false`, because by default the integration component is identical to the component.

integrationComponentDidBecomeVisible

```
protected void integrationComponentDidBecomeVisible()
```

Invoked by the receiver's supercontroller when the receiver's integration component becomes visible, giving the receiver a chance to respond. EOComponentController's implementation sets the receiver's visibility to be `true`, because by default the integration component is identical to the component.

CLASS `EOComponentController`

`isComponentPrepared`

```
protected boolean isComponentPrepared()
```

Returns `true` if the receiver is prepared, `false` otherwise.

See Also: [“Managing the Component”](#) (page 96)

`isRootComponentController`

```
public boolean isRootComponentController()
```

Returns `true` if the receiver is a root component controller, `false` otherwise. A component controller is the root component controller if its supercontroller is not an instance of `EOComponentController`.

`isVisible`

```
public boolean isVisible()
```

Returns `true` if the receiver is visible, `false` otherwise. A component controller is visible if its component is on the screen. Note, showing a subcontroller in its supercontroller doesn't necessarily mean that it is visible. For example, you can show a component in a tab view, but the component won't be visible unless the tab view is visible.

See Also: [“Visibility”](#) (page 96)

`label`

```
public String label()
```

Returns the receiver's label. If the label is not explicitly set, `EOComponentController`'s implementation attempts to derive a label from its subcontrollers.

See Also: [“Component Appearance”](#) (page 97)

CLASS `EOComponentController`

makeInvisible

```
public boolean makeInvisible()
```

Makes the receiver's user interface invisible. If the receiver's supercontroller is a component controller, makes the receiver invisible by making the receiver's supercontroller invisible. Otherwise, invokes `hideInSupercontroller`. Returns `true` if the method succeeds in making the receiver invisible, `false` otherwise.

makeVisible

```
public boolean makeVisible()
```

Makes the receiver's user interface visible. Establishes the receiver's connection to its supercontrollers and invokes `showInSupercontroller`. If the receiver's supercontroller is a component controller, it also attempts to make the supercontroller visible. Returns `true` if the method succeeds in making the receiver visible, `false` otherwise.

See Also: [“Visibility”](#) (page 96)

minimumComponentSize

```
public java.awt.Dimension minimumComponentSize()
```

Returns the current minimum size required to display the receiver's component, including the size required for its subcontroller area.

See Also: [“Resizing”](#) (page 97)

minimumComponentSizeWithoutSubcontrollers

```
public java.awt.Dimension minimumComponentSizeWithoutSubcontrollers()
```

Returns the current minimum size required to display the receiver's component, excluding the subcontroller area.

See Also: [“Resizing”](#) (page 97)

CLASS EOComponentController

minimumIntegrationComponentSize

```
public java.awt.Dimension minimumIntegrationComponentSize()
```

Returns the minimum size required to display the receiver's integration component.

See Also: [“Resizing”](#) (page 97)

minimumSubcontrollerAreaSize

```
public java.awt.Dimension minimumSubcontrollerAreaSize()
```

Returns the minimum size of the subcontroller area to display the receiver's subcontrollers.

See Also: [“Resizing”](#) (page 97)

prefersIconOnly

```
public boolean prefersIconOnly()
```

Returns `true` if the receiver prefers to represent itself with only an icon, `false` otherwise.

See Also: [“Component Appearance”](#) (page 97)

prepareComponent

```
protected void prepareComponent()
```

If the receiver's component is not already prepared, it generates the component.

See Also: [“Managing the Component”](#) (page 96)

removeComponentOfSubcontroller

```
protected void removeComponentOfSubcontroller(EOComponentController controller)
```

Removes the user interface for the specified subcontroller, `controller`, from the receiver's user interface and informs `controller` that its integration component became invisible.

CLASS EOComponentController

removeTransientSubcontroller

```
protected boolean removeTransientSubcontroller(EOController controller)
```

See the method description for `removeTransientSubcontroller` in the `EOController` class specification.

setAlignmentWidth

```
public void setAlignmentWidth(int alignmentWidth)
```

Sets the receiver's alignment width to `alignmentWidth`. Throws an `IllegalStateException` if the receiver is already prepared. In other words, you can only set the alignment width before the component is generated.

See Also: [“Layout”](#) (page 97)

setAlignsComponents

```
public void setAlignsComponents(boolean flag)
```

Sets according to `flag` whether the receiver aligns the components in its user interface. Throws an `IllegalStateException` if the receiver is already prepared. In other words, you can only set the alignment behavior before the component is generated.

See Also: [“Layout”](#) (page 97)

setCanResizeHorizontally

```
public void setCanResizeHorizontally(boolean flag)
```

Sets according to `flag` whether the receiver's component can resize horizontally. Throws an `IllegalStateException` if the receiver is already prepared. In other words, you can only set the horizontal resizing behavior before the component is generated.

See Also: [“Resizing”](#) (page 97)

CLASS EOComponentController

setCanResizeVertically

```
public void setCanResizeVertically(boolean flag)
```

Sets according to `flag` whether the receiver's component can resize vertically. Throws an `IllegalStateException` if the receiver is already prepared. In other words, you can only set the vertical resizing behavior before the component is generated.

See Also: [“Resizing”](#) (page 97)

setComponent

```
public void setComponent(java.awt.Component component)
```

Sets the receiver's component to `component`.

See Also: [“Managing the Component”](#) (page 96)

setDefaultComponentSize

```
public void setDefaultComponentSize(java.awt.Dimension dimension)
```

Sets the default size of the receiver's component to `dimension`.

See Also: [“Resizing”](#) (page 97)

setIcon

```
public void setIcon(javax.swing.Icon icon)
```

Sets the receiver's icon to `icon`.

See Also: [“Component Appearance”](#) (page 97)

setLabel

```
public void setLabel(String label)
```

Sets the receiver's label to `label`.

See Also: [“Component Appearance”](#) (page 97)

CLASS EOComponentController

setPrefersIconOnly

```
public void setPrefersIconOnly(boolean flag)
```

Sets according to `flag` whether the receiver prefers to represent itself with only an icon or with an icon and a label.

See Also: [“Component Appearance”](#) (page 97)

setSubcontrollerArea

```
public void setSubcontrollerArea(javax.swing.JComponent component)
```

Sets the component that holds the user interface for the receiver’s subcontrollers to `component`.

See Also: [“Class Description”](#) (page 95)

setUsesHorizontalLayout

```
public void setUsesHorizontalLayout(boolean flag)
```

Sets according to `flag` whether the receiver uses horizontal layout. Throws an `IllegalStateException` if the receiver is already prepared. In other words, you can only set the layout direction before the component is generated.

See Also: [“Layout”](#) (page 97)

setVisible

```
public void setVisible(boolean flag)
```

Sets the visibility of the receiver according to `flag`. Invokes `componentDidBecomeVisible` or `componentDidBecomeInvisible` to notify the receiver that its visibility changed and to give the receiver the opportunity to respond appropriately. Also notifies the receiver’s ancestors that a subcontroller’s visibility has changed, giving the supercontrollers the opportunity to respond.

If `flag` is `true`, this method disposes of transient receivers after making them visible.

See Also: [“Visibility”](#) (page 96)

CLASS EOComponentController

showInSupercontroller

```
public boolean showInSupercontroller()
```

Invokes `showSubcontroller` to add the receiver's user interface to its supercontroller's receiver. **Returns** `true` on success, `false` otherwise. If the supercontroller is `null`, this method also makes the receiver visible.

Note: Invoking this method doesn't necessarily change the visibility of the receiver. For example, a switch controller might switch the component it displays, but if the switch controller isn't visible, the subcontroller doesn't become visible when it's shown.

This method is invoked automatically (for example, from `makeVisible`). You should never need to invoke it yourself.

See Also: [“Visibility”](#) (page 96)

showSubcontroller

```
protected boolean showSubcontroller(EOComponentController controller)
```

Adds `controller`'s user interface to the interface of the receiver. **Returns** `true` if the subcontroller was successfully shown, `false` otherwise. `EOComponentController`'s implementation simply returns `true`: Since the integration components for subcontrollers are added to a controller's user interface automatically, the subcontrollers are already shown. `EOTabSwitchController` is an example of a subclass that overrides this method in a meaningful way. To show one subcontroller, the tab switch controller hides another.

See Also: [“Visibility”](#) (page 96)

subcontrollerArea

```
public javax.swing.JComponent subcontrollerArea()
```

Returns the component that holds the user interface for the receiver's subcontrollers.

See Also: [“Class Description”](#) (page 95)

CLASS EOComponentController

subcontrollerMinimumSizeDidChange

```
public void subcontrollerMinimumSizeDidChange(  
    EOComponentController controller,  
    javax.swing.JComponent component,  
    java.awt.Dimension dimension)
```

Updates the receiver's user interface to accommodate a change to the subcontroller's minimum size. This method is invoked by subcontrollers when they change in a way that might affect their component's minimum size. A subcontroller sends this method with itself, its integration component, and its new minimum size as the arguments. The expectation is that the supercontroller will make space for the subcontroller if it needs to.

See Also: [“Resizing”](#) (page 97)

subcontrollerWasAdded

```
protected void subcontrollerWasAdded(EOController controller)
```

Invokes `addComponentOfSubcontroller` to add the integration component (if any) for the receiver's subcontroller, `controller`, to the receiver's user interface. Invoked from `addSubcontroller` to notify the receiver that its subcontroller `controller` has been added to the controller hierarchy.

subcontrollerWasRemoved

```
protected void subcontrollerWasRemoved(EOController controller)
```

Invokes `removeComponentOfSubcontroller` to remove the integration component (if any) for the receiver's subcontroller, `controller`, from the receiver's user interface. Invoked from `removeSubcontroller` to notify the receiver that its subcontroller `controller` has been removed from the controller hierarchy.

toString

```
public String toString()
```

Returns the receiver as a string that states the receiver's class name and type name, whether the receiver is connected, the number of subcontrollers, whether or not the receiver has been prepared, whether or not the receiver is visible, information about widget sizing and alignment behavior, and so on.

CLASS EOComponentController

usesHorizontalLayout

public boolean usesHorizontalLayout()

Returns true if the receiver uses a horizontal layout, false otherwise.

See Also: [“Layout”](#) (page 97)

CLASS EOComponentController

EOController

Inherits from:	Object
Implements:	NSDisposable NSKeyValueCodingAdditions EOAction.Enabling NSKeyValueCoding.ErrorHandling NSKeyValueCoding
Package:	com.webobjects.eoapplication

Class Description

The EOController class defines basic behavior for controller objects that are responsible for managing and sometimes generating the user interface for the client side of a Java Client application. An application's controllers are arranged in a hierarchy, which describes the complete functionality of an application.

The controller hierarchy mirrors the hierarchy of windows and widgets that make up the client application's user interface. The root of the hierarchy is an EOApplication object. The EOApplication's subcontrollers are usually window or applet controllers, which themselves have subcontrollers.

The most significant functionality provided by the EOController class is managing the controller hierarchy (building, connecting, and traversing the hierarchy) and handling actions.

Building the Controller Hierarchy

EOController defines methods for building the controller hierarchy. You can add and remove controllers (`addSubcontroller`, `removeFromSupercontroller`), be notified when the controller hierarchy changes (`subcontrollerWasAdded` and `subcontrollerWasRemoved`), and inquire about the relationships controllers have to one another (`subcontrollers`, `supercontroller`, `isAncestorOfController`, and `isSupercontrollerOfController`).

You might need to directly invoke the methods `addSubcontroller` and `removeFromSupercontroller` to programmatically manipulate the controller hierarchy. The base implementations of these methods are sufficient for most subclasses. They set and unset a controller's supercontroller (`setSupercontroller`) and notify that supercontroller that a subcontroller was added or removed.

If you write a custom controller and you need to do something special when a subcontroller is added to or removed from the controller hierarchy, override the methods `subcontrollerWasAdded` and `subcontrollerWasRemoved` to put your customizations there. Taking this approach, you shouldn't have to override the add and remove methods.

Traversing the Controller Hierarchy

EOController defines numerous methods for traversing the controller hierarchy, but a single method provides the basic traversal functionality. The method `controllerEnumeration` creates and returns an enumeration that includes all the descendants of a controller (not including the controller), all the ancestors of a controller (not including the controller), or a controller and its descendants. You can further restrict the controllers included in an enumeration by specifying an interface the controllers must implement in order to be included. For more information, see the `EOController.Enumeration` interface specification and the method description for `controllerEnumeration`.

Other methods that traverse the controller hierarchy use a controller enumeration to perform the traversal. There are methods that return controllers in an enumeration that match one or more key-value pairs. Methods that use key-value coding on the controllers in an enumeration, returning the first controller that has a specified key or returning the value for that key. Also, there's a method (`invokeMethod`) that invokes a particular method on the controllers in an enumeration.

Connecting Controllers

A controller in the controller hierarchy can be connected to its supercontroller or not. Controllers are connected when they're performing their duties, and they are disconnected when they become idle. Generally controllers are connected only when their user interface is visible. For example, the controllers associated with a window are connected when the window is visible, and they're disconnected when the window becomes invisible.

When a controller *connects* to its supercontroller, it gets from its supercontroller whatever resources or information it needs, and it prepares itself in whatever way necessary to perform its duties (for example, setting delegates). Similarly, when a controller breaks its connection to its supercontroller, it cleans up its resources for an idle period.

The EOController class defines methods for connecting controllers. There are methods for connecting and disconnecting a controller from its supercontroller (`establishConnection` and `breakConnection`), and also methods that make connections all the way up the controller hierarchy (`establishConnectionToSupercontrollers`) and break connections all the way down (`breakConnectionToSubcontrollers`). Generally you use the latter methods that connect or disconnect an entire branch of a tree. EOController's implementations of all these methods is generally sufficient for subclasses. They set the connection status of a controller (`setConnected`), and notify the controller that its connection has been established or broken. You shouldn't have to override these methods.

If you do need to do something when a controller is connected or disconnected, you should override the methods `connectionWasEstablished` and `connectionWasBroken`. These methods are invoked automatically by `establishConnection` and `breakConnection`.

Accessing and Enabling Actions

Controllers define actions that users can perform (such as quitting the application) and they know how to respond to those actions when they're performed. EOController defines methods that manage a controllers actions.

A controller has a set of actions. It also keeps track of which of those actions are enabled and which are disabled. For performance reasons, EOController's method implementations cache some of this information. Thus, whenever you do something that changes a controller's actions (such as adding a new subcontroller or enabling or disabling an action), the caches must be reset. Most of the time they're reset automatically, but subclasses might need to explicitly reset them with the method `resetActions`.

CLASS EOController

To specify the actions a subclass understands, override the method `defaultActions`. However, to find out what actions a controller understands, use `actions`. This method simply manages and returns a cache of the methods returned by `defaultActions`. Some implementations of a `defaultActions` method are potentially costly to invoke over and over again, because they dynamically build their collections of actions. The `actions` method is simply an optimization. EOController's implementation of `actions` should be sufficient for subclasses; you should never need to override it.

To find out what actions a controller can perform at a specific point in time, use the method `enabledActions`. This method returns only the controller's actions that aren't explicitly disabled. As with `actions`, `enabledActions` manages and returns a cache of methods, and EOController's implementation should be sufficient for subclasses.

Transience

Some controllers are needed only to dynamically generate the user interface and don't serve any purpose after the user interface has been created and connected. For example, an `EOTextFieldController` creates a widget and a corresponding association and then is no longer needed. Controllers such as `EOTextFieldController` can be **transient**, because after their work is done, they can sometimes be removed from the controller hierarchy and disposed of (with `disposeIfTransient`). This keeps the controller hierarchy simple, which makes user interface management more efficient.

Controllers specify whether or not they can be transient by overriding the method `canBeTransient`. Some controllers can be transient sometimes and not other times, so not all implementations simply return `true` or `false`. For example, an `EOTableController` can be transient if the double click action is unassigned. If the action is assigned, however, the controller must listen for a double click and react when one occurs.

Subclasses that can be transient should invoke the method `disposeIfTransient` as soon as their work is done and they can be disposed of. Sometimes a controller's supercontroller doesn't allow the controller to be disposed of. For example, the `EOTabSwitchComponent` doesn't allow its subcontrollers to be disposed of even if they're transient.

Rule System and XML Description

The following tables identify the `controllerType`, XML tag, and XML attributes used by the rule system and EOXMLUnarchiver to generate a controller hierarchy. For more information, see the section [“Rule System and XML Description”](#) (page 8) in the package introduction.

Default Rule System Controller Type

None

XML Tag

None

XML Attribute	Value	Description
<code>className</code>	string	Name of a class to instantiate instead of the default class.
<code>disabledActionNames</code>	array of strings	Names of actions to explicitly disable.
<code>typeName</code>	string	This is usually a textual representation of the specification used to generate the controller, for example “question = window, task = query”. The type name is used by the controller factory to identify which windows are the same so that it can reuse resources. The <code>typeName</code> is also used by the defaults system to specify per-window defaults.

Constants

EOController defines the following `int` constants to identify types of enumerations returned by the method `controllerEnumeration`:

Constant	Description
<code>SubcontrollersEnumeration</code>	An enumeration object that enumerates over a controller's subcontrollers, not including the controller itself.
<code>SupercontrollersEnumeration</code>	An enumeration object that enumerates over a controller's supercontrollers, not including the controller itself.
<code>ControllerAndSubcontrollersEnumeration</code>	An enumeration object that enumerates over a controller and its subcontrollers.

Interfaces Implemented

NSDisposable

dispose

NSKeyValueCoding (Inherited from EOKeyValueCoding)

takeValueForKey

valueForKey

EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions)

handleQueryWithUnboundKey

handleTakeValueForUnboundKey

unableToSetNullForKey

EOKeyValueCodingAdditions

takeValueForKeyPath

valueForKeyPath

EOAction.Enabling

canPerformActionNamed

Method Types

Constructors

EOController

CLASS EOController

Managing the controller hierarchy

- addSubcontroller
- subcontrollerWasAdded
- removeFromSupercontroller
- removeSubcontroller
- subcontrollerWasRemoved
- setSupercontroller
- removeTransientSubcontroller
- canBeTransient
- subcontrollers
- supercontroller
- isAncestorOfController
- isSupercontrollerOfController

Traversing the controller hierarchy

- controllerEnumeration
- controllersInEnumeration
- controllerWithKeyValuePair
- controllerWithKeyValuePairs
- controllersWithKeyValuePair
- controllersWithKeyValuePairs
- hierarchicalControllerForKey
- hierarchicalValueForKey
- invokeMethod

Connecting controllers

- establishConnectionToSupercontrollers
- establishConnection
- connectionWasEstablished

CLASS EOController

breakConnectionToSubcontrollers

breakConnection

connectionWasBroken

setConnected

isConnected

Accessing and enabling actions

actions

defaultActions

enabledActions

actionWithName

actionNames

disableActionNamed

enableActionNamed

isActionNamedEnabled

resetActions

Reusing controllers

prepareForNewTask

Accessing the type name

typeName

setTypeName

Accessing keys

canAccessFieldsDirectly

Disposing

disposeIfTransient

disposableRegistry

Methods inherited from Object

toString

Constructors

EOController

```
public EOController()
```

Description forthcoming.

```
public EOController(EOXMLUnarchiver unarchiver)
```

Creates and returns a new controller. The no argument constructor is used when you create a controller programmatically, whereas the version taking an unarchiver is used in a Direct to Java Client applications to create controllers from an XML description.

Controller subclasses should implement both constructors. Most commonly, controllers are created with the assistance of an unarchiver. For more information on this unarchiving, see the book *Getting Started with Direct to Java Client*.

Static Methods

canAccessFieldsDirectly

```
public static boolean canAccessFieldsDirectly()
```

Returns `true` if the receiver accesses its instance variables directly or `false` otherwise. By default, controllers don't access instance variables directly and return `false`.

See Also: `accessInstanceVariablesDirectly` (**EOCustomObject**)

Instance Methods

actionNames

```
public NSArray actionNames()
```

Returns an array of strings naming the actions the controller defines and responds to.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

actionWithName

```
public EOAction actionWithName(String actionName)
```

If the receiver has an action named `actionName`, this method returns that action; otherwise, the method returns `null`.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

actions

```
public NSArray actions()
```

Returns an array containing the receiver’s actions. EOController’s implementation caches the result of `defaultActions` and returns that. The cache is cleared with the method `resetActions`.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

addSubcontroller

```
public void addSubcontroller(EOController subcontroller)
```

Adds `controller` as a subcontroller of the receiver and sets the receiver as `controller`’s supercontroller (first removing `controller` from it’s supercontroller if it already has one). Invoke this method to programmatically add a subcontroller to the hierarchy.

CLASS EOController

EOController's implementation sets `subcontroller`'s supercontroller and notifies the receiver that a subcontroller was added. It does nothing if `controller` is a supercontroller of the receiver. The default implementation of this method should be sufficient for most subclasses; you shouldn't have to override it. If you need to do something special when a subcontroller is added, override `subcontrollerWasAdded`.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

breakConnection

```
public void breakConnection()
```

Breaks the receiver's connection to its supercontroller. Invokes `connectionWasBroken` to give the receiver a chance to clean up, and informs all its ancestors that a subcontroller's connections have changed so the ancestors can respond appropriately. Use this method to programmatically disconnect a single controller (and not its subcontrollers).

EOController's implementation is sufficient for most subclasses, so you don't ordinarily override this method.

See Also: [“Connecting Controllers”](#) (page 121)

breakConnectionToSubcontrollers

```
public void breakConnectionToSubcontrollers()
```

Breaks the connections the receiver's subcontrollers have to their subcontrollers, and then breaks the receiver's connections to its subcontrollers. This method is invoked recursively down the subcontroller chain until the receiver and all its subcontrollers are disconnected. Use this method to programmatically disconnect a branch of the controller hierarchy from a particular controller down.

EOController's implementation is sufficient for most subclasses, so you don't ordinarily override this method.

See Also: [“Connecting Controllers”](#) (page 121)

CLASS EOController

canBeTransient

```
public boolean canBeTransient()
```

Returns `true` if the controller can be transient, `false` otherwise. EOController's implementation returns `false`.

See Also: [“Transience”](#) (page 122)

canPerformActionNamed

```
public boolean canPerformActionNamed(String actionName)
```

Conformance to EOAction.Enabling. See the method description of `canPerformActionNamed` in the interface specification for EOAction.Enabling.

See Also: `isActionNamedEnabled`, [“Accessing and Enabling Actions”](#) (page 121)

connectionWasBroken

```
protected void connectionWasBroken()
```

Invoked from `breakConnection` to notify the receiver that its connection to its supercontroller has been broken, giving the receiver the opportunity to clean up after its become idle.

See Also: [“Connecting Controllers”](#) (page 121)

connectionWasEstablished

```
protected void connectionWasEstablished()
```

Invoked from `establishConnection` to notify the receiver that its connection to the controller hierarchy has been established, giving the receiver the opportunity to prepare itself (for example, setting delegates).

See Also: [“Connecting Controllers”](#) (page 121)

CLASS EOController

controllerEnumeration

```
public EOController.Enumeration controllerEnumeration(  
    int enumerationType,  
    Class controllerInterface)
```

Returns an enumeration object of the specified type and interface. For example, invoking this method with `SubcontrollersEnumeration` as the `enumerationType` and with `MyControllerInterface` as the `controllerInterface` returns an enumeration object that returns the receiver's subcontrollers that implement the interface `MyControllerInterface`.

The `enumerationType` argument can be one of:

- n `SubcontrollersEnumeration`
- n `SupercontrollersEnumeration`
- n `ControllerAndSubcontrollersEnumeration`

The `controllerInterface` argument can be the name of an interface or `null` to specify no interface, which returns all the controllers specified by `enumerationType`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `EOController.Enumeration` interface specification

controllersInEnumeration

```
public NSArray controllersInEnumeration(  
    int enumerationType,  
    Class controllerInterface)
```

Returns the controllers in an enumeration specified by `enumerationType` and `controllerInterface`.

See Also: `controllerEnumeration`

CLASS EOController

controllersWithKeyValuePair

```
public NSArray controllersWithKeyValuePair(  
    int enumerationType,  
    Class controllerInterface,  
    String key,  
    Object value)
```

Traverses the controller hierarchy, and returns the controllers in the hierarchy whose values for `key` match `value`. This method uses a controller enumeration specified by `enumerationType` and `controllerInterface` to find the controllers. The method tests the controllers returned by the enumeration for matches and returns them. Matches are determined with the method `valueForKeyPath`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

controllersWithKeyValuePairs

```
public NSArray controllersWithKeyValuePairs(  
    int enumerationType,  
    Class controllerInterface,  
    NSDictionary keyValuePairs)
```

Traverses the controller hierarchy, and returns the controllers in the hierarchy whose key-value pairs match those specified in `keyValuePairs`. This method uses a controller enumeration specified by `enumerationType` and `controllerInterface` to find the controllers. The method tests the controllers returned by the enumeration for matches and returns them. Matches are determined with the method `valueForKeyPath`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

CLASS EOController

controllerWithKeyValuePair

```
public EOController controllerWithKeyValuePair(  
    int enumerationType,  
    Class controllerInterface,  
    String key,  
    Object value)
```

Traverses the controller hierarchy, and returns the first controller in the hierarchy whose value for `key` matches `value`. This method uses a controller enumeration specified by `enumerationType` and `controllerInterface` to find the controller. The method tests the controllers returned by the enumeration for a match and returns the first that it matches. Matches are determined with the method `valueForKeyPath`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

controllerWithKeyValuePairs

```
public EOController controllerWithKeyValuePairs(  
    int enumerationType,  
    Class controllerInterface,  
    NSDictionary keyValuePairs)
```

Traverses the controller hierarchy, and returns the first controller in the hierarchy whose key-value pairs match those specified in `keyValuePairs`. This method uses a controller enumeration specified by `enumerationType` and `controllerInterface` to find the controller. The method tests the controllers returned by the enumeration for a match and returns the first that it matches. Matches are determined with the method `valueForKeyPath`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

defaultActions

```
protected NSArray defaultActions()
```

Returns an array of the receiver’s default actions (EOAction objects). A subclass of EOController should override this method to return the action it defines merged with the actions of its superclass. Never invoke this method directly. Instead, invoke `actions`, which caches the results of `defaultActions` and is therefore more efficient.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

CLASS EOController

disableActionNamed

```
public void disableActionNamed(String actionName)
```

Disables the action specified by the name `actionName` and resets the receiver's actions.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

disposableRegistry

```
public NSDisposableRegistry disposableRegistry()
```

Returns the receiver's disposable registry. This registry contains objects that will be disposed of together with the receiver. Subclasses can use the registry to register objects that should be disposed when their controller is disposed.

dispose

```
public void dispose()
```

Conformance to `NSDisposable`. See the method description of `dispose` in the interface specification for `NSDisposable`.

disposeIfTransient

```
protected boolean disposeIfTransient()
```

Disposes the receiver if it's transient, first removing it from its supercontroller with `removeTransientSubcontroller`. Returns `true` if the receiver is transient and has been disposed, `false` otherwise. If the receiver's supercontroller is `non-null`, this method also attempts to dispose of the supercontroller if it's transient.

See Also: [“Transience”](#) (page 122), `removeTransientSubcontroller`

CLASS EOController

enableActionNamed

```
public void enableActionNamed(String actionName)
```

Enables the action named `actionName` and resets the receiver's actions.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

enabledActions

```
public NSArray enabledActions()
```

Returns an array of the receiver's enabled actions—those of the receiver's `EOAction` objects that aren't explicitly disabled. This method caches the enabled actions to enhance performance. The cache is cleared with the method `resetActions`.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

establishConnection

```
public void establishConnection()
```

Connects the receiver to the controller hierarchy. Invokes `connectionWasEstablished` to give the receiver a chance to ready the user interface. After connecting the receiver, this method disposes of it if it's transient and is therefore no longer needed. Use this method to programmatically connect a single controller (and not its ancestors).

`EOController`'s implementation is sufficient for most subclasses, so you don't ordinarily override this method.

See Also: [“Connecting Controllers”](#) (page 121)

establishConnectionToSupercontrollers

```
public void establishConnectionToSupercontrollers()
```

Connects the receiver's supercontroller to the controller hierarchy, and then establishes the receiver's connection to the controller hierarchy. This method is invoked recursively up the supercontroller chain until the receiver and all its ancestors are connected. Use this method to programmatically prepare a branch of the controller hierarchy from a controller up to the root controller.

CLASS EOController

EOController's implementation is sufficient for most subclasses, so you don't ordinarily override this method.

See Also: [“Connecting Controllers”](#) (page 121)

handleQueryWithUnboundKey

```
public Object handleQueryWithUnboundKey(String key)
```

Conformance to EOKeyValueCoding. See the method description of `handleQueryWithUnboundKey` in the interface specification for `EOKeyValueCoding`.

handleTakeValueForUnboundKey

```
public void handleTakeValueForUnboundKey(  
    Object value,  
    String key)
```

Conformance to EOKeyValueCoding. See the method description of `handleTakeValueForUnboundKey` in the interface specification for `EOKeyValueCoding`.

hierarchicalControllerForKey

```
public EOController hierarchicalControllerForKey(  
    Class controllerInterface,  
    String key)
```

Starting at the receiver, searches up the controller hierarchy for the first controller that implements `controllerInterface` and has a non-null value for `key`. Returns that controller or `null` if none of the controllers have a non-null value for `key`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

CLASS EOController

hierarchicalValueForKey

```
public Object hierarchicalValueForKey(  
    Class controllerInterface,  
    String key)
```

Starting at the receiver, searches up the controller hierarchy for the first controller that implements `controllerInterface` and has a non-null value for `key`. Returns the value or null if none of the controllers have a non-null value for `key`.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

invokeMethod

```
public void invokeMethod(  
    int enumerationType,  
    Class controllerInterface,  
    String methodName,  
    Class[] parameterTypes[],  
    Object[] parameters[])
```

Traverses the controller hierarchy, invoking the method specified by `methodName` and `parameterTypes` on the appropriate controllers. This method uses a controller enumeration specified by `enumerationType` and `controllerInterface` to find the controllers on which to invoke the specified method. For each controller in the enumeration, this method invokes the `methodName` method with the values in `parameters` as arguments to the method.

See Also: [“Traversing the Controller Hierarchy”](#) (page 120), `controllerEnumeration`

isActionNamedEnabled

```
public boolean isActionNamedEnabled(String actionName)
```

Returns true if the action specified by `actionName` isn't specifically disabled, false otherwise.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

CLASS EOController

isAncestorOfController

```
public boolean isAncestorOfController(EOController controller)
```

Returns true if `controller` is a subcontroller of the receiver, of the receiver's subcontrollers, or their subcontrollers, and so on; false otherwise.

isConnected

```
public boolean isConnected()
```

Returns true if the receiver is connected, false otherwise.

See Also: [“Connecting Controllers”](#) (page 121)

isSupercontrollerOfController

```
public boolean isSupercontrollerOfController(EOController controller)
```

Returns true if `controller` is an immediate subcontroller of the receiver, false otherwise.

prepareForNewTask

```
public void prepareForNewTask(boolean prepareSubcontrollersForNewTask)
```

Prepares the receiver for performing a new task by resetting any data. If `prepareSubcontrollersForNewTask` is true, this method also sends `prepareForNewTask` to each of the receiver's subcontrollers. This method is invoked to prepare a branch of the controller hierarchy to be reused. Subclasses should override this method to get rid of data and perform any additional clean up.

removeFromSupercontroller

```
public void removeFromSupercontroller()
```

Removes the receiver from its supercontroller's set of subcontrollers. Invoke this method when you need to programmatically remove a controller from the controller hierarchy.

CLASS EOController

EOController's implementation simply invokes `removeSubcontroller` on the receiver's supercontroller. This method is a convenience so you don't have to look up a controller's supercontroller. The default implementation should be sufficient for subclasses; you shouldn't have to override it.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

removeSubcontroller

```
protected void removeSubcontroller(EOController subcontroller)
```

Removes `subcontroller` from the controller hierarchy. EOController's implementation disconnects `subcontroller` from the controller hierarchy, and invokes `subcontrollerWasRemoved` on the receiver to give the receiver a chance to respond appropriately. Never invoke this method directly; use `removeFromSupercontroller` instead. The default implementation should be sufficient for subclasses; you shouldn't have to override it. If you need to do something when a subcontroller is removed, implement `subcontrollerWasRemoved`.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

removeTransientSubcontroller

```
protected boolean removeTransientSubcontroller(EOController subcontroller)
```

Removes `subcontroller` from the controller hierarchy if `subcontroller` can be transient and if the receiver allows it. Returns `true` if the subcontroller could be removed, `false` otherwise. This method is invoked from `disposeIfTransient`, which is invoked in various situations to remove controllers as soon as they can become transient.

See Also: [“Transience”](#) (page 122)

CLASS EOController

resetActions

```
public void resetActions()
```

Destroys the receiver's cache of actions and enabled actions, and destroys the action caches of the receiver's supercontrollers. This method is generally invoked automatically when the receiver's set of actions changes or when an action's enabled state is changed, but you can invoke it yourself to clear the caches as needed. EOController's implementation of this method is sufficient for most subclasses. You shouldn't have to override it.

See Also: [“Accessing and Enabling Actions”](#) (page 121)

setConnected

```
protected void setConnected(boolean flag)
```

Sets the receiver's connected status according to `flag`. EOController's implementation is sufficient for most subclasses; you don't normally override this method. Nor should you ever need to invoke it; `establishConnection` and `breakConnection` set the controller's connection status automatically.

See Also: [“Connecting Controllers”](#) (page 121)

setSupercontroller

```
protected boolean setSupercontroller(EOController controller)
```

Sets the receiver's supercontroller to `controller` and resets the receiver's actions. Returns `true` on success or `false` otherwise. It fails if `controller` is unacceptable as the receiver's supercontroller. Also, `controller` can be `null` to unset the receiver's supercontroller.

EOController's implementation is sufficient for most subclasses; you don't normally override this method. Nor should you ever need to invoke it; `addSubcontroller` sets the supercontroller automatically.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

CLASS EOController

setTypeNames

```
public void setTypeNames(String typeName)
```

Sets the receiver's type name to `typeName`.

See Also: [“Rule System and XML Description”](#) (page 123)

subcontrollers

```
public NSArray subcontrollers()
```

Returns the receiver's immediate subcontrollers. Use `controllerEnumeration` of `controllersInEnumeration` to return all the controllers in the hierarchy under the receiver.

subcontrollerWasAdded

```
protected void subcontrollerWasAdded(EOController subcontroller)
```

Invoked from `addSubcontroller` to notify the receiver that its subcontroller `subcontroller` has been added to the controller hierarchy, giving the receiver the opportunity to prepare the subcontroller for use.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

subcontrollerWasRemoved

```
protected void subcontrollerWasRemoved(EOController subcontroller)
```

Invoked from `removeSubcontroller` to notify the receiver that its subcontroller `subcontroller` has been removed from the controller hierarchy, giving the receiver the opportunity to perform any necessary clean up.

See Also: [“Building the Controller Hierarchy”](#) (page 120)

supercontroller

```
public EOController supercontroller()
```

Returns the receiver's supercontroller, or `null` if the receiver has no supercontroller.

CLASS EOController

```
public EOController supercontroller(Class controllerInterface)
```

Searching from the receiver's immediate supercontroller, returns the first supercontroller that implements the interface `controllerInterface`. Returns `null` if the receiver has no supercontroller or if none of the supercontrollers implement `controllerInterface`. Returns the receiver's immediate supercontroller if `controllerInterface` is `null`.

takeValueForKey

```
public void takeValueForKey(  
    Object value,  
    String key)
```

Conformance to `NSKeyValueCoding`. See the method description of `valueForKey` in the interface specification for `NSKeyValueCoding`.

takeValueForKeyPath

```
public void takeValueForKeyPath(  
    Object value,  
    String keyPath)
```

Conformance to `EOKeyValueCodingAdditions` (`com.webobjects.eocontrol`). See the method description of `takeValueForKeyPath` in the interface specification for `EOKeyValueCodingAdditions`.

toString

```
public String toString()
```

Returns the receiver as a string that states the receiver's class name and type name, whether the receiver is connected, and the number of subcontrollers.

CLASS EOController

typeName

```
public String typeName()
```

Returns the receiver's type name—a string that uniquely identifies the receiver as a node in the controller hierarchy. EOController's implementation returns `null`. The type name is used to identify controllers that have the same task. It is used to configure a controller with user defaults and also to reuse controllers when possible.

See Also: [“Rule System and XML Description”](#) (page 123)

unableToSetNullForKey

```
public void unableToSetNullForKey(String key)
```

Conformance to EOKeyValueCoding. See the method description of `unableToSetNullForKey` in the interface specification for EOKeyValueCoding.

valueForKey

```
public Object valueForKey(String key)
```

Conformance to NSKeyValueCoding. See the method description of `valueForKey` in the interface specification for NSKeyValueCoding.

valueForKeyPath

```
public Object valueForKeyPath(String keyPath)
```

Conformance to EOKeyValueCodingAdditions (com.webobjects.eocontrol). See the method description of `valueForKeyPath` in the interface specification for EOKeyValueCodingAdditions.

EODefaultResourceBundle

Inherits from: java.util.ResourceBundle
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Constructors

EODefaultResourceBundle

```
public EODefaultResourceBundle()
```

Description forthcoming.

Instance Methods

getKeys

public java.util.Enumeration getKeys()

Description forthcoming.

handleGetObject

protected Object handleGetObject(String aString) throws java.util.MissingResourceException

Description forthcoming.

EODefaults

Inherits from: Object
Implements: NSDisposable
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

- clearAllValues
- dispose
- loadPersistentValues
- savePersistentValues
- setPersistentValueForKey

CLASS EODefaults

setTransientValueForKey

valueForKey

Constructors

EODefaults

public EODefaults()

Description forthcoming.

Instance Methods

clearAllValues

public void clearAllValues()

Description forthcoming.

dispose

public void dispose()

Description forthcoming.

loadPersistentValues

public void loadPersistentValues()

Description forthcoming.

CLASS EODefaults

savePersistentValues

```
public void savePersistentValues()
```

Description forthcoming.

setPersistentValueForKey

```
public void setPersistentValueForKey(  
    Object anObject,  
    String aString)
```

Description forthcoming.

setTransientValueForKey

```
public void setTransientValueForKey(  
    Object anObject,  
    String aString)
```

Description forthcoming.

valueForKey

```
public Object valueForKey(String aString)
```

Description forthcoming.

CLASS EODefaults

EODialogController

Inherits from: EOSimpleWindowController :
EOWindowController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
DIALOGCONTROLLER	windowController

Method Types

All methods

EODialogController

CLASS EODialogController

```
runControllerInNewDialog  
generateBorderSize  
newWindow  
setWindowResizable  
setWindowTitle
```

Constructors

EODialogController

```
public EODialogController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EODialogController()
```

Description forthcoming.

Static Methods

runControllerInNewDialog

```
public static void runControllerInNewDialog(  
    EOComponentController anEOComponentController,  
    String aString)
```

Description forthcoming.

Instance Methods

generateBorderSize

protected java.awt.Dimension generateBorderSize()

Description forthcoming.

newWindow

protected java.awt.Window newWindow(javax.swing.JComponent aJComponent)

Description forthcoming.

setWindowResizable

```
protected void setWindowResizable(  
    java.awt.Window aWindow,  
    boolean aBoolean)
```

Description forthcoming.

setWindowTitle

```
protected void setWindowTitle(  
    java.awt.Window aWindow,  
    String aString)
```

Description forthcoming.

CLASS EODialogController

EODialogs

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Constants

Constant	Description
CancelOperation	Description forthcoming.
DefaultOperation	Description forthcoming.
OptionalOperation	Description forthcoming.

Method Types

All methods

```
runChooseOperationDialog  
runConfirmOperationDialog  
runConfirmOperationDialog  
runErrorDialog  
runInformationDialog
```

Constructors

EODialogs

```
public EODialogs()
```

Description forthcoming.

Static Methods

runChooseOperationDialog

```
public static int runChooseOperationDialog(  
    String aString,  
    String aString,  
    String aString,  
    String aString)
```

Description forthcoming.

CLASS EODialogs

runConfirmOperationDialog

```
public static boolean runConfirmOperationDialog(  
    String aString,  
    String aString,  
    String aString,  
    String aString)
```

Description forthcoming.

runConfirmOperationDialog

```
public static boolean runConfirmOperationDialog(  
    String aString,  
    String aString,  
    String aString)
```

Description forthcoming.

runErrorDialog

```
public static void runErrorDialog(  
    String aString,  
    String aString)
```

Description forthcoming.

runInformationDialog

```
public static void runInformationDialog(  
    String aString,  
    String aString)
```

Description forthcoming.

EODisplayUtilities

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Constants

Constant	Description
ComponentAlignmentContainerIndicatorKey	Description forthcoming.
ComponentAlignmentMinimumWidthKey	Description forthcoming.
ComponentAlignmentTitleIndicatorKey	Description forthcoming.

Method Types

All methods

activateWindow
activateWindowIfVisible
componentPrefersHorizontalResizing
componentPrefersVerticalResizing
displayLabelForString
fillTargetSizeWithUnionSize
fillTargetSizeWithUnionSize
integrateTransientSubcontrollerComponentForController
localizedDisplayLabelForString
locateWindow
locateWindow
minimumComponentSizeWithIntegratedComponents
minimumComponentSizeWithIntegratedComponents
minimumSubcontrollerAreaSizeWithIntegratedComponents
relocateWindow
removeComponentFromParentContainer
tryToRemoveComponent
unionSize
unionSize
updateComponentInContainer
updateComponentInController

Static Methods

activateWindow

```
public static void activateWindow(java.awt.Window aWindow)
```

Description forthcoming.

activateWindowIfVisible

```
public static boolean activateWindowIfVisible(java.awt.Window aWindow)
```

Description forthcoming.

componentPrefersHorizontalResizing

```
public static boolean componentPrefersHorizontalResizing(javax.swing.JComponent aJComponent)
```

Description forthcoming.

componentPrefersVerticalResizing

```
public static boolean componentPrefersVerticalResizing(javax.swing.JComponent aJComponent)
```

Description forthcoming.

displayLabelForString

```
public static String displayLabelForString(String aString)
```

Description forthcoming.

CLASS EODisplayUtilities

fillTargetSizeWithUnionSize

```
public static void fillTargetSizeWithUnionSize(  
    java.awt.Dimension aDimension,  
    java.awt.Dimension aDimension,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

fillTargetSizeWithUnionSize

```
public static boolean fillTargetSizeWithUnionSize(  
    java.awt.Dimension aDimension,  
    int anInt,  
    int anInt)
```

Description forthcoming.

integrateTransientSubcontrollerComponentForController

```
public static void integrateTransientSubcontrollerComponentForController(  
    EOComponentController anEOComponentController,  
    EOComponentController anEOComponentController,  
    java.awt.Dimension aDimension,  
    boolean aBoolean)
```

Description forthcoming.

localizedDisplayLabelForString

```
public static String localizedDisplayLabelForString(String aString)
```

Description forthcoming.

locateWindow

```
public static void locateWindow(  
    java.awt.Window aWindow,  
    java.awt.Dimension aDimension,  
    java.awt.Point aPoint)
```

Description forthcoming.

CLASS EODisplayUtilities

locateWindow

```
public static void locateWindow(  
    java.awt.Window aWindow,  
    java.awt.Dimension aDimension,  
    int anInt,  
    int anInt)
```

Description forthcoming.

minimumComponentSizeWithIntegratedComponents

```
public static java.awt.Dimension minimumComponentSizeWithIntegratedComponents(  
    EOComponentController anEOComponentController,  
    java.awt.Dimension aDimension,  
    java.awt.Dimension aDimension,  
    NSArray aNSArray,  
    boolean aBoolean)
```

Description forthcoming.

minimumComponentSizeWithIntegratedComponents

```
public static java.awt.Dimension minimumComponentSizeWithIntegratedComponents(  
    EOComponentController anEOComponentController,  
    java.awt.Dimension aDimension,  
    java.awt.Dimension aDimension,  
    NSArray aNSArray)
```

Description forthcoming.

minimumSubcontrollerAreaSizeWithIntegratedComponents

```
public static java.awt.Dimension minimumSubcontrollerAreaSizeWithIntegratedComponents(  
    java.awt.Dimension aDimension,  
    NSArray aNSArray,  
    boolean aBoolean)
```

Description forthcoming.

CLASS EODisplayUtilities

relocateWindow

```
public static void relocateWindow(  
    java.awt.Window aWindow,  
    java.awt.Dimension aDimension,  
    int anInt)
```

Description forthcoming.

removeComponentFromParentContainer

```
public static void removeComponentFromParentContainer(java.awt.Component aComponent)
```

Description forthcoming.

tryToRemoveComponent

```
public static void tryToRemoveComponent(java.awt.Component aComponent)
```

Description forthcoming.

unionSize

```
public static java.awt.Dimension unionSize(  
    java.awt.Dimension aDimension,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

unionSize

```
public static java.awt.Dimension unionSize(  
    int anInt,  
    int anInt,  
    int anInt,  
    int anInt)
```

Description forthcoming.

CLASS EODisplayUtilities

updateComponentInContainer

```
public static void updateComponentInContainer(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    java.awt.Dimension aDimension,  
    boolean aBoolean,  
    boolean aBoolean,  
    javax.swing.JComponent aJComponent,  
    boolean aBoolean)
```

Description forthcoming.

updateComponentInController

```
public static void updateComponentInController(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    java.awt.Dimension aDimension,  
    boolean aBoolean,  
    boolean aBoolean,  
    boolean aBoolean,  
    boolean aBoolean)
```

Description forthcoming.

CLASS EODisplayUtilities

EODocumentController

Inherits from:	EOEntityController : EOComponentController : EOController
Implements:	EODocument EOEditable EOAssociationConnector (Inherited from EOEntityController) EOComponentController.EndEditing (Inherited from EOEntityController) EOObserving (Inherited from EOEntityController) EOObjectDisplay (Inherited from EOEntityController) NSInlineObservable (Inherited from EOController) NSDisposable (Inherited from EOController) EOKeyValueCodingAdditions (Inherited from EOController) EOAction.Enabling (Inherited from EOController) EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions) EOKeyValueCodingAdditions (Inherited from EOKeyValueCoding) NSKeyValueCoding (Inherited from EOKeyValueCoding)
Package:	com.webobjects.eoapplication

Class Description

The EODocumentController class provides behavior for displaying and editing enterprise objects in a user interface. EODocumentController's API is mostly specified by the interfaces EODocument and EOEditable. Additionally, much of the way that EODocumentController works is set up by its superclass, EOEntityController. Since EOEntityControllers use EOEditingContexts and EODisplayGroups to manage and display a set of enterprise objects;

CLASS EODocumentController

EODocumentControllers use them as well. However, in addition to displaying enterprise objects, document controllers can also edit their objects. You can insert, update, and delete enterprise objects; undo and redo unsaved changes; and save and revert.

EODocumentController provides several methods that interact with a user. For example, the methods `revert` and `saveIfUserConfirms` open dialogs to confirm that a user wants to revert or save before performing the action. Also, many of the methods open dialogs when an error occurs, telling the user what happened.

Root Document Controller Responsibilities

EODocumentController defines the concept of a root document controller. A document controller is the root if none of its ancestors are EODocuments. A root document controller usually provides the editing context for all its descendent document controllers—they typically don't have their own. Consequently, the root document controller has responsibilities that non-root document controllers don't have. For example, only the root document controller provides save and revert behavior.

Rule System and XML Description

The following tables identify the `controllerType`, XML tag, and XML attributes used by the rule system and EOXMLUnarchiver to generate a controller hierarchy. For more information, see the section [“Rule System and XML Description”](#) (page 8) in the package introduction.

Default Rule System Controller Type

`entityController`

XML Tag

`DOCUMENTCONTROLLER`

XML Attribute	Value	Description
<code>editability</code>	<code>string</code>	One of “Never“, “Always“, or “IfSupercontroller“. See the <code>EOEditable</code> interface specification for more information on these settings.

Interfaces Implemented

EODocument

isDocumentForGlobalID
isEdited
save
saveIfUserConfirms
setEdited

EOEditable

editability
isEditable
setEditability
supercontrollerEditabilityDidChange
takeResponsibilityForEditabilityOfAssociation

EOAssociationConnector (Inherited from EOEntityController)

EOComponentController.EndEditing (Inherited from EOEntityController)

EOObserving (Inherited from EOEntityController)

EOObjectDisplay (Inherited from EOEntityController)

NSInlineObservable (Inherited from EOController)

NSDisposable (Inherited from EOController)

dispose

EOKeyValueCodingAdditions (Inherited from EOController)

EOAction.Enabling (Inherited from EOController)

CLASS EODocumentController

canPerformActionNamed

EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions)

NSKeyValueCoding (Inherited from EOKeyValueCoding)

Method Types

Constructors

EODocumentController

Inserting, updating, and deleting

insertObject

deleteSelectedObjects

wasEdited

Saving

canSave

saveChanges

saveAndMakeInvisible

saveIfUserConfirms

saveIfUserConfirmsAndMakeInvisible

saveIfUserConfirmsAndMakeInvisible

saveFailed

Reverting

canRevert

revert

revertAndMakeInvisible

revertChanges

revertFailed

CLASS `EODocumentController`

Undoing and Redoing

`canUndo`

`undo`

`canRedo`

`redo`

Determining the root document controller

`isRootDocumentController`

Methods inherited from `EOEntityController`

`handleEditingContextNotification`

Methods inherited from `EOController`

`connectionWasEstablished`

`defaultActions`

`prepareForNewTask`

Methods inherited from `Object`

`toString`

Constructors

`EODocumentController`

```
public EODocumentController()
```

```
public EODocumentController(EOXMLUnarchiver unarchiver)
```

Creates a new document controller. For information on how these constructors are used and on what they do, see the method description for the `EOController` constructors in the `EOController` class specification.

Instance Methods

canPerformActionNamed

```
public boolean canPerformActionNamed(String actionName)
```

Conformance to `EOAction.Enabling`. `EODocumentController`'s implementation uses the methods `canRedo`, `canRevert`, `canSave`, and `canUndo` to determine the enabling state of the corresponding actions.

See Also: `canPerformActionNamed` (`EOAction.Enabling`)

canRedo

```
public boolean canRedo()
```

Returns `true` if the receiver can redo, `false` otherwise. A document controller can redo as long as its editing context's undo manager can redo and as long as it (or one of its subcontrollers) is editable.

canRevert

```
public boolean canRevert()
```

Returns `true` if the receiver can revert, `false` otherwise. A document controller can revert only if it's been edited and only if it's the root document controller.

canSave

```
public boolean canSave()
```

Returns `true` if the receiver can save, `false` otherwise. A document controller can save only if it's been edited and only if it's the root document controller.

CLASS `EODocumentController`

canUndo

```
public boolean canUndo()
```

Returns `true` if the receiver can undo, `false` otherwise. A document controller can undo as long as its editing context's undo manager can undo and as long as it (or one of its subcontrollers) is editable.

connectionWasEstablished

```
protected void connectionWasEstablished()
```

See the method description for `connectionWasEstablished` in the `EOController` class specification. `EODocumentController`'s implementation additionally updates its editability.

defaultActions

```
protected NSArray defaultActions()
```

Adds actions for handling editing to the default actions defined by the superclass, `EOEntityController`. More specifically, it adds save and revert actions. However, note that `defaultActions` only adds save and revert if the receiver is the root document controller, if it's editable, and if it's not modal.

deleteSelectedObjects

```
public void deleteSelectedObjects()
```

Deletes the objects selected in the receiver's display group and then sets the receiver's edited state to `true`.

dispose

```
public void dispose()
```

Conformance to `NSDisposable`. See the method description of `dispose` in the interface specification for `NSDisposable`.

CLASS EODocumentController

editability

```
public int editability()
```

Conformance to EOEditable. See the method description of `editability` in the interface specification for EOEditable.

handleEditingContextNotification

```
public void handleEditingContextNotification(NSNotification notification)
```

See the method description for `handleEditingContextNotification` in the EOEntityController class specification. EODocumentController's implementation additionally updates its edited state if the receiver is a root document controller.

insertObject

```
public void insertObject()
```

Creates a new enterprise object, inserts it into the receiver's display group, and sets the receiver's edited status to `true`.

isDocumentForGlobalID

```
public boolean isDocumentForGlobalID(  
    com.weboobjects.eocontrol.EOGlobalID globalID,  
    String entityName)
```

Conformance to EODocument. See the method description of `isDocumentForGlobalID` in the interface specification for EODocument.

isEditable

```
public boolean isEditable()
```

Conformance to EOEditable. See the method description of `isEditable` in the interface specification for EOEditable.

CLASS EODocumentController

isEdited

```
public boolean isEdited()
```

Conformance to EODocument. See the method description of `isEdited` in the interface specification for EODocument.

isRootDocumentController

```
public boolean isRootDocumentController()
```

Returns `true` if none of the supercontrollers are EODocuments, `false` otherwise.

prepareForNewTask

```
public void prepareForNewTask(boolean flag)
```

See the method description for `prepareForNewTask` in the EOController class specification. EODocumentController's implementation additionally sets its edited state to `false`.

redo

```
public void redo()
```

Tells the receiver's editing context to redo.

revert

```
public boolean revert()
```

Reverts the receiver's unsaved changes upon user confirmation. If the receiver has been edited, opens a dialog to verify that the user wants to revert. Upon confirmation, invokes `revertChanges` requesting an error dialog upon failure. Returns `true` on success, `false` upon failure or if the user cancels the revert.

CLASS EODocumentController

revertAndMakeInvisible

```
public boolean revertAndMakeInvisible()
```

Reverts the receiver's unsaved changes and makes the receiver invisible. Reverts by invoking `revertChanges`, requesting an error dialog upon failure Returns `true` if changes are successfully reverted, `false` if the receiver can't be reverted or if the revert fails.

revertChanges

```
public boolean revertChanges(boolean showErrorDialog)
```

Tells the receiver's editing context to revert, refetches if necessary, and sets the receiver's editing state to `false`. If the revert fails, catches the exception and, if `showErrorDialog` is `true`, invokes `revertFailed` to show the reason for failure. Returns `true` if the revert succeeds, `false` otherwise.

revertFailed

```
protected void revertFailed(  
    Exception exception,  
    boolean showErrorDialog)
```

If `showErrorDialog` is `true`, brings the receiver's user interface to the front and opens a dialog displaying `exception`'s class name and exception message. Invoked from `revertChanges`.

save

```
public boolean save()
```

Saves the receiver's changes. Saves by invoking `saveChanges`, requesting an error dialog upon failure Returns `true` if changes are successfully saved, `false` if the receiver can't save or if the save fails.

saveAndMakeInvisible

```
public boolean saveAndMakeInvisible()
```

Saves the receiver's changes and makes the receiver invisible. Saves by invoking `saveChanges`, requesting an error dialog upon failure Returns `true` if changes are successfully reverted, `false` if the receiver can't be reverted or if the revert fails.

CLASS EODocumentController

saveChanges

```
public boolean saveChanges(  
    boolean showErrorDialog,  
    String saveOperationTitle)
```

Tells the receiver's editing context to save changes and sets the receiver's editing state to `false`. If the save fails, catches the exception and, if `showErrorDialog` is true, invokes `saveFailed` to show the reason for failure. Returns `true` if the save succeeds, `false` otherwise.

saveFailed

```
protected void saveFailed(  
    Exception showErrorDialog,  
    boolean showErrorDialog,  
    String saveOperationTitle)
```

If `showErrorDialog` is true, brings the receiver's user interface to the front and opens a dialog displaying `exception`'s class name and exception message. Invoked from `saveChanges`.

saveIfUserConfirms

```
public boolean saveIfUserConfirms(  
    String operationTitle,  
    String message)
```

```
public boolean saveIfUserConfirms()
```

Saves the receiver's unsaved changes upon user confirmation. If the receiver has been edited, opens a dialog to verify that the user wants to save. If `operationTitle` and `message` are provided, they are used as the dialog title and message; otherwise, "Save" and "Save Changes?" are used. Upon confirmation, invokes `saveChanges` requesting an error dialog upon failure. Returns `true` on success, `false` upon failure or if the user cancels the save.

CLASS EODocumentController

saveIfUserConfirmsAndMakeInvisible

```
public boolean saveIfUserConfirmsAndMakeInvisible(  
    String operationTitle,  
    String message)  
  
public boolean saveIfUserConfirmsAndMakeInvisible()
```

Saves the receiver's unsaved changes upon user confirmation and makes the receiver invisible. Saves by invoking `saveIfUserConfirms`, requesting an error dialog upon failure. The arguments `operationTitle` and `message` are used as the title and message of the confirmation panel. "Save" and "Save changes?" are substituted for `null`. If the no-argument form of this method is invoked, then the title of the confirmation dialog is "Close" and the dialog has no message. Returns `true` if changes are successfully saved, `false` if the receiver can't be saved or if the save fails.

setEditability

```
public void setEditability(int editability)
```

Conformance to `EOEditable`. See the method description of `setEditability` in the interface specification for `EOEditable`.

setEdited

```
public void setEdited(boolean flag)
```

Conformance to `EODocument`. See the method description of `setEdited` in the interface specification for `EODocument`.

supercontrollerEditabilityDidChange

```
public void supercontrollerEditabilityDidChange()
```

Conformance to `EOEditable`. See the method description of `supercontrollerEditabilityDidChange` in the interface specification for `EOEditable`. `EODocumentController`'s implementation updates the receiver's editability and resets its actions.

CLASS EODocumentController

takeResponsibilityForEditabilityOfAssociation

```
public void takeResponsibilityForEditabilityOfAssociation(  
    com.webobjects.eointerface.EOAssociation association)
```

Conformance to EOEditable. See the method description of `takeResponsibilityForEditabilityOfAssociation` in the interface specification for `EOEditable`.

toString

```
public String toString()
```

Returns the receiver as a string, including the receiver's editability and whether or not it has unsaved edits.

undo

```
public void undo()
```

Tells the receiver's editing context to redo.

wasEdited

```
protected void wasEdited()
```

Invoked from `setEdited` to notify the receiver that edited status has changed, giving the receiver the opportunity to respond.

CLASS EODocumentController

EOEntityController

Inherits from:	EOComponentController : EOController : Object
Implements:	EOObserving EOObjectDisplay EOAssociationConnector EOComponentController.EndEditing
Package:	com.webobjects.eoapplication

Class Description

The EOEntityController class provides behavior for displaying enterprise objects in a user interface that can optionally be loaded from an archive (a nib file). EOEntityController's most basic API is specified by the interface EOObjectDisplay, which identifies an implementation strategy that uses EOEditingContexts and EODisplayGroups to manage an entity controller's enterprise objects. An entity controller has an entity name, which identifies the kind of enterprise objects the controller works with. Additionally it has an editing context that manages the controller's enterprise objects, a display group that displays the enterprise objects and manages a selection, and a controller display group that connects controller methods to the user interface. For more information, see the EOObjectDisplay interface specification.

User Interface Archive

As a subclass of EOComponentController, EOEntityController manages a user interface component. However, whereas component controllers dynamically generate their components, entity controllers have the ability to load their components from an archive. An entity controller

CLASS EOEntityController

has an archive name, which specifies the archive from which to load the controller's component. If, however, a controller doesn't have an archive name, the controller can fall back on dynamically generating its component (an empty EOView).

Managing the Editing Context

As mentioned earlier, EOEntityController uses an editing context to manage its enterprise objects. By default, an entity controller attempts to get its editing context from a supercontroller. An entity controller looks up the controller hierarchy for the first EOObjectDisplay ancestor that has an editing context. If it finds one, the entity controller uses that supercontroller's editing context. If it doesn't find one, it creates one.

You can change the way an entity controller gets its editing context by specifying a **provider method** with `setEditingContextProviderMethodName`. If an entity controller has an editing context provider method, it gets its editing context by invoking that method.

The provider method name is a string, which can be a key path or the name of an arbitrary class's static method. For an example of setting the method name to a key path, consider a subclass of EOEntityController that implements the method `customizedEditingContext` to return an editing context for the controller to use. In this case, the provider method name could be set to "customizedEditingContext".

If the provider method name is the name of a static method, the format of the string is "<class name>:<static method name>". For example, suppose that you've written a subclass of EOApplication that implements a static method, `customizedEditingContextForAllControllers`, to return an editing context for all an application's controllers to share. Then the editing context provider method name for all entity controllers could be set to "CustomApplicationClass:customizedEditingContextForAllControllers".

EOEntityController provides two methods that you can use as provider methods: `newEditingContext` and `nestedEditingContext`. The former simply creates a new editing context and is a convenience for setting the provider method. The latter attempts to create a new editing context that's nested inside an ancestor's editing context. If no ancestors provide an editing context to be a parent, `nestedEditingContext` simply creates a new editing context.

Managing the Display Group

EOEntityController uses a display group to display its enterprise objects. By default, an entity controller attempts to get its display group from a supercontroller. An entity controller looks up the controller hierarchy for the first EOObjectDisplay ancestor. If that supercontroller has the

CLASS EOEntityController

same entity name and a display group, the entity controller uses that supercontroller's display group. If it doesn't find one, it invokes `loadArchive` to see if a display group is provided in the archive. If the controller still doesn't have a display group, it simply creates one.

You can change the way an entity controller gets its display group by specifying a **provider method** with `setDisplayGroupProviderMethodName`. If an entity controller has a display group provider method, it gets its display group by invoking that method. The display group provider method name works the same way the editing context provider method name works. For more information, see [“Managing the Editing Context”](#) (page 182).

EOEntityController provides two methods that you can use as provider methods: `newDisplayGroup` and `newDisplayGroupUsingOptimisticRefresh`. The simply create new display groups and are convenience methods for setting the provider method.

Rule System and XML Description

The following tables identify the `controllerType`, XML tag, and XML attributes used by the rule system and EOXMLUnarchiver to generate a controller hierarchy. For more information, see the section [“Rule System and XML Description”](#) (page 8) in the package introduction.

Default Rule System Controller Type

entityController

XML Tag

ENTITYCONTROLLER

XML Attribute	Value	Description
archive	string	The name of a nib file from which the controller loads its component (instead of dynamically creating it).

CLASS EOEntityController

XML Attribute	Value	Description
displayGroupProviderMethod Name	string	A key path or string of the form “<class name>: <method name>” that names a method the controller uses to create its display group.
editingContextProviderMet hodName	string	A key path or string of the form “<class name>: <method name>” that names a method the controller uses to create its editing context.
entity	string	Name of the controller’s entity.

Constants

Constant	Description
NestedEditingContextProviderMethod Name	Description forthcoming.
NewDisplayGroupProviderMethodName	Description forthcoming.
NewEditingContextProviderMethodNam e	Description forthcoming.

Interfaces Implemented

EOObserving

objectWillChange

EOObjectDisplay

controllerDisplayGroup

displayGroup

editingContext

entityName

EOAssociationConnector

takeResponsibilityForConnectionOfAssociation

EOComponentController.EndEditing

endEditing

NSDisposable (Inherited from EOController)

dispose

EOKeyValueCodingAdditions (Inherited from EOController)

EOAction.Enabling (Inherited from EOController)

EOKeyValueCoding (Inherited from EOKeyValueCodingAdditions)

NSKeyValueCoding (Inherited from EOKeyValueCoding)

Method Types

CLASS EOEntityController

Constructors

EOEntityController

Setting the entity

setEntityName

Loading an archive

prepareComponent

loadArchive

controllerDidLoadArchive

objectForOutletPath

setArchiveName

archiveName

Managing the editing context

newEditingContext

setEditingContext

setEditingContextProviderMethodName

editingContextProviderMethodName

nestedEditingContext

startListeningToEditingContext

stopListeningToEditingContext

handleEditingContextNotification

setResetsEditingContextWhenPreparingForNewTask

resetsEditingContextWhenPreparingForNewTask

Managing the controller display group

setControllerDisplayGroup

hasControllerDisplayGroup

Managing the objects display group

newDataSource

CLASS EOEntityController

newDisplayGroup
newDisplayGroupUsingOptimisticRefresh
setDisplayGroup
startListeningToDisplayGroup
stopListeningToDisplayGroup
setObjectWithGlobalID
setObjectsWithFetchSpecification
displayGroupSortOrderings
setDisplayGroupProviderMethodName
displayGroupProviderMethodName

Accessing selected objects

selectedObject
selectedObjectGlobalID
selectedObjects
selectedObjectsGlobalIDs

Fetching

fetchesOnConnect
setFetchesOnConnect

Determining the root document controller

isRootEntityController

Notifying observers of change

willChange

Methods inherited from EOController

connectionWasBroken
connectionWasEstablished
establishConnection
prepareForNewTask

CLASS EOEntityController

Methods inherited from Object

toString

Constructors

EOEntityController

```
public EOEntityController(EOXMLUnarchiver unarchiver)
```

Description forthcoming.

```
public EOEntityController()
```

Description forthcoming.

Instance Methods

archiveName

```
public String archiveName()
```

Description forthcoming.

connectionWasBroken

```
protected void connectionWasBroken()
```

Description forthcoming.

CLASS EOEntityController

connectionWasEstablished

protected void connectionWasEstablished()

Description forthcoming.

controllerDidLoadArchive

protected void controllerDidLoadArchive(NSDictionary aNSDictionary)

Description forthcoming.

controllerDisplayGroup

public com.webobjects.eointerface.EODisplayGroup controllerDisplayGroup()

Description forthcoming.

displayGroup

public com.webobjects.eointerface.EODisplayGroup displayGroup()

Description forthcoming.

displayGroupProviderMethodName

public String displayGroupProviderMethodName()

Description forthcoming.

displayGroupSortOrderings

protected NSArray displayGroupSortOrderings()

Description forthcoming.

CLASS EOEntityController

dispose

```
public void dispose()
```

Description forthcoming.

editingContext

```
public com.webobjects.eocontrol.EOEditingContext editingContext()
```

Description forthcoming.

editingContextProviderMethodName

```
public String editingContextProviderMethodName()
```

Description forthcoming.

endEditing

```
public boolean endEditing()
```

Description forthcoming.

entityName

```
public String entityName()
```

Description forthcoming.

establishConnection

```
public void establishConnection()
```

Description forthcoming.

CLASS EOEntityController

fetchesOnConnect

public boolean fetchesOnConnect()

Description forthcoming.

handleEditingContextNotification

public void handleEditingContextNotification(NSNotification aNSNotification)

Description forthcoming.

hasControllerDisplayGroup

public boolean hasControllerDisplayGroup()

Description forthcoming.

isRootEntityController

public boolean isRootEntityController()

Description forthcoming.

loadArchive

protected boolean loadArchive()

Description forthcoming.

nestedEditingContext

public com.webobjects.eocontrol.EOEditingContext nestedEditingContext()

Description forthcoming.

CLASS EOEntityController

newDataSource

```
protected com.webobjects.eocontrol.EODataSource newDataSource()
```

Description forthcoming.

newDisplayGroup

```
public com.webobjects.eointerface.EODisplayGroup newDisplayGroup()
```

Description forthcoming.

newDisplayGroupUsingOptimisticRefresh

```
public com.webobjects.eointerface.EODisplayGroup newDisplayGroupUsingOptimisticRefresh()
```

Description forthcoming.

newEditingContext

```
public com.webobjects.eocontrol.EOEditingContext newEditingContext()
```

Description forthcoming.

objectForOutletPath

```
public Object objectForOutletPath(  
    EOArchive anEOArchive,  
    String aString)
```

Description forthcoming.

objectWillChange

```
public void objectWillChange(Object anObject)
```

Description forthcoming.

CLASS EOEntityController

prepareComponent

protected void prepareComponent()

Description forthcoming.

prepareForNewTask

public void prepareForNewTask(boolean aBoolean)

Description forthcoming.

resetsEditingContextWhenPreparingForNewTask

public boolean resetsEditingContextWhenPreparingForNewTask()

Description forthcoming.

selectedObject

public com.webobjects.eocontrol.EOEnterpriseObject selectedObject()

Description forthcoming.

selectedObjectGlobalID

public com.webobjects.eocontrol.EOGlobalID selectedObjectGlobalID()

Description forthcoming.

selectedObjects

public NSArray selectedObjects()

Description forthcoming.

CLASS EOEntityController

selectedObjectsGlobalIDs

```
public NSArray selectedObjectsGlobalIDs()
```

Description forthcoming.

setArchiveName

```
public void setArchiveName(String aString)
```

Description forthcoming.

setControllerDisplayGroup

```
public void setControllerDisplayGroup(com.webobjects.eointerface.EODisplayGroup anEODisplayGroup)
```

Description forthcoming.

setDisplayGroup

```
public void setDisplayGroup(com.webobjects.eointerface.EODisplayGroup anEODisplayGroup)
```

Description forthcoming.

setDisplayGroupProviderMethodName

```
public void setDisplayGroupProviderMethodName(String aString)
```

Description forthcoming.

setEditingContext

```
public void setEditingContext(com.webobjects.eocontrol.EOEditingContext anEOEditingContext)
```

Description forthcoming.

CLASS EOEntityController

setEditingContextProviderMethodName

```
public void setEditingContextProviderMethodName(String aString)
```

Description forthcoming.

setEntityName

```
public void setEntityName(String aString)
```

Description forthcoming.

setFetchesOnConnect

```
public void setFetchesOnConnect(boolean aBoolean)
```

Description forthcoming.

setObjectWithGlobalID

```
public void setObjectWithGlobalID(com.webobjects.eocontrol.EOGlobalID anEOGlobalID)
```

Description forthcoming.

setObjectsWithFetchSpecification

```
public void  
    setObjectsWithFetchSpecification(com.webobjects.eocontrol.EOFetchSpecification anEOFetchSpecification  
    )
```

Description forthcoming.

setResetsEditingContextWhenPreparingForNewTask

```
public void setResetsEditingContextWhenPreparingForNewTask(boolean aBoolean)
```

Description forthcoming.

CLASS EOEntityController

startListeningToDisplayGroup

protected void startListeningToDisplayGroup()

Description forthcoming.

startListeningToEditingContext

protected void startListeningToEditingContext()

Description forthcoming.

stopListeningToDisplayGroup

protected void stopListeningToDisplayGroup()

Description forthcoming.

stopListeningToEditingContext

protected void stopListeningToEditingContext()

Description forthcoming.

takeResponsibilityForConnectionOfAssociation

public void
takeResponsibilityForConnectionOfAssociation(com.webobjects.eointerface.EOAssociation anEOAssociation)

Description forthcoming.

toString

public String toString()

Description forthcoming.

CLASS EOEntityController

willChange

```
public void willChange()
```

Description forthcoming.

CLASS EOEntityController

EOFrameController

Inherits from: EOSimpleWindowController :
EOWindowController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
FRAMECONTROLLER	windowController

Method Types

All methods

EOFrameController

CLASS EOFrameController

runControllerInNewFrame
dispose
generateBorderSize
newWindow
setWindowResizable
setWindowTitle
verifyContentMinimumSize

Constructors

EOFrameController

```
public EOFrameController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOFrameController()
```

Description forthcoming.

Static Methods

runControllerInNewFrame

```
public static void runControllerInNewFrame(  
    EOComponentController anEOComponentController,  
    String aString)
```

Description forthcoming.

Instance Methods

dispose

```
public void dispose()
```

Description forthcoming.

generateBorderSize

```
protected java.awt.Dimension generateBorderSize()
```

Description forthcoming.

newWindow

```
protected java.awt.Window newWindow(javax.swing.JComponent aJComponent)
```

Description forthcoming.

setWindowResizable

```
protected void setWindowResizable(  
    java.awt.Window aWindow,  
    boolean aBoolean)
```

Description forthcoming.

setWindowTitle

```
protected void setWindowTitle(  
    java.awt.Window aWindow,  
    String aString)
```

Description forthcoming.

CLASS EOFrameController

verifyContentSize

```
protected java.awt.Dimension verifyContentSize(  
    java.awt.Window aWindow,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

EOInspectorController

Inherits from: EOWindowController :
 EOComponentController :
 EOController :
 Object

Implements: EOComponentController.ResetUserInterface

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
INSPECTORCONTROLLER	windowController

Method Types

All methods

EOInspectorController

CLASS EOInspectorController

activateWindow
addComponentOfSubcontroller
dispose
generateBorderSize
generateComponent
inspectorIdentifier
integrationComponentDidBecomeInvisible
integrationComponentDidBecomeVisible
resetUserInterface
setInspectorIdentifier
subcontrollerMinimumSizeDidChange

Constructors

EOInspectorController

```
public EOInspectorController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOInspectorController()
```

Description forthcoming.

Instance Methods

activateWindow

```
public void activateWindow()
```

Description forthcoming.

addComponentOfSubcontroller

```
protected void addComponentOfSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

generateBorderSize

```
protected java.awt.Dimension generateBorderSize()
```

Description forthcoming.

generateComponent

```
protected void generateComponent()
```

Description forthcoming.

CLASS EOInspectorController

inspectorIdentifier

```
public String inspectorIdentifier()
```

Description forthcoming.

integrationComponentDidBecomeInvisible

```
protected void integrationComponentDidBecomeInvisible()
```

Description forthcoming.

integrationComponentDidBecomeVisible

```
protected void integrationComponentDidBecomeVisible()
```

Description forthcoming.

resetUserInterface

```
public void resetUserInterface()
```

Description forthcoming.

setInspectorIdentifier

```
public void setInspectorIdentifier(String aString)
```

Description forthcoming.

subcontrollerMinimumSizeDidChange

```
public void subcontrollerMinimumSizeDidChange(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

EOInterfaceController

Inherits from: EODocumentController :
EOEntityController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

EOInterfaceController serves as a convenient base class for logic related to the interface of client-side applications. When the WebObjectsApplication wizard in Project Builder creates a new client-side interface, it adds (to the client-side subproject) an Interface Builder nib file representing this interface and a skeletal EOInterfaceController subclass defined as the nib file's root object or "owner."

In an application constructed in conformance to the Model-View-Controller paradigm, EOInterfaceController plays the role of controller. It has four special outlets (defined in the EOEntityController superclass): its `editingContext`, its `component`, its `displayGroup`, and its `controllerDisplayGroup`, all of which you can configure using Interface Builder. The object identified by `component` is an AWT JComponent that functions as the view, since it is the main entry point into the user interface. Because an enterprise object must always inhabit an editing context, `editingContext` and its contents serve as the "model." The `displayGroup` is an EODisplayGroup

CLASS EOInterfaceController

containing the enterprise objects manipulated by the controller's user interface (which may will involve other display groups). The `controllerDisplayGroup` is a convenience instance containing nothing but the interface controller itself.

XML Tag	Default Rule System Controller Type
INTERFACECONTROLLER	entityController

Method Types

All methods

- EOInterfaceController
- archiveName
- collectChangesFromServer
- generateComponent

Constructors

EOInterfaceController

```
public EOInterfaceController()
```

```
public EOInterfaceController(com.webobjects.eocontrol.EOEditingContext editingContext)
```

Initializes a new instance then attempts to load the nib file matching the class name. The one-argument and two-argument constructors allow you to specify the editing context used as the nib file's substitution editing context during the load.

CLASS EOInterfaceController

```
public EOInterfaceController(  
    com.webobjects.eocontrol.EOEditingContext editingContext,  
    String archiveName)
```

Initializes a new instance then attempts to load the associated nib file identified by `archiveName`. The `editingContext` argument is used as the nib file's substitution editing context during the load.

```
public EOInterfaceController(EOXMLUnarchiver unarchiver)
```

Initializes a new instance with the contents of the `unarchiver` EOXMLUnarchiver.

Instance Methods

archiveName

```
public String archiveName()
```

Returns the name of the nib file that specifies the receiver's user interface. Defaults to the receiver's class name.

collectChangesFromServer

```
public void collectChangesFromServer()
```

Updates the receiver's editing context to reflect any changes to enterprise objects pending on the server.

generateComponent

```
protected void generateComponent()
```

Since an EOInterfaceController requires a nib file, this method is overridden to raise a `NSInternalInconsistencyException`.

CLASS EOInterfaceController

EOMenuSwitchController

Inherits from: EOSwitchController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
MENUSWITCHCONTROLLER	dividingController

Method Types

All methods

EOMenuSwitchController
addBorderComponentForControllerToDisplayComponent

CLASS EOMenuSwitchController

borderSize
dispose
newDisplayComponent
removeBorderComponentForControllerFromDisplayComponent
selectedBorderComponentInDisplayComponent
showBorderComponentAtIndexInDisplayComponent

Constructors

EOMenuSwitchController

```
public EOMenuSwitchController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOMenuSwitchController()
```

Description forthcoming.

Instance Methods

addBorderComponentForControllerToDisplayComponent

```
protected void addBorderComponentForControllerToDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOMenuSwitchController

borderSize

```
public java.awt.Dimension borderSize()
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

newDisplayComponent

```
protected javax.swing.JComponent newDisplayComponent()
```

Description forthcoming.

removeBorderComponentForControllerFromDisplayComponent

```
protected void removeBorderComponentForControllerFromDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

selectedBorderComponentInDisplayComponent

```
protected javax.swing.JComponent  
    selectedBorderComponentInDisplayComponent(javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOMenuSwitchController

showBorderComponentAtIndexInDisplayComponent

```
protected void showBorderComponentAtIndexInDisplayComponent(  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

EOModalDialogController

Inherits from: EODialogController :
EOWindowController :
EOComponentController :
EOController :
Object

Implements: EOComponentController.Modal

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag**Default Rule System Controller Type**

MODALDIALOGCONTROLLER

modalDialogController

Method Types

All methods

EOModalDialogController
runControllerInNewModalDialog
activateWindow
closeWindow
isModal
newWindow

Constructors

EOModalDialogController

public EOModalDialogController(EOXMLUnarchiver anEOXMLUnarchiver)

Description forthcoming.

public EOModalDialogController()

Description forthcoming.

Static Methods

runControllerInNewModalDialog

```
public static void runControllerInNewModalDialog(  
    EComponentController anEComponentController,  
    String aString)
```

Description forthcoming.

Instance Methods

activateWindow

```
public void activateWindow()
```

Description forthcoming.

closeWindow

```
public boolean closeWindow()
```

Description forthcoming.

isModal

```
public boolean isModal()
```

Description forthcoming.

CLASS EOModalDialogController

newWindow

protected java.awt.Window newWindow(javax.swing.JComponent aJComponent)

Description forthcoming.

EOProgrammaticSwitchController

Inherits from: EOSwitchController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
PROGRAMMATICSWITCHCONTROLLER	dividingController

Method Types

All methods

EOProgrammaticSwitchController
addBorderComponentForControllerToDisplayComponent

CLASS EOProgrammaticSwitchController

```
newDisplayComponent  
removeBorderComponentForControllerFromDisplayComponent  
selectedBorderComponentInDisplayComponent  
showBorderComponentAtIndexInDisplayComponent
```

Constructors

EOProgrammaticSwitchController

```
public EOProgrammaticSwitchController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

Instance Methods

addBorderComponentForControllerToDisplayComponent

```
protected void addBorderComponentForControllerToDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent)
```

Description forthcoming.

newDisplayComponent

```
protected javax.swing.JComponent newDisplayComponent()
```

Description forthcoming.

CLASS EOProgrammaticSwitchController

removeBorderComponentForControllerFromDisplayComponent

```
protected void removeBorderComponentForControllerFromDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

selectedBorderComponentInDisplayComponent

```
protected javax.swing.JComponent  
    selectedBorderComponentInDisplayComponent(javax.swing.JComponent aJComponent)
```

Description forthcoming.

showBorderComponentAtIndexInDisplayComponent

```
protected void showBorderComponentAtIndexInDisplayComponent(  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

CLASS EOProgrammaticSwitchController

EOSimpleWindowController

Inherits from: EOWindowController :
EOComponentController :
EOController :
Object

Implements: WindowListener (java.awt.event package)
ComponentListener (java.awt.event package)
EOComponentController.ResetUserInterface

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
None (abstract class)	windowController

Method Types

All methods

ESimpleWindowController
activateWindow
addComponentOfSubcontroller
closeWindow
componentDidBecomeInvisible
componentDidBecomeVisible
componentHidden
componentMoved
componentResized
componentShown
deactivateWindow
dispose
disposeIfDeactivated
integrationComponentDidBecomeInvisible
integrationComponentDidBecomeVisible
makeVisible
newWindow
newWindow
resetUserInterface
setDisposeIfDeactivated
setLabel
setWindow

CLASS `EOSimpleWindowController`

```
setWindowResizable  
setWindowTitle  
startListeningToWindow  
stopListeningToWindow  
subcontrollerEditedDidChange  
subcontrollerMinimumSizeDidChange  
verifyContentMinimumSize  
window  
windowActivated  
windowClosed  
windowClosing  
windowDeactivated  
windowDeiconified  
windowIconified  
windowOpened
```

Constructors

`EOSimpleWindowController`

```
public EOSimpleWindowController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOSimpleWindowController()
```

Description forthcoming.

Instance Methods

activateWindow

```
public void activateWindow()
```

Description forthcoming.

addComponentOfSubcontroller

```
protected void addComponentOfSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

closeWindow

```
public boolean closeWindow()
```

Description forthcoming.

componentDidBecomeInvisible

```
protected void componentDidBecomeInvisible()
```

Description forthcoming.

componentDidBecomeVisible

```
protected void componentDidBecomeVisible()
```

Description forthcoming.

CLASS EOSimpleWindowController

componentHidden

```
public void componentHidden(java.awt.event.ComponentEvent aComponentEvent)
```

Description forthcoming.

componentMoved

```
public void componentMoved(java.awt.event.ComponentEvent aComponentEvent)
```

Description forthcoming.

componentResized

```
public void componentResized(java.awt.event.ComponentEvent aComponentEvent)
```

Description forthcoming.

componentShown

```
public void componentShown(java.awt.event.ComponentEvent aComponentEvent)
```

Description forthcoming.

deactivateWindow

```
public void deactivateWindow()
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

CLASS EO SimpleWindowController

disposeIfDeactivated

public boolean disposeIfDeactivated()

Description forthcoming.

integrationComponentDidBecomeInvisible

protected void integrationComponentDidBecomeInvisible()

Description forthcoming.

integrationComponentDidBecomeVisible

protected void integrationComponentDidBecomeVisible()

Description forthcoming.

makeVisible

public boolean makeVisible()

Description forthcoming.

newWindow

protected abstract java.awt.Window newWindow(javax.swing.JComponent aJComponent)

Description forthcoming.

newWindow

protected java.awt.Window newWindow()

Description forthcoming.

CLASS `EOSimpleWindowController`

`resetUserInterface`

```
public void resetUserInterface()
```

Description forthcoming.

`setDisposeIfDeactivated`

```
public void setDisposeIfDeactivated(boolean aBoolean)
```

Description forthcoming.

`setLabel`

```
public void setLabel(String aString)
```

Description forthcoming.

`setWindow`

```
public void setWindow(java.awt.Window aWindow)
```

Description forthcoming.

`setWindowResizable`

```
protected abstract void setWindowResizable(  
    java.awt.Window aWindow,  
    boolean aBoolean)
```

Description forthcoming.

`setWindowTitle`

```
protected abstract void setWindowTitle(  
    java.awt.Window aWindow,  
    String aString)
```

Description forthcoming.

CLASS EOSimpleWindowController

startListeningToWindow

```
protected void startListeningToWindow()
```

Description forthcoming.

stopListeningToWindow

```
protected void stopListeningToWindow()
```

Description forthcoming.

subcontrollerEditedDidChange

```
public void subcontrollerEditedDidChange(EOController anEOController)
```

Description forthcoming.

subcontrollerMinimumSizeDidChange

```
public void subcontrollerMinimumSizeDidChange(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

verifyContentMinimumSize

```
protected java.awt.Dimension verifyContentMinimumSize(  
    java.awt.Window aWindow,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

window

```
public java.awt.Window window()
```

Description forthcoming.

CLASS EOSimpleWindowController

windowActivated

```
public void windowActivated(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowClosed

```
public void windowClosed(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowClosing

```
public void windowClosing(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowDeactivated

```
public void windowDeactivated(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowDeiconified

```
public void windowDeiconified(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowIconified

```
public void windowIconified(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

CLASS EOSimpleWindowController

windowOpened

```
public void windowOpened(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

EOSwitchController

Inherits from: EOComponentController : EOController : Object
Implements: EOComponentController.ResetUserInterface
Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
None (abstract class)	None

Method Types

All methods

EOSwitchController
addBorderComponentForControllerToDisplayComponent
addComponentOfSubcontroller

CLASS EOswitchController

borderComponents
borderSize
borderedSizeForComponentSize
componentDidBecomeInvisible
componentDidBecomeVisible
componentShouldChange
componentSizeForBorderedSize
componentSwitched
dispose
generateComponent
hideSubcontroller
inset
minimumComponentSize
newDisplayComponent
removeBorderComponentForControllerFromDisplayComponent
removeComponentOfSubcontroller
removeTransientSubcontroller
resetUserInterface
selectedBorderComponentInDisplayComponent
showBorderComponentAtIndex
showBorderComponentAtIndexInDisplayComponent
showSubcontroller
subcontrollerMinimumSizeDidChange
subcontrollerVisibilityDidChange
switchedControllers
visibleBorderComponentIndex

Constructors

EOSwitchController

```
public EOSwitchController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOSwitchController()
```

Description forthcoming.

Instance Methods

addBorderComponentForControllerToDisplayComponent

```
protected abstract void addBorderComponentForControllerToDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent)
```

Description forthcoming.

addComponentOfSubcontroller

```
protected void addComponentOfSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

CLASS EO SwitchController

borderComponents

protected NSArray borderComponents()

Description forthcoming.

borderSize

public java.awt.Dimension borderSize()

Description forthcoming.

borderedSizeForComponentSize

public java.awt.Dimension borderedSizeForComponentSize(java.awt.Dimension aDimension)

Description forthcoming.

componentDidBecomeInvisible

protected void componentDidBecomeInvisible()

Description forthcoming.

componentDidBecomeVisible

protected void componentDidBecomeVisible()

Description forthcoming.

componentShouldChange

public boolean componentShouldChange(int anInt)

Description forthcoming.

CLASS EOswitchController

componentSizeForBorderedSize

```
public java.awt.Dimension componentSizeForBorderedSize(java.awt.Dimension aDimension)
```

Description forthcoming.

componentSwitched

```
public void componentSwitched(int anInt)
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

generateComponent

```
protected void generateComponent()
```

Description forthcoming.

hideSubcontroller

```
protected boolean hideSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

inset

```
protected int inset()
```

Description forthcoming.

CLASS EOSwitchController

minimumComponentSize

```
public java.awt.Dimension minimumComponentSize()
```

Description forthcoming.

newDisplayComponent

```
protected abstract javax.swing.JComponent newDisplayComponent()
```

Description forthcoming.

removeBorderComponentForControllerFromDisplayComponent

```
protected abstract void removeBorderComponentForControllerFromDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

removeComponentOfSubcontroller

```
protected void removeComponentOfSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

removeTransientSubcontroller

```
protected boolean removeTransientSubcontroller(EOController anEOController)
```

Description forthcoming.

resetUserInterface

```
public void resetUserInterface()
```

Description forthcoming.

CLASS EO SwitchController

selectedBorderComponentInDisplayComponent

```
protected abstract javax.swing.JComponent  
    selectedBorderComponentInDisplayComponent(javax.swing.JComponent aJComponent)
```

Description forthcoming.

showBorderComponentAtIndex

```
protected void showBorderComponentAtIndex(int anInt)
```

Description forthcoming.

showBorderComponentAtIndexInDisplayComponent

```
protected abstract void showBorderComponentAtIndexInDisplayComponent(  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

showSubcontroller

```
protected boolean showSubcontroller(EOComponentController anEOComponentController)
```

Description forthcoming.

subcontrollerMinimumSizeDidChange

```
public void subcontrollerMinimumSizeDidChange(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    java.awt.Dimension aDimension)
```

Description forthcoming.

CLASS EOSwitchController

subcontrollerVisibilityDidChange

```
public void subcontrollerVisibilityDidChange(EOComponentController anEOComponentController)
```

Description forthcoming.

switchedControllers

```
protected NSArray switchedControllers()
```

Description forthcoming.

visibleBorderComponentIndex

```
protected int visibleBorderComponentIndex()
```

Description forthcoming.

EOTabSwitchController

Inherits from: EOSwitchController :
EOComponentController :
EOController :
Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
TABSWITCHCONTROLLER	dividingController

Method Types

All methods

EOTabSwitchController
addBorderComponentForControllerToDisplayComponent

CLASS EOTabSwitchController

borderSize
inset
newDisplayComponent
removeBorderComponentForControllerFromDisplayComponent
selectedBorderComponentInDisplayComponent
showBorderComponentAtIndexInDisplayComponent

Constructors

EOTabSwitchController

```
public EOTabSwitchController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOSTabSwitchController()
```

Description forthcoming.

Instance Methods

addBorderComponentForControllerToDisplayComponent

```
protected void addBorderComponentForControllerToDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOTabSwitchController

borderSize

```
public java.awt.Dimension borderSize()
```

Description forthcoming.

inset

```
protected int inset()
```

Description forthcoming.

newDisplayComponent

```
protected javax.swing.JComponent newDisplayComponent()
```

Description forthcoming.

removeBorderComponentForControllerFromDisplayComponent

```
protected void removeBorderComponentForControllerFromDisplayComponent(  
    EOComponentController anEOComponentController,  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

selectedBorderComponentInDisplayComponent

```
protected javax.swing.JComponent  
    selectedBorderComponentInDisplayComponent(javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOTabSwitchController

showBorderComponentAtIndexInDisplayComponent

```
protected void showBorderComponentAtIndexInDisplayComponent(  
    javax.swing.JComponent aJComponent,  
    javax.swing.JComponent aJComponent,  
    int anInt)
```

Description forthcoming.

EOUserInterfaceParameters

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

actionTitleFont

actionTitlePosition

allowsActionIcons

allowsIcons

allowsSmallActionIcons

disabledTextBackgroundColor

CLASS EOUserInterfaceParameters

editableTextBackgroundColor
highlightLabelColor
highlightLabelFont
highlightTitleColor
highlightTitleFont
labelColor
labelFont
largeBorder
localizedIcon
localizedString
makeIconBackgroundsTransparent
mediumBorder
minimumActionButtonSize
minimumSmallActionButtonSize
minimumSpecialActionButtonSize
optimizesMenuAccelerators
queryTextBackgroundColor
setActionTitleFont
setActionTitlePosition
setAllowsActionIcons
setAllowsIcons
setAllowsSmallActionIcons
setBorders
setDisabledTextBackgroundColor
setEditableTextBackgroundColor
setHighlightLabelColor
setHighlightLabelFont

CLASS EOUserInterfaceParameters

setHighlightTitleColor
setHighlightTitleFont
setLabelColor
setLabelFont
setMakeIconBackgroundsTransparent
setMinimumActionButtonSize
setMinimumSmallActionButtonSize
setMinimumSpecialActionButtonSize
setOptimizesMenuAccelerators
setQueryTextBackgroundColor
setSmallActionTitleFont
setSmallActionTitlePosition
setSpecialActionTitleFont
setSpecialActionTitlePosition
setStandardResourceBundle
setTitleColor
setTitleFont
setUsesBorderWithActionIcons
setUsesBorderWithSmallActionIcons
setUsesSpecialColors
setUsesSpecialFonts
setUsesTitleWithActionIcons
setUsesTitleWithSmallActionIcons
setUsesWindowMenus
setWidgetFont
smallActionTitleFont
smallActionTitlePosition

CLASS EOUInterfaceParameters

smallBorder
specialActionTitleFont
specialActionTitlePosition
standardActionIcon
standardResourceBundle
standardSmallActionIcon
titleColor
titleFont
usesBorderWithActionIcons
usesBorderWithSmallActionIcons
usesSpecialColors
usesSpecialFonts
usesTitleWithActionIcons
usesTitleWithSmallActionIcons
usesWindowMenus
widgetFont

Constructors

EOUInterfaceParameters

public EOUInterfaceParameters()

Description forthcoming.

Static Methods

actionTitleFont

```
public static java.awt.Font actionTitleFont()
```

Description forthcoming.

actionTitlePosition

```
public static int actionTitlePosition()
```

Description forthcoming.

allowsActionIcons

```
public static boolean allowsActionIcons()
```

Description forthcoming.

allowsIcons

```
public static boolean allowsIcons()
```

Description forthcoming.

allowsSmallActionIcons

```
public static boolean allowsSmallActionIcons()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

disabledTextBackgroundColor

```
public static java.awt.Color disabledTextBackgroundColor()
```

Description forthcoming.

editableTextBackgroundColor

```
public static java.awt.Color editableTextBackgroundColor()
```

Description forthcoming.

highlightLabelColor

```
public static java.awt.Color highlightLabelColor()
```

Description forthcoming.

highlightLabelFont

```
public static java.awt.Font highlightLabelFont()
```

Description forthcoming.

highlightTitleColor

```
public static java.awt.Color highlightTitleColor()
```

Description forthcoming.

highlightTitleFont

```
public static java.awt.Font highlightTitleFont()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

labelColor

public static java.awt.Color labelColor()

Description forthcoming.

labelFont

public static java.awt.Font labelFont()

Description forthcoming.

largeBorder

public static int largeBorder()

Description forthcoming.

localizedIcon

public static javax.swing.Icon localizedIcon(String aString)

Description forthcoming.

localizedString

public static String localizedString(String aString)

Description forthcoming.

makeIconBackgroundsTransparent

public static boolean makeIconBackgroundsTransparent()

Description forthcoming.

CLASS EOUserInterfaceParameters

mediumBorder

```
public static int mediumBorder()
```

Description forthcoming.

minimumActionButtonSize

```
public static java.awt.Dimension minimumActionButtonSize()
```

Description forthcoming.

minimumSmallActionButtonSize

```
public static java.awt.Dimension minimumSmallActionButtonSize()
```

Description forthcoming.

minimumSpecialActionButtonSize

```
public static java.awt.Dimension minimumSpecialActionButtonSize()
```

Description forthcoming.

optimizesMenuAccelerators

```
public static boolean optimizesMenuAccelerators()
```

Description forthcoming.

queryTextBackgroundColor

```
public static java.awt.Color queryTextBackgroundColor()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setActionTitleFont

```
public static void setActionTitleFont(java.awt.Font aFont)
```

Description forthcoming.

setActionTitlePosition

```
public static void setActionTitlePosition(int anInt)
```

Description forthcoming.

setAllowsActionIcons

```
public static void setAllowsActionIcons(boolean aBoolean)
```

Description forthcoming.

setAllowsIcons

```
public static void setAllowsIcons(boolean aBoolean)
```

Description forthcoming.

setAllowsSmallActionIcons

```
public static void setAllowsSmallActionIcons(boolean aBoolean)
```

Description forthcoming.

setBorders

```
public static void setBorders(  
    int anInt,  
    int anInt,  
    int anInt)
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setDisabledTextBackgroundColor

```
public static void setDisabledTextBackgroundColor(java.awt.Color aColor)
```

Description forthcoming.

setEditableTextBackgroundColor

```
public static void setEditableTextBackgroundColor(java.awt.Color aColor)
```

Description forthcoming.

setHighlightLabelColor

```
public static void setHighlightLabelColor(java.awt.Color aColor)
```

Description forthcoming.

setHighlightLabelFont

```
public static void setHighlightLabelFont(java.awt.Font aFont)
```

Description forthcoming.

setHighlightTitleColor

```
public static void setHighlightTitleColor(java.awt.Color aColor)
```

Description forthcoming.

setHighlightTitleFont

```
public static void setHighlightTitleFont(java.awt.Font aFont)
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setLabelColor

```
public static void setLabelColor(java.awt.Color aColor)
```

Description forthcoming.

setLabelFont

```
public static void setLabelFont(java.awt.Font aFont)
```

Description forthcoming.

setMakeIconBackgroundsTransparent

```
public static void setMakeIconBackgroundsTransparent(boolean aBoolean)
```

Description forthcoming.

setMinimumActionButtonSize

```
public static void setMinimumActionButtonSize(java.awt.Dimension aDimension)
```

Description forthcoming.

setMinimumSmallActionButtonSize

```
public static void setMinimumSmallActionButtonSize(java.awt.Dimension aDimension)
```

Description forthcoming.

setMinimumSpecialActionButtonSize

```
public static void setMinimumSpecialActionButtonSize(java.awt.Dimension aDimension)
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setOptimizesMenuAccelerators

```
public static void setOptimizesMenuAccelerators(boolean aBoolean)
```

Description forthcoming.

setQueryTextBackgroundColor

```
public static void setQueryTextBackgroundColor(java.awt.Color aColor)
```

Description forthcoming.

setSmallActionTitleFont

```
public static void setSmallActionTitleFont(java.awt.Font aFont)
```

Description forthcoming.

setSmallActionTitlePosition

```
public static void setSmallActionTitlePosition(int anInt)
```

Description forthcoming.

setSpecialActionTitleFont

```
public static void setSpecialActionTitleFont(java.awt.Font aFont)
```

Description forthcoming.

setSpecialActionTitlePosition

```
public static void setSpecialActionTitlePosition(int anInt)
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setStandardResourceBundle

```
public static void setStandardResourceBundle(java.util.ResourceBundle aResourceBundle)
```

Description forthcoming.

setTitleColor

```
public static void setTitleColor(java.awt.Color aColor)
```

Description forthcoming.

setTitleFont

```
public static void setTitleFont(java.awt.Font aFont)
```

Description forthcoming.

setUsesBorderWithActionIcons

```
public static void setUsesBorderWithActionIcons(boolean flag)
```

Description forthcoming.

setUsesBorderWithSmallActionIcons

```
public static void setUsesBorderWithSmallActionIcons(boolean flag)
```

Description forthcoming.

setUsesSpecialColors

```
public static void setUsesSpecialColors(boolean aBoolean)
```

Description forthcoming.

CLASS EOUserInterfaceParameters

setUsesSpecialFonts

```
public static void setUsesSpecialFonts(boolean aBoolean)
```

Description forthcoming.

setUsesTitleWithActionIcons

```
public static void setUsesTitleWithActionIcons(boolean aBoolean)
```

Description forthcoming.

setUsesTitleWithSmallActionIcons

```
public static void setUsesTitleWithSmallActionIcons(boolean aBoolean)
```

Description forthcoming.

setUsesWindowMenus

```
public static void setUsesWindowMenus(boolean aBoolean)
```

Description forthcoming.

setWidgetFont

```
public static void setWidgetFont(java.awt.Font aFont)
```

Description forthcoming.

smallActionTitleFont

```
public static java.awt.Font smallActionTitleFont()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

smallActionTitlePosition

```
public static int smallActionTitlePosition()
```

Description forthcoming.

smallBorder

```
public static int smallBorder()
```

Description forthcoming.

specialActionTitleFont

```
public static java.awt.Font specialActionTitleFont()
```

Description forthcoming.

specialActionTitlePosition

```
public static int specialActionTitlePosition()
```

Description forthcoming.

standardActionIcon

```
public static javax.swing.Icon standardActionIcon(String aString)
```

Description forthcoming.

standardResourceBundle

```
public static java.util.ResourceBundle standardResourceBundle()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

standardSmallActionIcon

```
public static javax.swing.Icon standardSmallActionIcon(String aString)
```

Description forthcoming.

titleColor

```
public static java.awt.Color titleColor()
```

Description forthcoming.

titleFont

```
public static java.awt.Font titleFont()
```

Description forthcoming.

usesBorderWithActionIcons

```
public static boolean usesBorderWithActionIcons()
```

Description forthcoming.

usesBorderWithSmallActionIcons

```
public static boolean usesBorderWithSmallActionIcons()
```

Description forthcoming.

usesSpecialColors

```
public static boolean usesSpecialColors()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

usesSpecialFonts

```
public static boolean usesSpecialFonts()
```

Description forthcoming.

usesTitleWithActionIcons

```
public static boolean usesTitleWithActionIcons()
```

Description forthcoming.

usesTitleWithSmallActionIcons

```
public static boolean usesTitleWithSmallActionIcons()
```

Description forthcoming.

usesWindowMenus

```
public static boolean usesWindowMenus()
```

Description forthcoming.

widgetFont

```
public static java.awt.Font widgetFont()
```

Description forthcoming.

CLASS EOUserInterfaceParameters

EOWindowController

Inherits from: EOComponentController : EOController : Object

Implements: ActionListener (java.awt.event package)
EOComponentController.Activation

Package: com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

XML Tag	Default Rule System Controller Type
None (abstract class)	windowController

Method Types

All methods

EOWindowController

generateBorderSizeForRootPaneContainerClass

CLASS EOWindowController

actionPerformed
activate
activateWindow
borderSize
borderedSizeForComponentSize
componentDidBecomeInvisible
componentShouldBeResizable
componentSizeForBorderedSize
defaultActions
dispose
generateBorderSize
generateComponent
integrationComponent
minimumIntegrationComponentSize
removeTransientSubcontroller
setUsesActivationAction
setUsesActivationButton
setUsesUserDefaultsWindowLocation
setUsesUserDefaultsWindowSize
setWindowPosition
usesActivationAction
usesActivationButton
usesUserDefaultsWindowLocation
usesUserDefaultsWindowSize
windowPosition

Constructors

EOWindowController

```
public EOWindowController(EOXMLUnarchiver anEOXMLUnarchiver)
```

Description forthcoming.

```
public EOWindowController()
```

Description forthcoming.

Static Methods

generateBorderSizeForRootPaneContainerClass

```
protected static java.awt.Dimension generateBorderSizeForRootPaneContainerClass(  
    Class aClass,  
    boolean aBoolean)
```

Description forthcoming.

Instance Methods

actionPerformed

```
public void actionPerformed(java.awt.event.ActionEvent anActionEvent)
```

Description forthcoming.

CLASS EOWindowController

activate

```
public boolean activate()
```

Description forthcoming.

activateWindow

```
public abstract void activateWindow()
```

Description forthcoming.

borderSize

```
public java.awt.Dimension borderSize()
```

Description forthcoming.

borderedSizeForComponentSize

```
public java.awt.Dimension borderedSizeForComponentSize(java.awt.Dimension aDimension)
```

Description forthcoming.

componentDidBecomeInvisible

```
protected void componentDidBecomeInvisible()
```

Description forthcoming.

componentShouldBeResizable

```
protected boolean componentShouldBeResizable(javax.swing.JComponent aJComponent)
```

Description forthcoming.

CLASS EOWindowController

componentSizeForBorderedSize

```
public java.awt.Dimension componentSizeForBorderedSize(java.awt.Dimension aDimension)
```

Description forthcoming.

defaultActions

```
protected NSArray defaultActions()
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

generateBorderSize

```
protected java.awt.Dimension generateBorderSize()
```

Description forthcoming.

generateComponent

```
protected void generateComponent()
```

Description forthcoming.

integrationComponent

```
public javax.swing.JComponent integrationComponent()
```

Description forthcoming.

CLASS EOWindowController

minimumIntegrationComponentSize

```
public java.awt.Dimension minimumIntegrationComponentSize()
```

Description forthcoming.

removeTransientSubcontroller

```
protected boolean removeTransientSubcontroller(EOController anEOController)
```

Description forthcoming.

setUsesActivationAction

```
public void setUsesActivationAction(boolean aBoolean)
```

Description forthcoming.

setUsesActivationButton

```
public void setUsesActivationButton(boolean aBoolean)
```

Description forthcoming.

setUsesUserDefaultsWindowLocation

```
public void setUsesUserDefaultsWindowLocation(boolean aBoolean)
```

Description forthcoming.

setUsesUserDefaultsWindowSize

```
public void setUsesUserDefaultsWindowSize(boolean aBoolean)
```

Description forthcoming.

CLASS EOWindowController

setWindowPosition

public void setWindowPosition(int anInt)

Description forthcoming.

usesActivationAction

public boolean usesActivationAction()

Description forthcoming.

usesActivationButton

public boolean usesActivationButton()

Description forthcoming.

usesUserDefaultsWindowLocation

public boolean usesUserDefaultsWindowLocation()

Description forthcoming.

usesUserDefaultsWindowSize

public boolean usesUserDefaultsWindowSize()

Description forthcoming.

windowPosition

public int windowPosition()

Description forthcoming.

CLASS EOWindowController

EOWindowObserver

Inherits from:	Object
Implements:	WindowListener (java.awt.event package) NSDisposable
Package:	com.webobjects.eoapplication

Class Description

Documentation for this class is forthcoming. For information on using this class, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

- activateBestWindow
- activatePreviousWindow
- activeWindow
- blockActiveWindowChangedNotification
- controllerForActiveWindow

CLASS EWindowObserver

controllerForLatestDeactivatedWindow
controllerForWindow
dispose
latestDeactivatedWindow
previousWindowToActivate
registerWindow
registerWindow
registeredWindows
unblockActiveWindowChangedNotification
unregisterWindow
unregisterWindowOfController
visibleWindows
windowActivated
windowClosed
windowClosing
windowDeactivated
windowDeiconified
windowDidBecomeActive
windowDidBecomeInactive
windowDidBecomeInvisible
windowDidBecomeVisible
windowForController
windowIconified
windowOpened

Constructors

EWindowObserver

protected EWindowObserver()

Description forthcoming.

Instance Methods

activateBestWindow

public void activateBestWindow()

Description forthcoming.

activatePreviousWindow

public void activatePreviousWindow()

Description forthcoming.

activeWindow

public java.awt.Window activeWindow()

Description forthcoming.

CLASS EOWindowObserver

blockActiveWindowChangedNotification

```
public void blockActiveWindowChangedNotification()
```

Description forthcoming.

controllerForActiveWindow

```
public EOController controllerForActiveWindow()
```

Description forthcoming.

controllerForLatestDeactivatedWindow

```
public EOController controllerForLatestDeactivatedWindow()
```

Description forthcoming.

controllerForWindow

```
public EOController controllerForWindow(java.awt.Window aWindow)
```

Description forthcoming.

dispose

```
public void dispose()
```

Description forthcoming.

latestDeactivatedWindow

```
public java.awt.Window latestDeactivatedWindow()
```

Description forthcoming.

CLASS EOWindowObserver

previousWindowToActivate

```
public java.awt.Window previousWindowToActivate()
```

Description forthcoming.

registerWindow

```
public void registerWindow(  
    java.awt.Window aWindow,  
    EOController anEOController)
```

Description forthcoming.

registerWindow

```
public void registerWindow(java.awt.Window aWindow)
```

Description forthcoming.

registeredWindows

```
public NSArray registeredWindows()
```

Description forthcoming.

unlockActiveWindowChangedNotification

```
public void unlockActiveWindowChangedNotification()
```

Description forthcoming.

unregisterWindow

```
public void unregisterWindow(java.awt.Window aWindow)
```

Description forthcoming.

CLASS EOWindowObserver

unregisterWindowOfController

```
public void unregisterWindowOfController(EOController anEOController)
```

Description forthcoming.

visibleWindows

```
public NSArray visibleWindows()
```

Description forthcoming.

windowActivated

```
public void windowActivated(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowClosed

```
public void windowClosed(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowClosing

```
public void windowClosing(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowDeactivated

```
public void windowDeactivated(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

CLASS EOWindowObserver

windowDeiconified

public void windowDeiconified(java.awt.event.WindowEvent aWindowEvent)

Description forthcoming.

windowDidBecomeActive

protected void windowDidBecomeActive(java.awt.Window aWindow)

Description forthcoming.

windowDidBecomeInactive

protected void windowDidBecomeInactive(java.awt.Window aWindow)

Description forthcoming.

windowDidBecomeInvisible

protected void windowDidBecomeInvisible(java.awt.Window aWindow)

Description forthcoming.

windowDidBecomeVisible

protected void windowDidBecomeVisible(java.awt.Window aWindow)

Description forthcoming.

windowForController

public java.awt.Window windowForController(EOController anEOController)

Description forthcoming.

CLASS EOWindowObserver

windowIconified

```
public void windowIconified(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

windowOpened

```
public void windowOpened(java.awt.event.WindowEvent aWindowEvent)
```

Description forthcoming.

EOXMLUnarchiver

Inherits from: Object

Package: com.webobjects.eoapplication

Class Description

EOXMLUnarchiver objects contain the parameters used to create controllers (objects of the EOController class and its descendents) in the controller hierarchy. The parameters are determined from an XML specification sent from server.

For more information on using this class, see the book *Getting Started with Direct to Java Client*.

Constants

EOXMLUnarchiver defines the following String constants:

Constant	Description
-----------------	--------------------

ActionKeyParameter	
--------------------	--

ActionNameParameter	
---------------------	--

ActionPriorityParameter	
-------------------------	--

CLASS EOXMLUnarchiver

Constant	Description
ActionWidgetPositionParameter	
AlignmentParameter	
AlignmentWidthParameter	
AlignsComponentsParameter	
AllowsMultipleSelectionParameter	
ArchiveNameParameter	
BorderTypeParameter	
ButtonPositionParameter	
CategoryNameParameter	
CategoryPriorityParameter	
ClassNameParameter	
ColorParameter	
DescriptionPathParameter	
DisabledActionNamesParameter	
DisplayGroupProviderMethodNameParameter	
DisplaysLabelInWidgetParameter	
DisposeIfDeactivatedParameter	
EditabilityParameter	
EditingContextProviderMethodNameParameter	
EnabledDisplayGroupProviderMethodNameParameter	
EnabledKeyParameter	
EntityParameter	

CLASS EOXMLUnarchiver

Constant	Description
FontParameter	
FormatAllowedParameter	
FormatClassParameter	
FormatPatternParameter	
HighlightParameter	
HorizontalBorderParameter	
HorizontallyResizableParameter	
IconNameParameter	
IconURLParameter	
ImageScalingParameter	
IsQueryWidgetParameter	
LabelAlignmentParameter	
LabelComponentPositionParameter	
LabelParameter	
MandatoryRelationshipPathsParameter	
MaximumValueKeyParameter	
MenuAcceleratorParameter	
MinimumHeightParameter	
MinimumValueKeyParameter	
MinimumWidthParameter	
MultipleWindowsAvailableParameter	
PrefersIconOnlyParameter	
QuickTimeCanvasResizingParameter	

CLASS EOXMLUnarchiver

Constant	Description
RelationshipPathParameter	
ScalingHintsParameter	
SendsActionToAllControllersParameter	
SharedIdentifierParameter	
ShortDescriptionParameter	
SmallIconNameParameter	
SmallIconURLParameter	
SortsByColumnOrderParameter	
TaskParameter	
TitleKeysParameter	
TitlePositionParameter	
TitlesDisplayGroupProviderMethodNameParameter	
TitlesEntityParameter	
TypeNameParameter	
URLKeyParameter	
UsesActionParameter	
UsesButtonParameter	
UsesHorizontalLayoutParameter	
UsesLabelComponentParameter	
UsesLargeButtonRepresentationParameter	
UsesTitledBorderParameter	

CLASS EOXMLUnarchiver

Constant	Description
UsesUserDefaultsWindowLocationParameter	
UsesUserDefaultsWindowSizeParameter	
ValueKeyParameter	
VerticalBorderParameter	
VerticallyResizableParameter	
WindowPositionParameter	

Method Types

Decoding objects

- decodeAlignmentForKey
- decodeArrayForKey
- decodeBooleanForKey
- decodeClassForKey
- decodeColorForKey
- decodeDictionaryForKey
- decodeEditabilityForKey
- decodeFontForKey
- decodeIntForKey
- decodePositionForKey
- decodeStringForKey
- decodeValueForKey

CLASS EOXMLUnarchiver

Other methods

EOXMLUnarchiver
decodeRootObject
decodeChildren

Constructors

EOXMLUnarchiver

```
public EOXMLUnarchiver(NSDictionary values)
```

Creates an XML archiver based on the `values` `NSDictionary`.

Static Methods

decodeRootObject

```
public static Object decodeRootObject(NSDictionary aNSDictionary)
```

Decodes the top controller in an XML description, which is represented by an `NSDictionary`.

Instance Methods

decodeAlignmentForKey

```
public int decodeAlignmentForKey(  
    String key,  
    int defaultAlignment)
```

Returns an alignment specification (JTextField.LEFT, JTextField.CENTER, or JTextField.RIGHT) for the `key` XML attribute. If no value for `key` is specified, returns `defaultAlignment`.

```
public int decodeAlignmentForKey(String key)
```

Returns an alignment specification (JTextField.LEFT, JTextField.CENTER, or JTextField.RIGHT) for the `key` XML attribute. If no value for `key` is specified, returns `JTextField.LEFT`.

decodeArrayForKey

```
public NSArray decodeArrayForKey(  
    String key,  
    NSArray defaultArray)
```

Returns an NSArray for the `key` XML attribute. If no value for `key` is specified, returns `defaultArray`.

```
public NSArray decodeArrayForKey(String key)
```

Returns an NSArray for the `key` XML attribute. If no value for `key` is specified, returns `null`.

decodeBooleanForKey

```
public boolean decodeBooleanForKey(  
    String key,  
    boolean defaultBoolean)
```

Returns a boolean for the `key` XML attribute. If no value for `key` is specified, returns `defaultBoolean`.

CLASS EOXMLUnarchiver

```
public boolean decodeBooleanForKey(String key)
```

Returns a `boolean` for `key` XML attribute. If no value for `key` is specified, returns `false`.

decodeChildren

```
public NSArray decodeChildren()
```

Returns an `NSArray` containing the receiver's decoded children. The children are the objects created from XML tags contained in the receiver's XML description.

decodeClassForKey

```
public Class decodeClassForKey(  
    String key,  
    Class defaultClass)
```

Returns a `Class` for the `key` XML attribute. If no value for `key` is specified, returns `defaultClass`.

```
public Class decodeClassForKey(String key)
```

Returns a `Class` for the `key` XML attribute. If no value for `key` is specified, returns `null`.

decodeColorForKey

```
public java.awt.Color decodeColorForKey(  
    String key,  
    java.awt.Color defaultColor)
```

Returns a `color` (a `java.awt.Color` object) for the `key` XML attribute. If no value for `key` is specified, returns `defaultColor`.

```
public java.awt.Color decodeColorForKey(String key)
```

Returns a `color` (a `java.awt.Color` object) for the `key` XML attribute. If no value for `key` is specified, returns `null`.

CLASS EOXMLUnarchiver

decodeDictionaryForKey

```
public NSDictionary decodeDictionaryForKey(  
    String key,  
    NSDictionary defaultDictionary)
```

Returns a NSDictionary for the `key` XML attribute. If no value for `key` is specified, returns `defaultDictionary`.

```
public NSDictionary decodeDictionaryForKey(String key)
```

Returns a NSDictionary for the `key` XML attribute. If no value for `key` is specified, returns `null`.

decodeEditabilityForKey

```
public int decodeEditabilityForKey(  
    String key,  
    int defaultEditability)
```

Returns an editability specification (`EOEditable.IfSupercontrollerEditable`, `EOEditable.AlwaysEditable`, or `EOEditable.NeverEditable`) for the `key` XML attribute. If no value for `key` is specified, returns `defaultEditability`.

```
public int decodeEditabilityForKey(String key)
```

Returns an editability specification (`EOEditable.IfSupercontrollerEditable`, `EOEditable.AlwaysEditable`, or `EOEditable.NeverEditable`) for the `key` XML attribute. If no value for `key` is specified, returns `EOEditable.IfSupercontrollerEditable`.

decodeFontForKey

```
public java.awt.Font decodeFontForKey(  
    String key,  
    java.awt.Font defaultFont)
```

Returns a font specification (a `java.awt.Font` object) for the `key` XML attribute. If no value for `key` is specified, returns `defaultFont`.

```
public java.awt.Font decodeFontForKey(String key)
```

Returns a font specification (a `java.awt.Font` object) for the `key` XML attribute. If no value for `key` is specified, returns `null`.

CLASS EOXMLUnarchiver

decodeIntForKey

```
public int decodeIntForKey(  
    String key,  
    int defaultInt)
```

Returns an `int` for the `key` XML attribute. If no value for `key` is specified, returns `defaultInt`.

```
public int decodeIntForKey(String key)
```

Returns an `int` for the `key` XML attribute. If no value for `key` is specified, returns `0`.

decodePositionForKey

```
public int decodePositionForKey(  
    String key,  
    int defaultPosition)
```

Returns a position specification (`E0ComponentController.Top`, `E0ComponentController.Bottom`, `E0ComponentController.Left`, `E0ComponentController.Right`, `E0ComponentController.TopLeft`, `E0ComponentController.TopRight`, `E0ComponentController.BottomLeft`, or `E0ComponentController.BottomRight`) for the `key` XML attribute. If no value for `key` is specified, returns `defaultPosition`.

```
public int decodePositionForKey(String key)
```

Returns a position specification (`E0ComponentController.Top`, `E0ComponentController.Bottom`, `E0ComponentController.Left`, `E0ComponentController.Right`, `E0ComponentController.TopLeft`, `E0ComponentController.TopRight`, `E0ComponentController.BottomLeft`, or `E0ComponentController.BottomRight`) for the `key` XML attribute. If no value for `key` is specified, returns `E0ComponentController.Center`.

decodeStringForKey

```
public String decodeStringForKey(  
    String key,  
    String defaultString)
```

Returns a `String` for the `key` XML attribute. If no value for `key` is specified, returns `defaultString`.

```
public String decodeStringForKey(String key)
```

Returns a `String` for the `key` XML attribute. If no value for `key` is specified, returns `null`.

CLASS EOXMLUnarchiver

decodeValueForKey

```
public Object decodeValueForKey(String key)
```

Returns an Object for the `key` XML attribute. If no value for `key` is specified, returns `null`.

CLASS EOXMLUnarchiver

EOAction.ActiveWindowDependentAction

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Instance Methods

updateInContextOfActiveWindowController

```
public abstract void updateInContextOfActiveWindowController(EOController anEOController)
```

INTERFACE EOAction.ActiveWindowDependentAction

EOAction.Enabling

Implemented by: EOController
Package: com.webobjects.eoapplication

Interface Description

The EOAction.Enabling interface defines a method, `canPerformActionNamed`, which allows you to tell if an action (an EOAction object) is enabled for the receiver.

Instance Methods

canPerformActionNamed

```
public abstract boolean canPerformActionNamed(String actionName)
```

Returns `true` if the receiver can perform an action (an EOAction object) named `actionName`, `false` otherwise. An EOController's implementation of this method generally returns `false` if the receiver doesn't have an action named `actionName` or if the `actionName` action is disabled.

See Also: `isActionNamedEnabled` (EOController)

INTERFACE EOAction.Enabling

EOActionWidgetController.ActionCollector

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

collectedActions

Instance Methods

collectedActions

public abstract NSArray collectedActions()

EOAssociationConnector

Implemented by: EOAssociationController,
EOEntityController,
EORangeValueController,
EOTableController

Package: com.webobjects.eoapplication

Interface Description

EOAssociationConnector is an interface that defines an object that can assume the responsibilities for connecting and disconnecting the associations of a transient subcontroller.

Instance Methods

takeResponsibilityForConnectionOfAssociation

```
public abstract void  
    takeResponsibilityForConnectionOfAssociation(com.webobjects.eointerface.EOAssociation association)
```

Invoked when one of the receiver's subcontrollers is disposed as a transient controller. This method instructs the receiver to assume responsibility for managing the subcontroller's EOAssociation, *association*.

INTERFACE EOAssociationConnector

EOComponentController.Activation

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Instance Methods

activate

```
public abstract boolean activate()
```

INTERFACE EOComponentController.Activation

EOComponentController.EndEditing

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Instance Methods

endEditing

```
public abstract boolean endEditing()
```

INTERFACE EOComponentController.EndEditing

EOComponentController.Modal

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Method Types

All methods

isModal

Instance Methods

isModal

`public abstract boolean isModal()`

EOComponentController.ResetUserInterface

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming. For information on using this interface, see the book *Getting Started with Direct to Java Client*.

Instance Methods

resetUserInterface

```
public abstract void resetUserInterface()
```

INTERFACE EOComponentController.ResetUserInterface

EOController.Enumeration

Implements: `java.util.Enumeration`

Package: `com.webobjects.eoapplication`

Interface Description

EOController.Enumeration is an interface that defines an enumeration that iterates over a set of EOController objects. It adds one method to the `java.util.Enumeration` interface: `nextController`, which simply returns the next controller in the enumeration's set. The `nextController` method saves you from having to cast the returned object to an EOController.

Use the EOController method `controllerEnumeration` to get an EOController.Enumeration. You can create three types of enumerations:

`SubcontrollersEnumeration`

Includes all the descendants of a controller—the controller's subcontrollers, their subcontrollers, and so on down the controller hierarchy—not including the controller itself.

`SupercontrollersEnumeration`

Includes all the ancestors of a controller—the controller's supercontroller, its supercontroller, and so on up the controller hierarchy—not including the controller itself.

`ControllerAndSubcontrollersEnumeration`

Includes a controller and all its descendants.

INTERFACE EOController.Enumeration

You can further restrict the controllers included in an enumeration by specifying an interface the controllers must implement in order to be included. For more information, see the method description for `controllerEnumeration` in the `EOController` class specification.

Instance Methods

nextController

```
public abstract EOController nextController()
```

Returns the next controller in the enumeration. Use this method instead of `nextElement` because it saves you a cast and because its implementation is more efficient.

See Also: `controllerEnumeration` (`EOController`)

EOModalDialogController.ModalActions

Package: com.webobjects.eoapplication

Interface Description

Documentation for this interface is forthcoming.

Method Types

All methods

cancel

modalDialogShouldClose

ok

Instance Methods

cancel

public abstract void cancel()

Description forthcoming.

modalDialogShouldClose

public abstract boolean modalDialogShouldClose()

Description forthcoming.

ok

public abstract boolean ok()

Description forthcoming.

EODocument

Implemented by:	EODocumentController
Implements:	EObjectDisplay
Package:	com.webobjects.eoapplication

Interface Description

EODocument is an interface that defines the behavior of a controller that displays and edits enterprise objects.

Instance Methods

isDocumentForGlobalID

```
public abstract boolean isDocumentForGlobalID(  
    com.webobjects.eocontrol.EOGlobalID globalID,  
    String entityName)
```

Returns `true` if the receiver is a document for the enterprise object associated with `globalID` and `entityName`, `false` otherwise. Typically implementations return `true` if the receiver's display group is displaying the specified enterprise object.

INTERFACE EODocument

isEdited

```
public abstract boolean isEdited()
```

Returns `true` if the receiver has unsaved edits, `false` otherwise.

save

```
public abstract boolean save()
```

Saves the receiver's edits, returning `true` on success or `false` otherwise.

saveIfUserConfirms

```
public abstract boolean saveIfUserConfirms(  
    String operationTitle,  
    String message)
```

If the receiver's enterprise object has been edited, opens an alert panel that allows the user to save the edits, discard the edits, or cancel the save operation. The `operationTitle` argument is used as the title of the alert panel, and `message` is used as the message in the panel. Returns `true` if the save succeeds, `false` upon failure or if the user cancels.

setEdited

```
public abstract void setEdited(boolean flag)
```

Sets the receiver's edited status according to `flag`.

EOEditable

Implemented by: EOAssociationController,
EODocumentController,
EORangeValueController

Package: com.webobjects.eoapplication

Interface Description

EOEditable is an interface that defines an API for managing the editability of a branch of the controller hierarchy. EOEditable controllers usually base the editability of their user interfaces on the editability of their supercontrollers. Thus, by default all the EOEditable subcontrollers of an editable controller are also editable. To enable or disable a portion of an application's user interface, you need only message the highest level controller associated with that user interface.

Constants

EOEditable defines the following `int` constants to identify the editability of an EOEditable controller:

Constant	Description
<code>NeverEditable</code>	The controller is never editable.
<code>AlwaysEditable</code>	The controller is always editable.
<code>IfSupercontrollerEditable</code>	The controller is editable only if its supercontroller is editable. If none of the controller's ancestors implement EOEditable, then its the same as if the controller is <code>AlwaysEditable</code> .

Instance Methods

editability

```
public abstract int editability()
```

Returns the editability of the receiver, one of `NeverEditable`, `AlwaysEditable`, or `IfSupercontrollerEditable`. The default behavior should be to return `IfSupercontrollerEditable`.

isEditable

```
public abstract boolean isEditable()
```

Returns `true` if the receiver is editable, and `false` otherwise. The default behavior should be to return `true` if the receiver is currently editable. The receiver is editable if:

n The receiver's editability is `AlwaysEditable`.

INTERFACE EOEditable

ⁿ The receiver's editability is `IfSupercontrollerEditable` and sending `isEditable` to the first `EOEditable` ancestor of the receiver returns `true`.

setEditability

```
public abstract void setEditability(int editability)
```

Sets the receiver's editability to `editability`, one of `NeverEditable`, `AlwaysEditable`, or `IfSupercontrollerEditable`.

supercontrollerEditabilityDidChange

```
public abstract void supercontrollerEditabilityDidChange()
```

Invoked to notify the receiver that the editability of its supercontroller changed, giving the receiver the opportunity to update its user interface to match the editability of the supercontroller.

takeResponsibilityForEditabilityOfAssociation

```
public abstract void takeResponsibilityForEditabilityOfAssociation(  
    com.webobjects.eointerface.EOAssociation association)
```

Invoked when one of the receiver's subcontrollers is disposed as a transient controller. This method instructs the receiver to assume responsibility for managing the editability of the subcontroller's `EOAssociation`, `association`.

INTERFACE EOEditable

EObjectDisplay

Implemented by: EOEntityController

Package: com.webobjects.eoapplication

Interface Description

EObjectDisplay is an interface that defines the behavior of a controller that displays enterprise objects using an EODisplayGroup.

Instance Methods

controllerDisplayGroup

```
public abstract com.webobjects.eointerface.EODisplayGroup controllerDisplayGroup()
```

Returns a display group containing the receiver—an EOController or subclass. This display group can be used to connect controller methods to the user interface.

INTERFACE EObjectDisplay

displayGroup

```
public abstract com.webobjects.eointerface.EODisplayGroup displayGroup()
```

Returns the display group the receiver uses to display and edit the properties of its enterprise objects.

editingContext

```
public abstract com.webobjects.eocontrol.EOEditingContext editingContext()
```

Returns the editing context the receiver uses to manage the graph of its enterprise objects.

entityName

```
public abstract String entityName()
```

Returns the name of the entity that describes the enterprise objects the receiver displays with its display group.

This Apple manual was written, edited, and composed on a desktop publishing system using Apple Macintosh computers and FrameMaker software.

Line art was created using Adobe™ Illustrator and Adobe Photoshop.

Text type is Palatino® and display type is Helvetica®. Bullets are ITC Zapf Dingbats®. Some elements, such as program listings, are set in Adobe Letter Gothic.

COLOPHON