
Dates and Times Programming Guide for Core Foundation

[Core Foundation](#) > [Data Management](#)



2005-08-11



Apple Inc.
© 2005 Apple Computer, Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple and the Apple logo are trademarks of Apple Inc., registered in the United States and other countries.

Times is a registered trademark of Heidelberger Druckmaschinen AG, available from Linotype Library GmbH.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

Introduction to Dates and Times Programming Guide for Core Foundation 7

Who Should Read This Document 7

Organization of This Document 7

Date Representations 9

CFAbsoluteTime 9

CFTimeInterval 9

CFGregorianCalendar 9

CFGregorianCalendarUnits 10

CFDate 10

Time Zones 11

Using Dates 13

Document Revision History 15

Listings

Using Dates 13

- Listing 1 Creating a NSDate object 13
- Listing 2 Comparing two NSDate objects 13
- Listing 3 Working with Gregorian dates 13

Introduction to Dates and Times Programming Guide for Core Foundation

Core Foundation provides date and time objects you can use without depending on operating-system internals.

Who Should Read This Document

You should read this document to learn about representations of date and time in the Core Foundation framework, and how to use them.

Organization of This Document

This topic discusses the different date and time representations, issues with time zones, and contains examples on how to use date and time objects:

- [“Date Representations”](#) (page 9)
- [“Time Zones”](#) (page 11)
- [“Using Dates”](#) (page 13)

Date Representations

Core Foundation allows you to work with five different representations of time:

- `CFAbsoluteTime`, a specific point in time relative to 1 January 2001 00:00:00 GMT
- `CFTimeInterval`, an interval of time in seconds
- `CFGregorianCalendarDate`, a specific point in time represented using the Gregorian calendar
- `CFGregorianCalendarUnits`, an interval of time in one or more of the units used in the Gregorian calendar
- `CFDate`, an absolute time in the format of a Core Foundation opaque type

CFAbsoluteTime

`CFAbsoluteTime` is useful when you need to refer to a specific point in time. A `CFAbsoluteTime` value represents time as a number of seconds relative to the reference date of 1 January, 2001 00:00:00 GMT. A positive value represents a date after the reference date, a negative value represents a date before it.

Absolute time can be confusing at first because an absolute time value is literally a time interval (the number of seconds since the reference date), but it is interpreted as a specific instant in time. For example, the absolute time `-32940326` indicates both a date and time—December 16th, 1999 at 17:54:34. An absolute time value cannot be used to refer to a date or a clock time independently, it always includes both.

`CFAbsoluteTime` is implemented as a `double` and can be compared with another absolute time using the standard C comparison operators.

CFTimeInterval

`CFTimeInterval` is appropriate when you need to measure duration. A `CFTimeInterval` represents elapsed time in seconds. As with `CFAbsoluteTime`, a `CFTimeInterval` is implemented using the C type `double` and so you can compare two `CFTimeInterval` values using the standard C comparison operators.

CFGregorianCalendarDate

`CFGregorianCalendarDate` represents time using the Gregorian calendar that has been in general use in Europe and the Western Hemisphere since 1582. A `CFGregorianCalendarDate` is implemented as a C structure with separate fields for years, months, days, hours, minutes, and seconds. You can check any or all of the fields of a `CFGregorianCalendarDate` for validity. A Gregorian date can also be converted to and from an absolute time.

CFGregorianUnits

CFGregorianUnits is analogous to a CTimeInterval in that it represents a duration rather than a specific point in time. Like CFGregorianDate, CFGregorianUnits is implemented as a C structure, but the data types of the fields are different to allow for larger values. For example, a CFGregorianDate will never have more than 52 weeks, or 24 hours, so the fields of the CFGregorianDate structure are implemented using the smallest data type appropriate for its maximum value. Because CFGregorianUnits is intended to represent arbitrary time intervals, it is implemented with 32 bit integers (except for seconds, which is of type `double` to allow for fractional values).

CFDate

If you need to place a date in a Core Foundation property list, it must be of type CFDate. A CFDate object is simply an absolute time “wrapped” as a Core Foundation opaque type. A Gregorian date must first be converted to an absolute time, and then it can become a CFDate object. A CFDate object can be compared with another CFDate using a standard Core Foundation comparison function. Note that a CFDate can only be created with an absolute time, CTimeInterval values are not supported. Use a CFNumber to wrap ordinary floating point values like a CTimeInterval. CFDate objects are immutable.

Time Zones

CFDate objects are all expressed as Greenwich Mean Time, or GMT. In order to convert a GMT date to your local time you must use a CTimeZone object. A CTimeZone represents a geopolitical region that has some temporal offset, either plus or minus, from GMT as well as an abbreviation—such as “PST”. In addition to familiar abbreviations, time zones are also named by country and region. For example the United States spans these times zones:

- USA Eastern: -5 hours GMT
- USA Indiana East: -5 hours GMT
- USA Central: -6 hours GMT
- USA Mountain: -7 hours GMT
- USA Arizona: -7 hours GMT
- USA Pacific: -8 hours GMT
- USA Alaska: -9 hours GMT
- USA Aleutian: -10 hours GMT
- USA Hawaii: -10 hours GMT

To make matters even more complex, any region may or may not be on Daylight Savings Time (DST).

In order to properly convert GMT to local time, you have to know which time zone you are in and if DST is in effect. Core Foundation uses time zone names, abbreviations, GMT offset, and DST information for a particular time zone obtained from a public-domain database maintained at <ftp://elsie.nci.nih.gov/pub/>. This database contains information representing the history of local time for many representative locations around the globe. The database is updated periodically to reflect changes made to GMT offsets and daylight-saving rules by political entities.

For examples of how to use CFDate and CTimeZone, see the [“Using Dates”](#) (page 13).

Using Dates

This task contains examples on creating, comparing, and converting dates. [Listing 1](#) (page 13) shows you how to get the current absolute time and convert it into a `CFDate` object.

Listing 1 Creating a `CFDate` object

```
CFAbsoluteTime    absTime;
CFDateRef         aCFDate;

absTime = CFAbsoluteTimeGetCurrent();
aCFDate = CFDateCreate(kCFAllocatorDefault, absTime);
```

To compare two dates, use the compare function `CFDateCompare` as shown in [Listing 2](#) (page 13).

Listing 2 Comparing two `CFDate` objects

```
// Standard Core Foundation comparison result.
CFComparisonResult result;

// Create two CFDates from absolute time.
date1 = CFDateCreate(kCFAllocatorDefault, CFAbsoluteTimeGetCurrent());
date2 = CFDateCreate(kCFAllocatorDefault, CFAbsoluteTimeGetCurrent());

// Pass NULL for the context param.
result = CFDateCompare(date1, date2, NULL);

switch (result) {
    case kCFCompareLessThan:
        printf("date1 is before date2!\n");
        break;
    case kCFCompareEqualTo:
        printf("date1 is the same as date2!\n");
        break;
    case kCFCompareGreaterThan:
        printf("date1 is after date2!\n");
        break;
}
```

The `CFDateCompare` function performs exact comparisons, which means it detects sub-second differences between dates. You might want to compare dates with a less fine granularity. For example, you might want to consider two dates equal if they are within one minute of each other. This can be accomplished by simply converting the `CFDates` to absolute time and comparing the two floating-point values using your fuzziness factor. To compare Gregorian units like month or week, you can convert both `CFDates` to `CFGregorianCalendar` and compare the appropriate fields. Converting absolute time to and from Gregorian dates is quite simple. [Listing 3](#) (page 13) demonstrates how to do this.

Listing 3 Working with Gregorian dates

```
Boolean            status;
```

Using Dates

```
CFGregorianCalendar    gregDate;
CFbsoluteTime        absTime;

// Construct a Gregorian date.
gregDate.year = 1999;
gregDate.month = 11;
gregDate.day = 23;
gregDate.hour = 17;
gregDate.minute = 33;
gregDate.second = 22.7;

// Check the validity of the date.
status = CFGregorianCalendarIsValid(gregDate, kCFGregorianCalendarAllUnits);
printf("Is my Gregorian date valid? %d\n", status);

// Convert the Gregorian date to absolute time.
absTime = CFGregorianCalendarGetAbsoluteTime(gregDate, NULL);
printf("The Absolute Time from a Gregorian date is: %d\n", absTime);
```

Document Revision History

This table describes the changes to *Dates and Times Programming Guide for Core Foundation*.

Date	Notes
2005-08-11	Changed title from "Dates and Times." Added links to formatting references.
2003-01-17	Converted existing Core Foundation documentation into topic format. Added revision history.

