
QTMovieLayer Class Reference

[QuickTime](#) > [Cocoa](#)



2009-04-06



Apple Inc.
© 2009 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

.Mac is a registered service mark of Apple Inc.

Apple, the Apple logo, Cocoa, eMac, Mac, Mac OS, Objective-C, and QuickTime are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

QTMovieLayer Class Reference 5

- Overview 5
- Tasks 5
 - Creating Movie Layers 5
- Class Methods 6
 - layerWithMovie: 6
- Instance Methods 6
 - initWithMovie: 6
 - movie 7

Document Revision History 9

Index 11

QTMovieLayer Class Reference

Inherits from	CALayer : NSObject
Conforms to	NSCoding (CALayer) CAMediaTiming (CALayer) NSObject (NSObject)
Framework	/System/Library/Frameworks/QTKit.framework
Availability	Available in QuickTime 7.2.1 and later.
Declared in	QTMovieLayer.h
Related sample code	CALayerEssentials Core Animation QuickTime Layer

Overview

This class provides a layer into which the frames of a `QTMovie` can be drawn, and is intended to provide support for Core Animation, that is, drawing the contents of a movie into a layer. `QTMovieLayer` renders a `QTMovie` within a layer hierarchy. Note that this class requires rendering using visual contexts. Do not attempt to directly modify the `contents` property of an `QTMovieLayer` object. Doing so will effectively turn it into a regular `CALayer`.

Tasks

Creating Movie Layers

- + `layerWithMovie:` (page 6)
Creates an autoreleased `QTMovieLayer` associated with the specified `QTMovie` object.
- `initWithMovie:` (page 6)
Creates a `QTMovieLayer` associated with the specified `QTMovie` object.
- `movie` (page 7)
Returns the movie associated with a `QTMovieLayer` object.

Class Methods

layerWithMovie:

Creates an autoreleased `QTMovieLayer` associated with the specified `QTMovie` object.

```
+ (id)layerWithMovie:(QTMovie *)movie
```

Parameters

movie

The QuickTime movie with which to create an autoreleased QuickTime layer object.

Discussion

By default, the movie starts playing immediately at rate 1.0 from the beginning of the movie. These default characteristics can be modified by setting layer properties or movie properties.

Availability

Mac OS X v10.5 and later.

Related Sample Code

CALayerEssentials

Core Animation QuickTime Layer

Declared In

`QTMovieLayer.h`

Instance Methods

initWithMovie:

Creates a `QTMovieLayer` associated with the specified `QTMovie` object.

```
- (id)initWithMovie:(QTMovie *)movie
```

Parameters

movie

The QuickTime movie with which to initialize the QuickTime layer object.

Discussion

By default, the movie starts playing immediately at rate 1.0 from the beginning of the movie. These default characteristics can be modified by setting layer properties or movie properties.

Availability

Mac OS X v10.5 and later.

Declared In

`QTMovieLayer.h`

movie

Returns the movie associated with a QTMovieLayer object.

- (QTMovie *)movie

Availability

Mac OS X v10.5 and later.

Declared In

QTMovieLayer.h

Document Revision History

This table describes the changes to *QTMovieLayer Class Reference*.

Date	Notes
2009-04-06	Fixed warning information. Added parameter descriptions. Minor fixes.
2009-03-04	Added explanation of layer hierarchy; fixed class inheritance path.
2007-10-31	Fixed error in description of inheritance class path.
2007-07-19	New document that describes the Objective-C class for creating a QuickTime movie layer.

REVISION HISTORY

Document Revision History

Index

I

`initWithMovie:` instance method [6](#)

L

`layerWithMovie:` class method [6](#)

M

`movie` instance method [7](#)